MIL-F-45557B

3 January 1975
SUPERSEDING
MIL-F-45557A
28 February 1969

MILITARY SPECIFICATION

FEEDER, AUTOMATIC GUN: M3A1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of gun-driven feed mechanism afor ammunition belted with M17 links for use on the 20mm, M61 and M61A1 automatic guns. The feeder pulls in the link-belted ammunition, strips the ammunition from the links, ejects the empty links, and feeds the de-linked ammunition into the gun. The feeder includes an electrically operated declutching feature for clearing the gun of ammunition, and switches for a rounds counter and a last round indicator.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of incitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-W-13855	-	Weapons, Small Arms and Aircraft Armament Subsystems, General Specification For.
MIL-P-14232	-	Parts, Equipment and Tools For Army Materiel, Packaging and Packing Of.
MIL-I-45607		Inspection Equipment, Acquisition, Maintenance and Disposition Of.

Military

MIL-STD-105		Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109	-	Quality Assurance Terms and Definitions.
MIL-STD-454	-	Standard General Requirements for Electronic Equipment.

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

DRAWINGS

Rock Island Arsenal
F7791085 - Feeder, Automatic Gun: M3A1.
IEL7274647 - Index of Inspection Equipment Lists.

(Product drawings referenced in this specification form a part of Drawing F7791085; Acceptance inspection drawings form a part of IEL7274647.)

Rock Island Arsenal
P5910555 - Packaging Data Sheet for Feeder, Automatic Gun: M3A1 w/Attaching Parts.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article. Requirements for submission of the first article shall be as specified in the contract (see 6.1). Unless otherwise specified (see 6.1), the first article shall include the pilot pack.

3.2 Materials, construction and design. Feeders and parts shall conform to the materials, construction and design requirements specified herein, on Drawing F7791085 and in MIL-W-13855.

3.2.1 Actuating shaft. The actuating shaft shall move through its full range of travel in the feeder shaft without binding to actuate the collar assembly.

3.2.2 Anti-backlash Pins. The anti-backlash pins shall be retained on the feeder housing by the spring pins and shall be held end returned to the extended position by the springs. They shall function through their full range of travel under spring action without binding.

3.2.3 Clevis. The clevis shall be retained on the support by the safety wired pin and shall move through its full range of travel without binding to actuate the actuating shalt.

3.2.4 Clevis and solenoid support. The clevis and solenoid support shall be fastened securely to the feeder housing by the bolts so that there shall be no relative movement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

3.2.5 Collar assembly. The collar assembly shall move through its full range of travel on the feeder shaft without binding to engage or disengage the feeder gear or the stop plate as evidenced by feeder operation.

3.2.6 Feeder gear assembly. The feeder gear assembly shall be retained securely on the feeder shaft by the lock nut. The anti-backlash arms shall be retained on the feeder gear and stops by the spring pins. The anti-backlash arms and stops shall function through their full range of travel under spring action without binding and shall be held normally and returned to the extended position by spring actions. The feeder gear assembly shall rotate without binding with the feeder in the declutched position.

3.2.7 Feeder shaft spring. The feeder shaft spring shall be fastened securely to the feeder spring plate by the screw and self locking nut. The feeder shaft spring shall hold the round against the feeder strippers when the feeder is operated.

3.2.8 Guides, strippers, and retainers. Guides, strippers, and retainers shall be fastened securely to the housing. There shall be no relative movement of these parts and they shall perform their respective guiding, stripping, and retaining functions When the feeder is operated.

3.2.9 Lever shaft. The lever shaft shall be retained on the clevis by the spring pin and shall move through its full range of travel under spring action without binding.

3.2.10 Traveling ring. The traveling ring shall rotate on the traveling ring cam without binding.

3.2.11 Traveling ring cam. The traveling ring cam shall rotate on the feeder shaft without binding.

3.2.12 Timing pin. The timing pin shall engage the timing hole in the drive gear to correctly position the feeder gear for mounting the feeder on a properly timed gun. The timing pin shall move through its full range of travel without binding arid shall be returned and held in the retracted position by action of the spring.

3.2.13 Connector. The connector shall be fastened securely to the connector bracket by the screws and nuts so that there shall be no relative movement. The insulation sleeves shall be securely retained in the connector.

3.2.14 Clamps. The clamps shall be fastened securely to the feeder housing by the screws and the clamps shall secure the sleeved wires from the switches to the connector so that there shall be no relative movement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

3.2.15 Rounds counter switch assembly. The rounds counter switch assembly shall be fastened securely to the feeder housing by the screws. The switch assembly shall perform its electrical function as a rounds counter and last count indicator when the feeder is operated using dummy cartridges.

3.2.16 Switch shoe. The switch shoe shall be retained on the feeder housing by the pins and shall be held and returned to the extended position by the spring. The switch shoe shall move through its full range of travel under spring action without binding and shall perform its function to operate the last round indicator switch when the feeder is operated using dummy cartridges.

3.2.17 Solenoid assembly. The solenoid assembly shall be fastened securely to the support by the solf locking nuts. The armature plate shall rotate through its full range of travel without binding.

3.2.17.1 Solenoid operation. The solenoid shall actuate the feeder actuating shaft to declutch the feeder when 22 to 32 volts direct current is applied to the solenoid. When the solenoid is de-energized it shall allow the feeder actuating shaft to return to its normal extended position under spring action of the lever shaft.

3.2.17.2 Solenoid dielectric withstanding voltage. The solenoid shall withstand 1,200 volts root mean square at frequency of 60 Hertz for 5 seconds without disruptive discharge or deterioration.

3.2.17.3 Electrical circuit. The electrical circuit wiring of the solenoid and switches to the connector shall be in accordance with the wiring diagram specified on the applicable drawing.

3.2.17.4 Insulation sleeves. The insulation sleeves and wire shall be securely retained in the connector, and fastened securely to the feeder housing in accordiance with the explicable drawing.

3.2.17.5 Soldered connections. The lead wires from the switches and the solenoid shall be securely soldered to the connector pins in accordance with the applicable drawing.

3.2.18 Timing. The relationship of the sprockets to the feeder gear shall be within the limits specified on the applicable drawing and shall provide for smooth transfer of rounds from the ammunition belt to the gun hand-off position.

3.2.19 Torque. The torque required to rotate the feeder shaft in the feeder assembly without ammunition shall not be more than 20-ounce-inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

3.3 Performance Characteristics.

3.3.1 Functioning. The feeder shall operate using Government Standard 20MM, M51A1 dummy cartridges or M55A2 ball cartridges without stoppage or breakage of parts attributable to the feeder. The feeder shall be capable of stripping all rounds from the links, feed the stripped rounds into the gun eject the empty links completely from the feeder, perform its clutching and declutching function, count rounds, and indicate last round. Testing shall be as specified in 4.5.3.2.

3.3.2 Endurance. The feeder shall be capable of feeding 12,000 rounds for endurance with at least 120 declutching operations, using Government standard 20MM, M51A1 dummy cartridges or M55A2 ball cartridges. There shall be no stoppage or malfunction attributable to the feeder. Testing shallbe as specified in 4.5.3:3.

3.4 Interchangeability. Unless otherwise specified on the drawings, all parts shall be interchangeable. Testing shall be as specified in 4.5.3.4.

3.5 Marking. Feeders and parts shall be clearly marked in accordance with the applicable drawings and MIL-W-13855. Each feeder shall be identifiedby serial numbers assigned by the procuring activity (see 6.1].

3.6 Workmanship. Workmanship shall be in accordance with MIL-W-13855.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.3 Classification of inspection. the inspection requirements specified herein are classified as follows:

a. First article inspection (see U.A).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. The first article (initial production unit(s) shall be submitted for inspection in accordance with the contract (see 6.1). The first article shall be representative of the production processes to be used during quantity production. The first article shall be subjected to the quality conformance inspection specified herein and such ether inspections as necessary to determine that all the requirements of the contract have been met.

4.5 Quality conformance inspection.

4.5.1 Inspection lot. The formation, size and presentation of inspection lots of feeders shall be in accordance with MIL-STD-105 and MIL-W-13855. Feeders shall be assembled from lots of component parts that have met all inspection requirements specified herein. Endurance test lot size shall be as specified in 4.5.3.3.

4.5.2 Examination.

4.5.2.1 Component parts and concurrent repair parts. Examination of component parts and concurrent repair parts shall be performed in accordance with the criteria specified in the contract (6.1). The contractor's examination of these parts shall be accomplished prior to their assembly into the end item or submission for acceptance as repair parts.

4.5.2.2 Feeders. Visually and manually examine each feeder to determine conformance with the material, construction and design requirements of 3.2 and the applicable requirements of 3.2.1 through 3.2.17 and 3.2.17.4. Each step in the examination shall include a visual examination for proper cleaning and presence of the specified protective coating and to determine the general quality, completeness of manufacture, assembly, clarity and legibility of markings and workmanship. The examination provisions shall be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Reinspections these characteristics on the completed product is not required provided assurance exists that the characteristic has not been changed, degraded or damaged by subsequent manufacturing, assembly or handling and that adequate inspection records are maintained. Feeders failing to meet the requirements shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.5.2.2.1 Solenoid operation. Feeders shall be examined for solenoid operation requirement (see 3.2.17.1) after the solenoid dielectric withstanding voltage test by applying 22 and 32 volts direct currant to the solenoid to assure that the actuating shaft is operated to declutch the feeder and that when the solenoid is de-energized it allows the actuating shafts to return to its normal extended position under spring action. (Do not energize the solenoid for more than 15 seconds.)

4.5.2.2.2 Solenoid dielectric withstanding voltage. Feeders shall be examined for solenoid dielectric withstanding voltage requirements (see 3.2.17.2) rising a current limited high potential tester in accordance with Drawing A7273225 and an electronic timer in accordance with Drawing A7273227. The high potential voltage shall be applied for five seconds between the coil terminals and grounded metal parts.

4.5.2.2.3 Electrical circuit. Feeders shall be examined for continuity (see 3.2.17.3 using a volt-ohm-milliameter tester in accordance with Drawing A7273226. Continuity of the solenoid circuit shall be examined by applying the low voltage across connector pins "C" and "D". Continuity of the rounds counter switch shall be examined by applying the low voltage across connector pins "B" and "E" and rotating the feeder shaft to assure that the stitch circuit closes and remains closed f'or 160 degrees ± 10 degrees for each shaft revolution. Continuity of the last round indicator shall be examined by applying the low voltage across connector pins "A" and "B" and actuating the switch shoe to assure that the circuit is open when the switch shoe is in the raised position using dummy ammmition, and that there is no continuity when the dummy ammunition is removed and the switch shoe is in the extended position. During each check for continuity, the lead wires shall be manipulated and any variation in the ohmmeter scale shall be considered as attributable to a faulty connection.

4.5.2.2.4 Soldered connections. Examine feeders for securely soldered lead wires (see 3.2.17.5) in the following manner:

a Remove the two screws and clamps that secure the insulation sleeve to the rear coupling of the connector.

b Draw the insulation sleeve rearward and uncouple the connector.

c Draw the grommet follower and the grommet rearward to expose the soldered connection.

d Examine the soldered connections in accordance with the visual and mechanical examination specified MIL-STD-454, Requirement 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

e Reassemble the connector.

4.5.2.2.5 Timing. Feeders shall be examined for timing requirement (see 3.2.18) using the inspection equipment in accordance with Drawing F273739. The gage shall be attached to the feeder and with the feeder gear engaged to the shaft, the feeder gear shall be rotated to engage the index pin into the feeder index hole. The gage timing plunger shall then be depressed between the nearest gear teeth as the index pin is released. With the feeder gear in this position the gage shall indicate whether the timing requirement has been met.

4.5.2.2.6 Torque test. Feeders shall be examined for torque requirement (see 3.2.19) using the inspection equipment in accordance with Drawing D7273809. The feeder shall be held in a horizontal position,the feeder gear fully engaged with the feeder shaft, and the feeder shaft spring loosened when the inspection equipment is attached and the feeder gear and shaft rotated.

4.5.3 Testing

4.5.3.1 Failure data. Unless otherwise specified herein, all tests shall be conducted on a complete feeder. If test requirements cited herein are not met, acceptance of feeders shall be deferred and the contractor shall accomplish es applicable, the following actions:

a. Conduct a failure analysis study performing a dimensional physical and visual examination of the components which are suspected to be the cause of failure or malfunction.
b. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect(s) in future production.
c. Examine feeders, partially assembled feeders, and components (including components end subassemblies at in-process or final assembly) to insure that material containing the same defect is purged from the inventory and not presented to the Goverment for acceptance.
d. Submit the results of the failure analysis and the corrective actions taken to the Government for review and approval prior to submitting a reconditioned lot or reconditioned feeder for retest.

4.5.3.2. Function testing. Each feeder shall be tested for functioning (see 3.3.1) using the test method specified in 4.6.1. Feeders failing to meet the requirements shell be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.5.3.3 Endurance testing.

4.5.3.3.1 Lot size. The initial endurance test lot size shall consist of the initial production; subsequent endurance test lot sizes shall consist of 100 feeders.

4.5.3.3.2 Procedure. One feeder shall be selected from each endurance lot and shall be tested for endurance (see 3.3.2) using the test methods specified in 4.6.2. Failure of the feeder to meet the requirements shall be cause for rejection of the represented lot.

4.5.3.4 Interchangeability testing.

4.5.3.4.1 In plant.

4.5.3.4.1.1 Feeders. A sample of three feeders shall be selected from each month's production and tested for interchangeability (see 3.4) using the test method specified in 4.6.3.1.1. Feeders taken for interchangeability testing shall have been found satisfactory in all examinations and tests. The three feeders shall be inspected fo and shall comply with the requirement for timing and torque after interchange of parts (see 4.5.2.2.5 and 4.5.2.2.6). In addition, the feeders shall be tested for functioning requirements after interchange of parts using the test methods specified in 4.6.1. Failure of feeders to meet the requirements of the interchangeability test shall be cause for rejection of the represented lot. Sample size and test methods shall be the same for retest.

4.5.3.4.1.2 Concurrent repair parts. A sample of two parts from each inspection lot of concurrent repair parts shall be subjected to the interchangeability test specified in 4.6.3.1.2. Failure of any part to meet the requirements shall be cause for rejection of the represented lot. A sample of double the number of parts used in the original test shall be tested from each reconditioned lot using the test method specified in 4.6.3.1.2.

4.5.3.4.2 Interplant. When feeders are manufactured concurrently by more than one contractor, each contractor shall forward monthly three feeders for the interplant interchangeability test specified in 4.6.3.2 (see 6.1). The contractor will be informed of any failure of the feeders to meet prescribed requirements. Upon completion of testing agency inspection, samples may be commercially packaged and will be returned to the contractor for repackaging in accordance with procurement documents at the contractor's expense.

4.5.3.5 Component parts and concurrent repair parts testing. Raw material testing, part testing, and certification shall be performed in accordance with the criteria specified in the contract (see 6.1). This all include chemical analysis and physical tests of materials and tests of protective finish, heat treatment, bonding and function of parts as applicable. The contractor shall accomplish these tests prior to assembly of parts into the end item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

4.5.4 Packaging examination and testing. Unless otherwise specified (see 6.1), the packaging examination and testing shall be in accordance with MIL-P-14232;

4.5.5 Certification. Unless otherwise specified, the contractor shall be responsible for testing necessary to accomplish certification. For each inspection lot of feeders, the contractor shall provide the Government representative with certified statements of compliance with applicable drawings and specifications of the following materials and processes specified on Drawing F7791085.

4.5.6 Inspection equipment.

4.5.6.1 Unless otherwise specified in the procurement documents (see 6.1), responsibilities for acquisition maintenance and disposition of measuring and testing equipment prescribed on lists contained on the Index of Inspection Equipment Lists, Drawing IEL7274647, and for all other inspection equipment required to perform inspection required by applicable specifications shall be in accordance with MIL-I-45607.

4.5.6.2 Accuracy of standard meeting equipment. When commercial and modified commercial inspection equipment is used, it must be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

4.6. Test methods.

4.6.1 Functioning test. Feeders shall be tested for functioning requirements using slave M61 or M61Al guns or contractor designed Government approved test equipment which simulates the function of the gun. Two belts of 100 rounds each of linked ammunition shall be used for testing each feeder. The feeders shall be accelerated up to a feeding steady state rate of 4,000 to 4,400 rounds per minute before the feeder is declutched at approximately the 40th and 80th round of each belt. The feeder shall not be declutched at fire-out (without ammunition in feeder). The feeder solenoid shall be energized to declutch the feeder at the instant power to the drive is removed, and shall be deenergized after the gun comes to a complete stop. The feeder solenoid shall not be energized for more than 15 seconds at any one time. After feeding each belt of ammunition the recorded data shall be checked to assure proper operation of the rounds counter switch, the last round indicator Switch, and the declutchtng mechanism. Instrumentation shall be of the contractor's design and shall be such that gun speed curve, timing marks, primer impulse, and feeder declutching actuation is taken and recorded concurrently for use in computing required data for each feeder.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T03:24Z
Check the source to verify that this is the currentversion before use.

4.6.2 Endurance test.

4.6.2.1 Feeders shall be tested for endurance requirement using slave M61 and M61A1 guns or contractor designed Government approved test equipment which simulates the function of the gun.

4.6.2.2 Linked ammunition in belts of 100 rounds each shallbe used. The feeders shall be accelerated up to a feeding steady state rate of 4,000 to 4,400 rounds per minute before the feeder is declutched approximately in the middle of each belt. The feeder shall not be de-clutched at fire-out (without ammunition in feeder). The feeder solenoid shall be energized to declutch the feeder at the instant power to the drive is removed, and shall be deenergized after the gun comes to a com-plete stop. The feeder solenoid shall not be energized for more than 15 seconds at any one the. Feeders shall be checked after each 1,500 rounds for correct timing and loosening of parts. All loosened parts shall be retightened and recorded. In addition, the feeders shall be cleaned and lubricated after each 1,500 rounds and at the end of each day's testing. The bearings and electrical parts shall be protected from contamination by cleaning materials. Instrumentation shall be in accordance with 4.6.1. Data shall be taken and recorded from one belt in each 1,500 round series for use in computing required data.

4.6.2.3 Endurance tested feeders shall be disposed of as specified in procurement documents (see 6.1).

4.6.3 Interchange of parts.

4.6.3.1 In plant.

4.6.3.1.1 Feeders. Feeders shall be tested for interchange of parts by disassembling and then reassembling parts using the parts and prearranged system specified below. Interchange of parts shall be accomplished by dividing the parts of each feeder into three groups of nonmating parts as shown below and distributing the groups into three different trays until each tray contains parts for a complete feeder. Groups of parts from the first feeder shall be taken in order and placed in trays one through three; groups of parts from the second feeder shall be taken in order and placed in two, three and one; groups of parts from the third feeder shall be taken in order and placed in trays three, one, and two. Commercial parts such as screws, spring pins, etc., shall be placed in the same tray as their mating or associate part. Any commercial part rendered unserviceable by disassembly shall be replaced without penalty to the interchangeability test. The feeders using only those parts which are in the same tray.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

Groups of non-mating parts

Group I

Bearing, ball (7794616)
(2 required)
Cam, counter (7790490)
Clevis (7794555)
Collar assembly (7794556)
Housing and guides (w/remaining
parts attached) (7791087)
Ring, traveling (7794562)
Spacer, feeder shaft (7791090)
Spring, helical, compression
(lever shaft) (7794569)
Spring, helical, torsion
(switch shoe) (779459)
Sprocket, rear (7791095)

Group II

Arm, anti-backlash (7794550)
(w/stop, arm 7794574 attached)
(5 required)
Pin, pivot (7794597)
Shaft, feeder (7791565)
Shaft, lever (7794565)
Spacer, feeder shaft (7791089)
Spring, feeder shaft (7268573)
Spring, helical, compression
(stop, arms) (7794570)
(5 required)
Stripper, front (7794608)

Group III

Bearing, ball (7794618)
Cam, traveling ring (7794554)
Gear, feeder (7794558)
Shaft, actuating (7794563)
Shoe, switch (7790460)
Spacer, feeder shaft (7794624)
sprocket, front (7791094)
stripper, feeder (7268576)
Support, clevis and solenoid (7794575)

4.6.3.1.2 Concurrent repair parts. Concurrent repair parts shall be tested for interchangeability requirement by disassembling two feeders, previously tested in 4.6.3.1.1, as necessary and then reassembling them using the concurrent repair, parts. No hand refinement of parts will be allowed, and the feeders shall operate and function properly. This test may be performed independently of the feeder interchangeability test specified in 4.663.1.1, and at more frequent intervals using accepted feeders taken from current production.

4.6.3.2 Interplant. Feeders to be subjected to the interplant interchangeability test shall be inspected for timing, (see 4.5.2.2.5) torque, (see 4.5.2.2.6) and functioning requirements using the inspection methods specified in 4.6.1 to assure proper operation before parts are interchanged. Feeders shall be interchanged in a manner similar to the detailed plan specified in 4.6.3.1.1 except that when

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

disassembling, every other feeder shall be one produced by a different manufacturer. After assembly, the feeders shall be inspected for timing, torque, and functioning requirements using the inspection as specified herein. Before feeders are returned to the contractors, the original parts shall be reassembled to their respective feeders.

5. PREPARATION FOR DELIVERY.

5.1 Pilot pack. The pilot pack shall consist of a complete feeder packaged in accordance With Packaging Data Sheet P5910555 for the level of protection specified in the contract (see 6.1), packed level C and forwarderd in accordance with 3.1.

5.2 Preservation, packaging, packing and marking. Feeders shall be preserved, packaged, packed, and marked in accordance with packaging data Sheet P5910555 for the level of protection specified in the contract (6.1).

5.3 Repair parts. Repair parts shall be preserved, packaged, packed, and marked in accordance with the packaging Data Sheet or other requirements for the level of protection specified in the contract (see 6.1).

6. NOTES

6.1 Ordering date. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Lists of drawings and specifications pertinent to the feeder, showing applicable revision dates.
c. Inspection criteria for components (see 4.5.2.1 and 4.5.3.5).
d. Shipping instructions for first article and pilot pack (see 3.1 and 5.1).
e. List of acceptance inspection equipment to be furnished the contractor (see 4.5.6.1) and responsibilities for other Government property to be furnished the contractor.
f. Packaging examination and testing, if different (see 4.5.4).
g. Shipping instructions for feeders and parts when an interplant interchangeability test is required (see 4.5.3.4.2).
h. Disposition of endurance tested feeders (see 4.6.2.3).
i. Selection of applicable levels of preservation, packaging, packing, and marking (see 5.1 and 5.2).
j. Packaging of repair parts (see 5.3).
k. Block of serial numbers (see 3.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

6.3 Contract data requirements. When warranted, requirements for reports of examination and testing (e.g. functioning, endurance and interchangeability tests, etc.) shall be specified on a DD Form 1423 included in the contract.

6.4 Unless otherwise specified (see 6.1) the contract should specify the application of MIL-I-45607 and MIL-C-45662 on the management Control Summary List DDForm 1660.

6.5 When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208 as appropriate, on the Management Control Systems Summary.List DDForm 1660.

Custodians:
Army - WC
Navy - OS
Air Force - 84

Review activities:
Navy - OS
Air Force - 84

User activities:
Navy - AS, MC

Reparing activity:
Army - WC

Project number:
1005-0519

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:24Z
Check the source to verify that this is the current version before use.