INCH-POUND

MIL-L-45589
AMENDMENT 1
23 January 2003

MILITARY SPECIFICATION

LAUNCHER, GRENADE, 40MM; M79

MIL-L-45589 was inactivated after 1 September 1997 for new design.

This amendment forms a part of MIL-L-45589, dated 2 February 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, Specifications, delete MIL-W-13855 in its entirety.

2.1, Delete MIL-STD-105 in its entirety and substitute "MIL-STD-1916 – DOD Preferred Methods for Acceptance of Product"

PAGE 2

2.1, Drawings:

Delete "IEL7274616" in its entirety.

Delete parenthetical statement in its entirety and substitute the following:

"(Part drawings referenced in this specification form a part of Drawing F7790600)"

Add the following drawings:

"7318984 - Gage Indicator
7799086 - Gage, Force Indicator
8440196 - Fixture, Sight Alignment
8440920 - Cylinder, Pressure"

PAGE 4

3.7, Delete in its entirety.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:28Z
Check the source to verify that this is the current version before use.

PAGE 9

3.10, Delete in its entirety and substitute the following:

"3.10 Workmanship. Workmanship and finish shall be in accordance with the highest grade practice used in manufacturing military weapons. Finished items and parts shall not exhibit poor material and processing such as seam, laps, laminations, cracks, visible steps, sharp edges, nicks, scratches, burrs, deformations and missing operations which may affect serviceability, functioning, operation, appearance or safety. Fins and other extraneous metal shall be removed from cast or forged parts. Hammering to shape, salvage operations (including repair by welding) or other similar practices shall not be permitted without prior approval of the contracting officer."

4.4.1.2, Delete in its entirety and substitute the following:

"4.4.1.2 Parts and packaging. The formation, size, and presentation of inspection lots of parts and packaging shall be in accordance with MIL-STD-1916."

PAGE 11

4.4.2.2.4b, Add "Drawing 7799086" at the end of the sentence.

PAGE 14

4.4.3.5, Delete subparagraphs a, b, and c in their entirety and substitute the following:

"(a) Torque of screws (see Drawing E7790600)
(b) Pin, Straight, Headless (see Drawing A7790637)"

PAGE 15

4.4.4.1, Delete in its entirety and substitute the following:

"4.4.4.1 Unless otherwise specified in the contract (see 6.1), responsibilities for acquisition, maintenance, and disposition of inspection and test equipment prescribed shall be in accordance with MIL-I-45607 and MIL-C-45662."

4.5.1:

Line 3, delete drawing "C7218984" and substitute "C7318984"

Line 6, delete drawing "B5039436" and substitute "B8440920"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:28Z
Check the source to verify that this is the current version before use.

PAGE 18

4.5.6.1, Delete the first sentence in its entirety and substitute the following:

"Launchers shall be tested for sight alignment after the firing tests using the sight alignment fixture conforming to Drawing F8440196 in accordance with applicable instructions."

PAGE 19

4.5.7, Second sentence, delete in its entirety and substitute the following:

"Approved inspection equipment shall be used."

Custodian:
Army – AR
Navy – OS
Air Force – 99

Preparing activity:
Army – AR

(Project 1010 - 0147)

Reviewer activities:
Navy – OS
Air Force – 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:28Z
Check the source to verify that this is the current version before use.