MILITARY SPECIFICATION

LINK, CARTRIDGE, 20MM: XM24

This amendment forms a part of Military Specification MIL-L-45594(WC), dated 19 June 1970.

Change "WC" to "AR" wherever it appears in the specification.

Change "XM24" to "M24" wherever it appears in the specification.

Page 1

2.1 Delete "MIL-C-45662 Calibration System Requirements".

In "STANDARDS" add to the end of the list "MIL-STD-45662 - Calibration System Requirements".

In "DRAWINGS" insert after "B8769067 - Magnetic Particle Inspection" drawings "D11577414 - Loop, Double" and "D11577415 - Loop, Single" each on a separate line in the list.

Page 3

3.2.4 Delete the entire paragraph and insert therefor:

"Flexibility. A belt assembly of links filled with dummy or inert rounds of ammunition shall have sufficient flexibility to be folded freely. In addition, there shall be no interference between the projecting surfaces of the links".

Page 5

4.5.3.b Delete the entire paragraph.

Page 7

4.5.3.4 Add the following to defect 104 in the CD table:

"Improper drainage is the presence or accumulation of liquid oil which is not held as an integral part of the phosphate coating and is evident as droplets, puddles, or as an oil film so wet as to be moving visually".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:30Z
Check the source to verify that this is the current version before use.

Page 9

4.5.5 Line 6, delete "MIL-C-45662" and insert therefor "MIL-STD-45662".

Page 10

4.6.7 Line 1, delete "foldover" and insert therefor "flexibility".

Custodian:

Army - AR

Preparing activity:

Army - AR

Project No. 1305-AC59

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:30Z
Check the source to verify that this is the current version before use.