MIL-M-45590A
AMENDMENT 1
17 February 1977

MILITARY SPECIFICATION

MACHINE GUN, CALIBER .50: FIXED, M85

This amendment forms a part of Military Specification MIL-M-45590A dated 1 August 1975, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 11

Paragraph 3.3.7 - Delete "high and low cyclic rate of fire of 800 to 950 and 400 to 500 rounds per minute respectively" and substitute "minimum high cyclic rate of 625 rounds per minute (RPM) and a minimum low cyclic rate of 400 RPM".

Paragraph 3.3.8 - Delete second sentence and substitute "The average high and average low cyclic rate of fire shall be 700 to 950 and 400 to 500 RPM, respectively."

PAGE 26

Paragraph 4.6.8.3 - Delete second sentence and substitute "The cyclic rate of fire shall be measured and recorded during one continuous burst at the high rate setting and during one continuous burst at the low rate setting, using a timer gage conforming to 4.6.7.5. A high and a low cyclic rate shall be taken on the first and second 90 round continuous burst, respectively, after 1620, 3420 and 4860 rounds of firing."

Custodian:
Army - WC
Navy - OS
Air Force - 99

User activity:
Navy - MC

Preparing activity:
Army - WC

Project number:
1005-0561

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:29Z
Check the source to verify that this is the current version before use.