MIL-P-45592(WC)

12 January 1971

SUPERSEDING
(See Section 6)

MILITARY SPECIFICATION

PISTOLS, CALIBER .22, AUTOMATIC, MATCH GRADE

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers hammerless (see 6.5), bluwback-operated, magazine-fed) rimfired pistols of commercial design that are chambered for caliber .22 long rifle Cartridges

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue *in* ef'feet on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-C-46935 - Cartridge, Commercial.
MIL-W-13855 - Weapons; Small Arms and Aircraft Armament Subsystems, General Specification for.
MIL-P-14313 - Pistols and Revolvers, Packaging of.
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of.
MIL-C-45662 - Calibration System Requirements,

STANDARDS

Military

MIL-STD-105 *Sampling* Procedures and Tables for Inspection by Attributes.
MIL-STD-109 Quality Assurance Terms and Definitions.

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:29Z
Check the source to verify that this is the current version before use.

DRAWING

U.S Army Munitions Command
C7553931 - Cartridge, Cal .22 Ball, Long Rifle, Commercial.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document fores a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

American National Standard Institute Inc.
B46.1 - Surface Texture

(Application for copies should be addressed to American National Standard Institute Inc., 1430 Broadway, New York, New York 10018.)

3. REQUIREMENTS

3.1 Bid samples. Each bidder shall forward three pistols of the design be proposes, to the test agency specified by the Procuring activity (see 6.2). for evaluation and test to determine compliance with this specification (see 4.4). Pistols shall be representative of the manufacturer's normal production. Unless otherwise specified in the proposed contract) bid sample pistols shall be prepared for delivery in accordance with level C requirements (see 6.2). Each bidder shall indicate the nommenclature and model designation used by the manufacturer to identity the pistol as one that meets the requirements of this specification.

3.1.1 Upon award of the contract, the approved bid sample pistols submitted by the successful bidder will be used by the contractor and the Government as manufacturing models in accordance with the manufacturing model provisions of MIL-W-13855.

3.1.2 For continuation orders when bid sample may not be required, the contractor shall furnish the manufacturing models and provide the Government representative with inspection and test records attesting that the items furnished are physicly and functionally equivent to the bid samples which were approved by the Government on prior contact.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:29Z
Check the source to verify that this is the current version before use.

3.2 Materials, construction and design. Materials, construction, and design requirements shall be as specified herein and shall be in accordance with the approved manufacturing models. The action and parts in rolling or sliding contact shall. be of hardened steel. Staked or dovetailed members shall have sufficient temper to retain their original fit after extended use.

3.2.1 General characteristics. General characteristics shall be in accordance with Table I.

Table I. General Characteristics

Weight (with empty magazine and without barrel weights)	40 to 53 ounces
Length of barrel	6 to 8 inches
Over-all length	l0½ to 12¼ inches
Magazine capacity	5 to 10 rounds
Trigger pull (see 3.2.l2)	2 to 3¼ pounds
Sight radius	10 inches (maximun)

3.2.2 Human engineering characteristics. Pistol design shall meet with the approval of the bid sample evaluation and test agency (see 3.1) for human engineering characteristics such as size, shape and balance deemed essential for expert match shooting.

3.2.3 Barrel. The barrel bore and chamber shall be free of scratches, pits, rings, cracks and seams.

3.2.4 Finishes.

3.2.4.1 Machine finish. Machine finishes shall be in accordance with commercial practice for the type of pistol furnished. Approved manufacturing models (see 3.1.1) shall be used as standards for machine finishes for pistols to be supplied under the contract. In the event of a dispute over the comparison of finishes of the manufacturing models and the production pistols, referee comparison shall be made in accord. ante with American National Standard B46.1.

3.2.4.2 Final protective finish. The exterior metallic surfaces shall be polished and blued, or finished in such other manner as approved by the procuring agency. The finish shall be applied so as not to draw the temper or alter the form or dimensions of components sufficiently to affect functioning. The finish shall be uniform in texture and appearance. Approved manufacturing models (see 3.1.1) shall be used as standards for final protective finishes for pistols to be supplied under the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:29Z
Check the source to verify that this is the current version before use.

3.2.5 Firing mechanism. The firing mechanism shall not release when the slide or bolt is released and allowed to go forward into battery position.

3.2.6 Magazine. The magazine shall be free of dents, cracks, burrs, scratches, sharp edges, spread or bent lips, or other defects which may affect functioning of either the magazine or the pistol. It shall fit easily into the pistol grip, be held firmly in place by the magazine catch, and release freely as evidenced by manual examination.

3.2.7 Safety. When the pistol is cocked, the safety shall be movable manually between the "safe" position and the "fire" position, and it shall remain in the position set until reset manually. When the safety is in the “safe” position, it shall not be possible to fire the pistol. When the safety is in the “fire” position, the firing mechanism shall release when the trigger is pulled.

3.2.8 Sights. The pistol shall be equiped with “Patridge type’’sights (A thick front, flat on top and parallel sides, and an open rear sight with corresponding parallel sides of such width that a clear opening *can* be seen on each side of the front sight while aiming). *The* front sight shall be fixed and shall have no looseness as evidenced by manual examination. The rear sight shall be adjustable for windage and elevation. Adjustment shall be of a positive self-locking click adjustment type and, after adjustment, the sight shall maintain its setting during normal firing conditions.

3.2.9 Slide or bolt stop. The pistol shall be equipped with a stop mechanism for locking the slide or bolt in the open (rearward) position. When the stop mechanism is in the “hold” position, it shall continue to hold the slide or bolt open until moved manually to the “release” position. Moving the stop to the “release” position shall permit the slide or bolt to return under spring action to battery position.

3.2.10 Stocks. Stocks shall be sound and shall be free of crocks, patches, splits, other defects which may affect appearance or serviceability. Approved manufacturing models (see 3.1.1) shall be used as standards for stocks for pistols to be supplied under the contract.

3.2.11 Trigger. The trigger shall return to its normal forward position immediately upon release after partial or complete trigger pull.

3.2.12 Trigger pull. The trigger pull shall be free of detectable creep and within the trigger pull range specified in Table I. Creep shall be interpreted to mean any movement between the time positive resistance is met and the firing mechanism is released.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:29Z
Check the source to verify that this is the current version before use.

3.2.13 High pressure resistance. Pistols shall be capable of with standing the firing of one high-pressure test cartridge that develops a mean breech pressure of 31,000 to 33,000 pounds per square inch. After proof firing, pistols shall be free of cracks, seams and other injurious defects. The cartridge cases shall be free of bulges, splits, rings and other defects which would indicate a defective barrel,

3.2.14 Functioning firing. Pistols shall operate without malfunctions when firing five rounds from the magazine. At the completion of the test there shall be no evidence of broken or unserviceable parts, ruptured or punctured cartridge cases, loose stocks or screws, or other unacceptable conditions. Malfunctions attributable to defective ammunition shall not be counted against the pistol being tested.

3.2.15 Targeting. The rear sight shall be capable of being zeroed to the pistol at the applicable range and still have additional windage and elevation adjustment remaining in both directions. A series of 5 shots fired from the pistol at a range of 50 yards shall be within or cut the edge of a bull's-eye 3½ inches in diameter when firing match cartridges as specified in 4.5.4.2.

3.2.16 Dispersion. The average extreme spread, measured from center to center of shot holes, of 3 consecutive groups of 10 shots each fired from the pistol at a range of 50 yards shall not exceed 2.00 inches, when firing match cartridges as specified in 4.5.4.2.

3.2.17 Enchrance. Pistols shall be capable of passing without malfunction or unserviceable parts a 2000 round endurance test using standard velocity grade cartridges as specified in 4.5.4.2. At the comletion of the test, pistols shall meet the trigger pull, targeting, and accuracy requirements of this specification (see 3.2.12, 3.2.15, and 3.2.16). Malfunctions attributable to defective ammunition shall not be counted against the pistol being tested.

3.3 Marking. Unless otherwise specified in procurement documents (see 6.2), pistols shall be marked in accordance with the marking provisions of MIL-W-13855. The letters "U.S." and the serial number shall be marked on the exterior surface of the receiver of the pistol,

3.4 Workmanship. Workmanship shall be in accordance with the requirements of MIL-w-13855 and the approved manufacturing models (see 3.1.1).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may use his own or any other facilities suitable for the performance of the inspection requiements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:29Z
Check the source to verify that this is the current version before use.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109. Whenever the term “inspector” is used, it denotes Government inspector

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

Bid sample inspection (see 4.4).
b. Quality conformance inspection (4.5).

4.4 Bid sample inspection. Inspection of bid sample pistols shall be performed at the designated testing agency. Pistols shall be subjected to all examinations and tests specified herein and such other inspection by the Government as is necessary to determine compliance with the requirements of this specification and the proposed contract.

4.4.1 Bid sample pistols. Examination of bid sample pistols shall be in accordance with the applicable provisions of MIL-w-13855. pistols shall be examined by the evaluation and test agency (see,3.1) for completeness of manufacture, general characteristics, human engineering characteristics, assembly, finishes, marking, and workmanship, and the barrel, firing mechanism, magazine, safety, sights, slide or bolt, stocks, and trigger shall be examined for compliance with the requirements specified in 3.2 through 3.2.12 and 3.2.16.

4.5 Quality conformance inspection.

4.5.1 Inspection lot. The formation, size, and presentation of inspection lots of pistols and packaging shall be in accordance with MIL-STD-105. Inspection lots shall be as large as practicable, in consideration of quality history, manufacturing conditions, and contractor’s delivery schedule, and within the limitations of the inspection lot provisions of MIL-W-13855.

4.5.2 Examination.

4.5.2.1 Pistols. Pistols shall be examined for completeness of manufacture, general characteristics, assembly, finishes, marking, and workmanship, and the barrel, firing mechanism, magazine, safety) sights, slide or bolt, stocks, and trigger shall be examined for compliance with the requirements specified in 3.2 through 3.2.12. Approved manufacturing models shall be utilized as standards.

4.5.2.1 Packaging. Examination of packaging of pistols shall be performed in accordance with MIL-P-14313.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:29Z
Check the source to verify that this is the current version before use.

4.5.3 Testing.

4.5.3.1 Bid sample testing. Bid sample testing shall be perfored by the Government and shall consist of all acceptance tests specified herein and the following tests.

4.5.3.1.1 Bid Sample accuracy testing. Each bid sample pistol shall be subjected to 10 accuracy tests as specified in 4.6.5. Nine out of the 10 tests performed on each pistol shall meet the accuracy requirements specified in 3.2.16.

4.5.3.1.2 Endurance testing. After being found satisfactory In examination and all other tests, each bid sample pistol shall be subjected to the endurance test specified in 4.6.6.

4.5.3.2 Acceptance testing.

4.5.3.2.1 Trigger pull, high-pressure resistance, fumctioning firing, targeting, and accuracy testing. The contractor shall pistol for trigger pulls high-pressure resistance, functiioning firing, targeting, and accuracy using the test methods specified in 4.6.1. through 4.6.5. The tests for functionin6 firing, targeting, and accuracy may be performed concurrently. Pistols failing to meet any of the requirements shall be rejected.

4.5.3.2.2 Packaging. Testing of packaging of pistols shall be performed in accordance with MIL-P-14313.

4.5.4 Inspection equipment.

4.5.4.1 Unless otherwise specified in procurement documents (see 6.2), responsibilities for acquisition, maintenance, and disposition of acceptance inspection equipment shall be in accordance with MIL-I-45607 and MIL-C-45662.

4.5.4.2 Ammunition. Cartridges loaded to develop a mean breech pressure of 31,000 to 33,000 pounds per square inch shall be used in the high-pressure resistance test. Cartridges for other firing tests shall be in accordance with MIL-c-46935 and USAMUCOM Drawing 7553931 using Match grade cartridges for the functioning, targeting, and dispersion and Standard Velocity grade cartridges for the endurance firing test (see 6.2).

4.6 Test methods.

4.6.1 Trigger pull test. Pistols shall be tested for trigger pull requirement (see 3.2.12) using an approved measuring device. The pistol shall be cocked and the safety shall be in the “fire” position. The load shall be gradually applied to the center of the trigger and exerted In a line parallel to the axis of the barrel bore. The trigger shall also be checked for creep by applying pressure manually to the triger at a uniform rate of increase over a period of not less than 3 seconds.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T03:29Z
Check the source to verify that this is the current version before use.

4.6.2 High-pressure resistance test. Pistols shall be tested for high-pressure resistance requirement (see, 3.2.13) by firing one high--pressure test cartridge in each pistol. After proof firing, pistols shall be examined for cracks, defamations, and other evidence of damage and cartridge cases shall be examined for bulges} splits) rings} and other defects caused by defective barrels.

4.6.3 Functioning firing test. Pistols shall be tested for functioning firing requirement.(see 3.2.14) by firing at least five rounds from the magazine. During this test, the pistols shall be checked for the functional requirements of the safety and the slide or bolt stop (see 3.2.7 and 3.2.9).

4.6.4 Targeting test. Pistols shall be tested for targeting requirement (see 3.2.15) using an arm rest or a machine rest simulating an arm rest and with the sights alined at 6 o'clock on the bull's-eye. Prior to firing, the rear sight may be adjusted as necessary for windage and elevation. After firing, the targets shall be checked to determine whether the targeting requirements have been met, and the pistol shall be checked to determine whether the rear sight is capable of being zeroed and whether additional windage and elevation adjustment is available (see 3.2.15).

4.6.5 Dispenersion test. Pistols shall be tested for accuracy requirement (see 3.2.16) using an arm rest or a machine rest simulating an arm rest.

4.6.6 Endurance test. Pistols shall be fired for endurance requirements (see 3.2.17) by firing 2,000 rounds of ammunition. Pistols may be cleaned and oiled after each 500 rounds or at the end of a day's firing. Upon completion of endurance test, pistols shall be subjected to the trigger pull, targeting, and accuracy tests specified in 4.5.l, 4.5.4 and 4.6.5 respectively.

5. PREPARATION FOR DELIVERY

5.1 Pistols shall be prepared for shipment in accordance with MIL-P-l4313 for the applicable level of preservation, packaging, and packing specified in procurement documents (see 6.2).

6. NOTES

6.1 Intended use. These weapons, of commercial design, are used by the Military for the purpose of match shooting.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T03:29Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following :

6.2.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Shipping instructions for bid samples (see 3.1).
Marking, if other than as specified (see 3.3).
d. Place of final inspection and acceptance (see “Notes” in MIL-w-13855).
e. Responsibilities for furnishing acceptance equipment (see 4.5.4.1).
f. Responsibility for furnishing ammunition (see 4.5.4.2).
g. Selection of applicable levels of preservation, packaging and packing (see 5.1).
h. Disposition of Government furnished property.

6.2.2 Contract data requirements. Monthly reports of the results of final examination and functional testing shall be specified for delivery on a DD Form l423 included in the contract.

6.3 Work programing for examination and testing of manufacturing models should be affected with the testing agency at the earliest practicable date (see 3.2).

6.4 Pistols submitted on bid samples shall be of the latest commercially available design of each manufacturer.

6.5 The term “hammerless pistol” denotes a pistol with an in-closed hammer or a pistol that does not utilize a hammer in the firing mechanism.

6.6 When warranted, the contract should specify the application of MIL-Q -9858 or MIL-I-45208, as appropriate On the Management COntrol Systems Summary List, DD Form 1660.

6.7 Supersession data. This specification includes the require-ments of Springfield Armory Purchase Description, SAPD-232, dated 9 October 1962.

Custodian:
Army WC

PreParing activity:
Army- UC

ProJect number:
1005-0415

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T03:29Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-P-45592(WC) Pistols, Caliber .22, Automatic, Match Grade

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A
[ ] DIRECT GOVERNMENT CONTRACT [ ] SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

[ ] YES [ ] NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:29Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
HEADQUARTERS
U. S. ARMY WEAPONS COMMAND

ROCK ISLAND, ILLINOIS 61201

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding General
U. S. Army Weapons Command
ATTN: AMSWE-REE-S
Rock Island, Illinois 61201

FOLD

To detach this form, cut along this line.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:29Z
Check the source to verify that this is the current version before use.