MIL-B-41805B
18 April 1973
SUPERSEDING
MIL-B-41805A
3 September 1968

MILITARY SPECIFICATION

BLANKET, COMBAT CASUALTY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for one type of cotton duck combat casualty blanket.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-276	- Thread, Cotton
V-T-285	- Thread, Polyester
CCC-C-419	- Cloth, Duck, Cotton, Unbleached, Plied-Yarns, Army and Numbered
CCC-C-428	- Cloth, Duck Cotton; Fire, Water, Weather, And Mildew Resistant

MILITARY

MIL-B-17757	- Boxes, Fiberboard, Corrugated (Modular Sizes)
MIL-C-43627	- Cloth, Duck, Cotton Plied Yarns, Fire, Water Weather and Mildew Resistant Treated, Lightdry Finish

FSC 7210

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:30Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads for 40" X 48" Pallets
MS-16686	- Medical Services Symbol

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, ATTN: Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606).

3. REQUIREMENTS

3.1 Guide sample.- Samples, when furnished, are solely for guidance and information to the supplier (see 6.3). Variations from this specification may appear in the sample, in which case this specification shall govern.

3.2 First Article Approval.- The requirement for the First Article will be as specified by the Procuring Activity.(see 6.2).

3.3 Materials.-

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:30Z
Check the source to verify that this is the current version before use.

3.3.1 Cloth, Cotton, Duck.- The blanket shall be made of cotton duck conforming to type III, 9.85 ounce of CCC-C-419. The duck shall be treated for fire, water, weather, and mildew resistance in accordance with type I, class 1 of CCC-C-428. As an alternate, the blanket may be made of cotton duck, shade olive drab No. 7, conforming to MIL-C-43627.

3.3.2 Thread.- The thread shall be cotton, dyed olive drab R cable No. 66021, Type IA3, ticket number 16, 4-ply conforming to V-T-276. As an alternate, the thread may be polyester, ticket F, dyed shade S-1, cable No. 66022 and shall conform to type I or II, Class 1, subclass B of V-T-285.

3.3.3 Marking.- The top side of each blanket shall be stamped or stenciled in black indelible ink or dyed with a caduceus conforming to type I of MS-16686 centered between the letters "U" and "S". The height of the letters shall be 1 1/4 inches plus or minus 1/8 inch high and the height of the caduceus shall be in proportion to the letters. The marking shall be in or close to the center of the blanket with the long axis of the caduceus parallel to the length of the blanket.

3.4 Design.- The blanket shall be fabricated of either one or two pieces of duck. When two pieces are used, the pieces shall be sewed so that the joining seam shall be formed along the long axis, midway between the edges of the blanket. A hem shall be made at every raw edge. The finished blanket shall measure 80 inches plus or minus one inch in length and 60 inches plus or minus one inch in width.

3.5 Construction.-

3.5.1 Stitches, seams, and stitching.- The stitch, seam, and stitching types shall conform to FED-STD-751. Hems and seams shall use stitch type 301 or 401, with 6 to 8 stitches per inch. Where stitch type 401 is used, the looper or underthread shall be on the underside of the blanket. Ends of all seams and stitching, when not caught in other seams or stitching, shall be backtacked not less than 1/2 inch. Type 401 skipped stitches or thread breaks may be repaired using 301 stitch type. Trim and remove all thread ends. All thread breaks shall be secured by stitching back of the break not less than 1/2 inch.

3.5.2 Hems.- The hem shall be finished on the underside of the blanket. The hems shall be sewn using seam type EFb-1 and shall finish 3/4 inch plus or minus 1/8 inch. Stitching shall be 1/8 to 3/16 inch from turned edge.

3.5.3 Blankets using one piece of duck.- The blanket shall be made from one full width piece of duck 60 inches plus or minus one inch in width, or one full width piece of duck 80 inches or more, so that the width of the duck shall be the length of the finished blanket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:30Z
Check the source to verify that this is the current version before use.

3.5.4 Blankets using two pieces of duck.- The blanket shall be made from two equal length pieces of duck. The cut ends of the duck shall be in alignment with each other. When two selvage edges are used at the joining seam, the selvage edge of one piece shall be lapped over the selvage edge of the other piece. Join the two pieces of duck using seam type LSa-2, stitching 1/8 to 3/16 inch from each overlapped edge. When one selvage edge and one raw edge are used at the joining seam, seam type LSb-2 shall be used and the selvage edge shall be on the under side of the blanket. The first row of stitches shall be 1/8 to 3/16 inch from turned edge and the second shall be 1/8 to 3/16 inches from raw and selvage edges. When two raw edges are used at the joining seam, seam type LSc-2 shall be used. Stitching shall be 1/8 to 3/16 inch from the turned edge.

3.6 Workmanship.- The finished blanket shall conform to the quality established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to the prescribed requirements.

4.1.1 Certificate of compliance.- Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 First article inspection.- The first article submitted in accordance with 3.2 shall be inspected as specified in 4.3.2.1 and 4.3.2.2 for compliance with design, construction, workmanship and dimensional requirements.

4.3 Inspection.- Inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated herein.

4.3.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:30Z
Check the source to verify that this is the current version before use.

4.3.2 Examination of the end item.- Examination of the end item shall be in accordance with 4.3.2.1 through 4.3.2.3.

4.3.2.1 Visual examination.- Defects shall be classified in accordance with Table I. The lot size shall be expressed in units of one blanket. The sample unit shall be one blanket. The acceptable quality level, expressed in defects per hundred units, shall be 6.5 for Major defects and 25 for major and minor defects combined. Inspection level shall be level II. The defects shall be counted regardless of their proximity to each other, excpet where two or more defects represent a single local condition, in which case only the most serious defect shall be counted.

Table I - Classification of Defects

Defects	Classification Major	Minor
Material		
Not type specified	X	
Any hole, cut, tear, or needle chew	X	
Any spots, stains, or streaks		X
Not finished as specified	X	
Workmanship		
Any required operation omitted	X	
Blanket composed of more than two pieces	X	
When two pieces are used, seam not midway by more than 1 inch		X
Seams and stitching		
Ends of stitching not backstitched	X	
Ends of stitching backstitched less than 1/2 inch		X
Any seam open 1/2 inch or less		X
Any seam open more than 1/2 inch	X	
Stitch type not as specified		X
Seam type not as specified	X	
Any raw edge not hemmed	X	
Stitch tension (tight-stitches break when normal tension is applied to seam or hem)		X
Stitch tension loose-resulting in loosely secured seam or hem		X
Stitches per inch less than minimum specified:		
by one stitch		X
by more than one stitch	X	
Stitches per inch in excess of maximum specified		X

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:30Z
Check the source to verify that this is the current version before use.

Defects	Classification Major	Minor
Seams and stitching (cont'd)		
Looper thread of 401 stitch type on top side	X	
Hems twisted or uneven in width by more than 1/8 inch		X
Width of hems more or less than specified		X
Center seam not sewn in a straight line perpendicular to the sides		X
Stitching less than 1/8 inch or more than 3/16 inch from each overlapped edge		X
Thread breaks overstitched less than 1/2 inch		X
Marking		
Not as specified		X
Missing, incorrect, illegible, or poorly applied		X
Not located in center of blanket or proximity		X
Size not as specified		X
Not on top side		X

4.3.2.2 Dimensional examination.- An examination shall be made to determine conformance to the length and width dimensions and tolerances. The sample unit shall be one blanket. The lot size shall be expressed in units of one blanket. The acceptable quality level, expressed in defects per hundred units shall be 4.0. Inspection level shall be S-3. Any deviation from the dimensional requirements shall constitute a defect.

4.3.2.3 Examination of preparation for delivery requirements.- An examination shall be made to determine that the packaging, packing, and marking comply with Section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery except that it need not be sealed. Defects of closure shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-3 and the acceptable quality level shall be 2.5 defects per hundred units.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged or not as specified.
Workmanship	Inadequate application of components, i.e., incomplete closure of container flaps, loose strapping, inadequate stapling; improper taping bulging or distortion of container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:30Z
Check the source to verify that this is the current version before use.

Examine	Defect
Content	Number per container more or less than required.

4.3.2.4 Examination for palletization.- An examination shall be made to determine that the palletization comply with section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Examine	Defect
Finished dimension	Length, width or height exceeds specified maximum requirement
Palletization	Not as specified Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; or improper size, location, sequence or method of application

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.- Each blanket shall be neatly folded to approximate dimensions of 11 1/2 inches by 14 1/2 inches. Six blankets shall be stacked in a bundle and securely tied with cotton tape or twine approximately four inches in from each end.

5.1.2 Level C.-Blankets shall be packaged to afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing.- Packing shall be level A, B, or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:30Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.- Twenty-four blankets packaged as specified in 5.1, shall be packed in a fiberboard shipping container assembled, closed and reinforced conforming to class weather-resistant, grade V2s, size 3A of MIL-B-17757. The fiberboard for the box liner shall conform to type CF, class weather-resistant, variety DW, grade V15c of MIL-B-17757. Level A packages shall be packed flat two in length, one in width and two in depth within the shipping container.

5.2.2 Level B.- Twenty-four blankets packaged as specified in 5.1, shall be packed in a fiberboard shipping container assembled and closed conforming to class domestic, grade 275, size 3A of MIL-B-17757. The fiberboard for the box liner shall conform to type CF, class domestic, variety DW, grade 275 of MIL-B-17757. Level A packages shall be packed flat two in length, one in width and two in depth within the shipping container.

5.2.2.1 When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with MIL-B-17757 and closed in accordance with the appendix of the box specification.

5.2.3 Level C.- Blankets, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Palletization.- When specified (see 6.2), blankets packed as specified, shall be palletized in accordance with Load Type 1 of MIL-STD-147. The pallet pattern shall conform to Pattern No. 3 as shown in the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means K and L.

5.4 Marking.- In addition to any special marking required by the contract or order, interior packages, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129. Each bundle shall have attached a manila colored paper shipping tag for the identification marking.

6. NOTES

6.1 Intended use.- The blanket is part of a field medical kit or set and is used to cover casualties of military personnel under combat conditions.

6.2 Ordering data.- Procurement documents should specify the following:

a. Title, number and date of this specification
b. Whether first article sample is required (see 3.2)

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:30Z
Check the source to verify that this is the current version before use.

c. Selection of applicable levels of packaging and packing (see 5.1 and 5.2)
d. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1)
e. When palletization is required (see 5.3)

6.3 Sample.- For access to samples, address the procuring activity issuing the invitation for bids.

Custodians:
Army - GL
Navy - SA
Air Force - 82

Preparing Activity:
Navy - SA

Project No. 7210-0135

Review Activities:
Army - MD
Air Force - 82
Navy - MS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:30Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
MIL-B-41805B Blanket, Combat Casualty

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY (Printed or typed name and activity - Optional)

DATE

DD, FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-25234

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:30Z
Check the source to verify that this is the current version before use.