NOT MEASUREMENT SENSITIVE


MIL-B-41809/11G
14 May 1990
SUPERSEDING
MIL-B-41809/11F
26 April 1983

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, US ARMY RECRUITER, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red brass

DIMENSIONS:
-1, -2:
HEIGHT: 2-1/8 inch (5.40 cm) (REF)
WIDTH: 1-3/4 inch (4.45 cm) (REF)
THICKNESS (Minimum): .030 inch (0.076 cm)
-3, -4, -5:
DIAMETER (Circumscribed): 3/16 inch (0.48 cm) (REF)
THICKNESS (At thickest point): .060 inch ± .005 inch (0.152 cm) ± (0.012 cm)

DASH NO:
-1: Silver with mounted stars
-2: Gold with mounted stars
-3: Star, silver
-4: Star, gold
-5: Star, gold with sapphire (see note 9)

ASSEMBLED WEIGHT (Maximum): 1 oz (480 Grains)

FINISH:
-1: Soft baked enameled, nickel plated, silver plated, oxidized, relieved, matte finish. Face and side lacquered.
-2: Soft baked enameled, gold plated, polished finish.
-3: Nickel plated, rhodium plated, matte finish.
-4,-5: Gold plated, matte finish.

NOTES:
1. Pierced areas shall be as indicated.
2. Attaching device shall be prong and clutch type. Three prongs shall be located on the center of the ring. Each prong shall be 120 degrees apart with one prong located on the vertical center line at the top of the ring.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:33Z
Check the source to verify that this is the current version before use.

3. A full forcer shall be used to bring up the design and meet the weight requirements.
4. Attaching device for the stars shall be a staple type prong. The prong shall be 1/8 inch + 1/16 inch - 0, (0.32 cm) + (0.16 cm) - 0 long and shall be formed from .010 inch ± .002 inch (0.025 cm) ± (0.005 cm) thick flat brass or nickel silver wire .040 inch ± .002 inch (0.101 cm) ± (0.005 cm) wide. The prong shall be centered on and soldered to the reverse of the star.
5. A .050 inch ± .005 inch (0.127 cm) ± (0.012 cm) diameter hole shall be drilled in the centers of the recessed star outline on the badge.
6. Stars shall be mounted on the badge with the tabs pushed through the holes so the stars are positioned in the recessed star outline on the badge and the tabs bent over to insure a tight snug fit.
7. Stars:
   a. UNIT PACKAGING: Thirty stars (30) of one finish only shall be placed in a polyethylene bag and heat sealed.
   b. PACKING: Stars shall be packed in accordance with Level C of the basic specification MIL-B-41809.
8. Green enamel shall match TIOH color chip no. 12 or the standard sample.
9. The dash no. 5 star shall have a 3 point full cut white sapphire set in a 4 bead setting. The setting shall be accomplished by filing the star point flat and drilling a hole in the center of the flat area of sufficient size to accept the stone.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-0487)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:33Z
Check the source to verify that this is the current version before use.