MIL-B-41809 / 15F
20 June 1985
SUPERSEDING
MIL-B-41809 / 15E
19 May 1982


MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, FIRE PROTECTION, AIR FORCE


This specification is approved for use by all Departments and Agencies of the Department of Defense. The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-B-41809.



-1,-5


-2,-6

-3,-7


-4,-8

DASH NO.
- -1: Firefighter, Regular Size
- -2: Assistant Fire Chief, Regular Size
- -3: Deputy Fire Chief, Regular Size
- -4: Fire Chief, Regular Size
- -5: Firefighter, Miniature Size
- -6: Assistant Fire Chief, Miniature Size
- -7: Deputy Fire Chief, Miniature Size
- -8: Fire Chief, Miniature Size

MATERIAL: RED BRASS

DIMENSIONS (INCHES):

BASE:

HEIGHT (OVERALL):
- -1,-2,-3,-4: 2-9/16 (REF)
- -5,-6,-7,-8: 1-3/4 (REF)

WIDTH (OVERALL):
- -1,-2,-3,-4: 1-5/8 (REF)
- -5,-6,-7,-8: 1-3/16 (REF)

THICKNESS OF FORCED AREA (ON LETTERING):
- -1,-2,-3,-4: .080 ± .005
- -5,-6,-7,-8: .070 ± .005

EDGE DEPTH (BOTTOM EDGE):
- -1,-2,-3,-4: .120 ± .010
- -5,-6,-7,-8: .085 ± .010

DEVICE:

DIAMETER:
- -1,-2,-3,-4: 1 (REF)
- -5,-6,-7,-8: 3/4 (REF)

THICKNESS (AT CENTER) (SEE NOTE 6):
- -1: .150 ± .010
- -2,-3,-4: .125 ± .010
- -5: .125 ± .010
- -6,-7,-8: .110 ± .010

WEIGHT (MAX):
- -1,-2,-3,-4: 1-1/2 OUNCE
- -5,-6,-7,-8: 3/4 OUNCE

FINISH:

BASE: NICKEL PLATED, SILVER PLATED, OXIDIZED RELIEVED, SATIN FINISH

DEVICE:
- -1,-5: NICKEL PLATED, SILVER PLATED, OXIDIZED RELIEVED SATIN FINISH
- -2,-3,-4,-6,-7,-8: GOLD PLATED, SATIN FINISH HIGHLIGHTED

NOTES:

1. DASH NOS. 1 AND 5 ARE SHOWN FOR ILLUSTRATIVE PURPOSES ONLY. THE DESIGN OF DASH NOS. 2,3,4,6,7 AND 8 ARE IDENTICAL TO THE DESIGN SHOWN EXCEPT FOR THE CENTER DEVICE.

2. A MOCK FORCER SHALL BE USED TO BRING UP THE DESIGN OF THE BASE, EAGLE, AND LETTERING AREAS. A MOCK FORCER MAY BE USED TO BRING UP THE DESIGN OF THE DEVICE.

3. THE CENTER DEVICE FOR DASH NOS. 2,3,4,6,7 AND 8 SHALL BE SECURED TO THE BASE BY TWO RIVETS. THE RIVETS SHALL BE LOCATED ON THE HORIZONTAL CENTERLINE EQUIDISTANT FROM EACH END AND 3/4 INCH ON CENTERS FOR REGULAR SIZE AND 3/8 INCH ON CENTERS FOR MINIATURE SIZE. AT THE OPTION OF THE MANUFACTURER THE DEVICE FOR DASH NOS. 1 AND 5 MAY BE EITHER SOFT SOLDERED OR RIVETED TO THE BASE IN THE LOCATION SHOWN.

4. THE ATTACHING DEVICE FOR 1,2,3 AND 4 SHALL BE A HEAVY DUTY PIN AND SAFETY CATCH TYPE. THE CATCH SHALL BE SIDE OPENING. THE ATTACHING DEVICE SHALL BE HARD SOLDERED ON THE VERTICAL CENTER LINE AND EQUIDISTANT FROM EACH END OF THE BADGE. THE PIN STEM SHALL BE 1-3/4 INCH ± 1/64 INCH IN LENGTH FOR THE REGULAR SIZE AND 1-1/2 INCH ± 1/64 INCH FOR THE MINIATURE SIZE.

5. THE JOINT AND CATCH SHALL BE POSITIONED ON THE SAME LEVEL PLANE TO EACH OTHER (PLATFORM AREAS ON THE BADGE'S REVERSE SIDE MAY BE USED FOR LEVELING THE JOINT AND CATCH) AND HARD SOLDERED.

6. THE OVERALL DEVICE THICKNESS SHALL INCLUDE THE DEPTH OF THE FORCED AREA, WHEN A FORCER IS USED.

7. THE BASE AND DASH NOS. 1 AND 5 DEVICES SHALL BE LACQUERED ON THE OBVERSE SIDE AND EDGES.

8. THE ATTACHING DEVICE FOR ALL MINIATURE SIZE BADGES SHALL BE THREE PRONG AND CLUTCHES. ONE PRONG SHALL BE LOCATED ON THE VERTICAL CENTERLINE BEHIND THE EAGLES BREAST. THE REMAINING PRONGS SHALL BE A HORIZONTAL LINE LOCATED 1/2 ± 1/32 INCH ABOVE THE BASE AND 3/4 ± 1/32 INCH ON CENTERS.

	CUSTODIANS:	REVIEW ACTIVITIES:	USER ACTIVITIES:
ARMY	IH		
AIR FORCE	99	11,82	45
NAVY			
OTHER		CT	

Project No. 8455 - F171

PREPARING ACTIVITY:

THE INSTITUTE OF HERALDRY, UNITED STATES ARMY

/FSC 8455/

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:35Z
Check the source to verify that this is the current version before use.