NOT MEASUREMENT SENSITIVE


MIL-B-41809/1C
14 May 1990
SUPERSEDING
MIL-B-41809/1B
31 December 1978

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, PRESIDENTIAL SERVICE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL:
BASE AND CENTER DISC: Gilding metal
DEVICE: Red brass

DIMENSIONS:
OUTSIDE DIAMETER: 1-15/16 inch (4.92 cm) (REF)
DIAMETER OF CENTER DISC: 1-23/32 inch (4.36 cm) (REF)
OVERALL HEIGHT OF DEVICE: 1-13/64 inch (3.08 cm) (REF)
DEVICE (Thickness at shield): 1/16 inch (0.16 cm)
ASSEMBLED THICKNESS (At shield): .250 inch + .010 inch - .0 (0.635 cm) + (0.025 cm) - .0

FINISH:
BASE: Gold plated, matte finish, peaks of rays polished
CENTER DISC: Hard enameled, nickle plated, silver plated, matte finish
DEVICE: Gold plated, matte finish, polished highlights.

NOTES:
1. Attaching device shall be prong and clutch type. Three prongs shall be located on a 1-1/2 inch (3.81 cm) diameter circle. Each prong shall be spaced 120 degrees apart with the top prong located on the vertical centerline at the top of the badge.
2. The center disc and the superimposed device shall be secured to the base by two or more rivets or soft soldered. When rivets are used, they may be an integral part of the device or fabricated from any type brass and soldered to the reverse of the device. The device shall follow the contour of the blue enamel disc.
3. Blue enamel color shall match TIOH color chip 20 or the standard sample.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:31Z
Check the source to verify that this is the current version before use.

4. Each badge shall be engraved with a serial number as specified in the procurement document using a condensed roman numeral. The numerals shall be 3/32 inch (0.24 cm) in height. The serial number shall be centered on the reverse of the badge with the base line of the number 1/4 inch (0.64 cm) from the lower edge of the badge.
5. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall have a shore D hardness of 85 and incorporate an ultra violet inhibitor. When epoxy resin is used, rivets shall be used to attach the center disc and device to the base.
6. The entire badge shall be lacquered after assembly.

Custodian:
Army - IH
Air Force - 11
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 82, 99
Navy - MC
DLA - CT

(Project no. 8455-0480)

User activity:
Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:31Z
Check the source to verify that this is the current version before use.