MILITARY SPECIFICATION

RECEIVERS, RANGE SAFETY, COMMAND

This amendment forms a part of Military Specification MIL-R-87954A(TE), dated 3 November 1979, and is approved for use by the US Army Test and Evaluation Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 8

a. Paragraph 3.8.8: Change to read as follows:

"3.8.8 Decoder signal plus noise characteristics. The noise response characteristics and "channel activated" decision threshold adjustment on each decoder channel shall be such that the "channel activated" decision is made no more than 50% of the time with signal plus noise composite modulation on the receiver input signal as follows:

a. Signal command channel frequency level one db below the "channel activated" decision level when the channel frequency is the only applied modulation.

b. Noise (uniform spectral density over the bandwidth required to pass all decoder channels present in the receiver) RMS level at least 12 db greater than paragraph a above."

b. Delete paragraph 3.8.8.1.

c. Paragraph 3.8.10, Line 1: Delete "minimum."

PAGE 9

Paragraph 3.9.3, Line 3: Add: "Sawtooth levels and additional level-frequency profiles shall be as specified in the applicable specification sheet."

PAGE 24

Paragraph 4.8.1.13b: Delete in its entirety.

Preparing activity:
Army-TE

Project 1430-A119

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:26Z
Check the source to verify that this is the current version before use.