THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-C-5015

THIS SPECIFICATION IS APPROVED FOR USE BY THE NAVAL AIR SYSTEMS COMMAND, DEPARTMENT OF THE NAVY, AND IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

Form approved
OMB No. 0704-0188



STYLE P (PIN INSERT)
STYLE S (SOCKET INSERT)

CLASS P–ENVIRONMENT RESISTANT, POTTING

SIZE	A COUPLING THREAD	B MIN USABLE THREAD	D +.015 -.000 I.D.	I MAX INSERT DIA	J +.031 -.000 INT SHELL SHLDR	K THICKNESS MOUNTING FLANGE MAX	K THICKNESS MOUNTING FLANGE MIN	L (a) MAX OVER-ALL LENGTH	M +.031 -.000 MTG FLANGE LOCATION	N MAX O.D.	O(REF) DIA PANEL OPENING MIN	P +.015 -.000 RET HEIGHT	R +.005 ℄-℄ MTG HOLE	S +.031 LENGTH SIDE	T +.010 -.005 DIA BOLT HOLE	U MIN (b)	V MAX DIA	FOR INSERT ARRANGEMENT SEE
8S	1/2-28	.375	.370	.250	.562	.156	.062	1.531	.562	.532	.635	.130	.594	.875	.120	.085	.613	MIL-STD-1651
10S	5/8-24		.448	.320						.656	.728	.165	.719	1.000			.707	
10SL				.448													.862	
12S	3/4-20		.557							.782	.885	.224	.812	1.094				
12		.625			.750			1.968	.750							.141		
14S	7/8-20	.375	.682	.525	.562			1.531	.562	.906	.963	.263	.906	1.188		.085	.941	
14		.625			.750			1.968	.750							.141		
16S	1 -20	.375	.807	.650	.562			1.531	.562	1.032	1.088	.325	.969	1.281		.085	1.066	
16		.625			.750			1.968	.750							.141		
18	1-1/8-18		.932	.770		.203	.094			1.156	1.228	.385	1.062	1.375			1.207	
20	1-1/4-18		1.058	.925				2.188		1.282	1.353	.463	1.156	1.500			1.332	
22	1-3/8-18		1.182	1.020						1.406	1.478	.510	1.250	1.625			1.457	
24	1-1/2-18		1.307	1.145					.812	1.532	1.604	.573	1.375	1.750	.147	.226	1.582	
28	1-3/4-18		1.526	1.365						1.782	1.854	.683	1.562	2.000			1.832	
32	2 -18		1.776	1.615		.359	.125		.875	2.032	2.132	.808	1.750	2.250	1.73		2.110	
36	2-1/4-16		1.995	1.830						2.282	2.417	.915	1.938	2.500			2.395	
40	2-1/2-16		2.245	2.047						2.532	2.616	1.023	2.188	2.750			2.594	

Ⓓ NOTES:

(a) CLASS P IS INACTIVE FOR NEW DESIGN AFTER 1 JAN 1991.

(b) THE SURFACE WITHIN THE "U" DIMENSION SHALL HAVE SURFACE IRREGULARITIES TO ASSIST THE GRIP OF THE POTTING COMPOUND TO THE SHELL.

MS3103-18-5SY

MS SHELL DRAWING NO.	SIZE	INSERT ARRANGEMENT NUMBER	STYLE (P OR S)	ALTERNATE INSERT POSITION (W, X, Y, OR Z). LEAVE BLANK FOR NORMAL POSITION

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.015.
THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

PREPARING ACTIVITY: NAVY-AS
CUSTODIANS: ARMY-CR NAVY-AS
AIR FORCE-85
REVIEW: ARMY-MI, AV, ME, NAVY-SH, EC, AF-99
USER: ARMY-AT, NAVY-OS, MC, CG
PROJECT NUMBER: 5935-3745-04

MILITARY SPECIFICATION SHEET

TITLE CONNECTOR, RECEPTACLE, ELECTRIC, POTTING SEAL, SOLDER CONTACTS, AN TYPE

SPECIFICATION SHEET NUMBER
MS3103D 31 AUG 1990

SUPERSEDING
MS25188 (AER)

AMSC- N/A FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Page 1 of 1

DD FORM 672 MAY 1988 PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.