NOT MEASUREMENT SENSITIVE

MIL-M-3946/26C
10 December 1993
SUPERSEDING
MIL-M-3946/26B
15 April 1986

# MILITARY SPECIFICATION SHEET

## MEDAL, MARINE CORPS EXPEDITIONARY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-M-3946.

OBVERSE

REVERSE

DASH NO:
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH metal finish chip Number 4.

DIMENSIONS:
DIAMETER:
-1: 1-1/4 inches (3.18 cm) (REF)
-2: 5/8 inch (1.59 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:36Z
Check the source to verify that this is the current version before use.

THICKNESS (At Thickest Point):

-1: 0.105 inch ± 0.010 inch (0.256 cm ± 0.025 cm)
-2: 0.080 inch ± 0.010 inch (0.203 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The pendant ring shall be fabricated from 0.050 inch ± 0.002 inch (0.127 cm ± 0.005 cm) nominal diameter wire with the same material and finish as the pendant. The ring shall have an outside diameter of 0.200 inch ± 0.010 inch (0.508 cm ± 0.025 cm). The ring shall be hard soldered to the top center of the pendant as shown.

3. The ribbon for the pendant drape shall conform to MIL-R-11589/81.

Custodian:
Army - IH
Navy - NU

Review activities:
Navy - MC
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0742)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:36Z
Check the source to verify that this is the current version before use.