INCH-POUND

MIL-S-19500/211B
AMENDMENT 4
02 March 1992
SUPERSEDING
AMENDMENT 3
28 February 1985

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, DIODE, SILICON, POWER RECTIFIER
TYPES 1N3164, 1N3168, 1N3170, 1N3172, 1N3174, 1N3175,
1N3176, 1N3177, AND R TYPES, JANTX, AND JANTXV

This amendment forms a part of MIL-S-19500/211B, dated 18 May 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Title: Delete and substitute as printed above.

1.5: Delete "$R_{\theta JC}$ = 0.15°C/W" and substitute "$R_{\theta JC}$ = 0.20°C/W".

PAGE 2

* Add 3.3.1 after 3.3:

"3.3.1 Processing exemptions. Suppliers to this detail specification are exempt from the following restrictions stated in MIL-S-19500 regarding offshore wafer processing:

a. Beveling operation.

b. Isotropic etching of die surface.

c. Die attach operation which promotes any diffusion of metal alloy into silicon die."


* Add 4.2.1 after 4.2:

"4.2.1 Qualification exemption. Suppliers to this detail specification are exempt from the basic plant retention of qualification clause of MIL-S-19500 appendix E sections 40.3 and 10.2 only if the device manufacturer has previously qualified this device at least once at the basic plant location."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:42Z
Check the source to verify that this is the current version before use.

FIGURE 1: Delete and substitute the new figure 1 as printed below:



NOTES:

1. Metric equivalents are given for general information only.
2. Complete threads to extend to within 2-1/2 threads of seating plane.
3. 3/4-16 UNF-2A. Maximum pitch diameter of plated threads shall be basic pitch diameter .7094 (18.019 mm) ref. (Screw Thread Standards for Federal Services) FED-STD-H28.
4. Angular orientation of terminal and tabulation with respect to hex base is undefined. Square or radius on end of terminal is undefined.
5. A chamfer (or undercut) on one or both ends of hexagonal portions is optional.
6. Tabulation optional.
7. Minimum flat.
8. Flexible leads.

Letter	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
A		1.520		38.10	4
B	.530	.755	13.46	19.18	
C	.063	.172	1.60	4.37	
ØD		1.100		27.94	
$ØD_1$		.600		15.24	
E	1.218	1.252	30.94	31.75	
F	.250	.562	6.35	14.27	5
H	5.125	6.750	130.18	171.45	
I_1	.375		9.53		7
ØM	.660	.745	16.76		2
M_1		.125		3.18	6
N	.793	.828	20.14	21.03	
Q		2.30		57.15	
Q_1		.375		9.53	6
Øt	.265	.350	6.73	8.89	
W					3

FIGURE 1. Physical dimensions for semiconductor devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:42Z
Check the source to verify that this is the current version before use.

4.3, add the following screen to the screening table:

"

Screen (see table II of MIL-S-19500)	Measurement
	JANTX and JANTXV levels
1	Method 2073 may be used in lieu of 2074 for compression bonded devices only.

"

TABLE II, subgroup 5: Delete "$R_{\theta JC}$ = 0.15°C/W" and substitute "$R_{\theta JC}$ = 0.20°C/W".

The margin of this amendment is marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR
Air Force - 11, 85
Navy - SH
DLA - ES

User activities:
Army - MI
Navy - CG, MC, WP

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5961-1348)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:42Z
Check the source to verify that this is the current version before use.