INCH-POUND

A-A-59152
9 January 1998

COMMERCIAL ITEM DESCRIPTION

TRUCK, FIRE FIGHTING, (RESCUE) (MEDIUM RESCUE TRUCK (MRT))

The General Services Administration has authorized the use of this Commercial Item Description (CID) by all federal agencies.

1. **SCOPE.** This Commercial Item Description (CID) describes a commercial MRT: diesel engine driven, automatic transmission, four wheel drive chassis, a four person cab with four doors and a Utility Body (UB). The MRT is intended to stow and transport forcible entry and rescue equipment for hazardous materials clean-up, and for structural, automotive and aircraft occupant rescue, in both on and off-road environments.

2. **SALIENT CHARACTERISTICS.**

2.1 The MRT shall be an assembly of new materials and shall be free of defects in design and construction that affect appearance, serviceability and durability. The MRT shall conform to the more stringent of State or Federal laws, applicable to a vehicle of this class and type, for use on the public roads and highways. All components of the MRT shall be represented in the manufacturer's sales literature as standard or optional equipment. The MRT shall meet the requirements found in Chapters 1, 2, 8, 9, 10, 11, 19, 21, 22 and 23 of NFPA 1901, Standard for Pumper Fire Apparatus, 1996 Edition, as applicable to a vehicle of the configuration specified. The MRT shall meet the performance parameters listed or referenced and shall be equipped as specified. Failure of the MRT to meet the annotated salient characteristics shall be cause for rejection of the vehicle.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: WR-ALC/TILBA, 420 SECOND STREET, SUITE 100, ROBINS AFB GA. 31098-5609 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4210

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

2.1.1 Performance. The MRT shall:

a. Operate in temperatures ranging from 0 to +125 degrees F.

b. Operate on paved and graded gravel roads and on off-road terrain.

c. Accelerate from stop to 50 MPH within 20 seconds on a level surface.

d. Maintain a minimum speed of 55 MPH on a level surface.

e. Maintain a minimum speed of 5 MPH while ascending a 30% grade.

f. Have approach and departure angles of not less than 22.5 degrees.

2.1.2 Chassis and vehicle components.

a. The MRT shall have a net payload (passengers and equipment) capacity of 5,000 pounds and a minimum Gross Vehicle Weight Rating (GVWR) of 21,000 pounds.

b. The MRT shall have a driver controlled emergency engine shutdown.

c. The MRT engine exhaust shall be directed away from standing ground access positions to the equipment compartments or the roof access ladder.

d. The MRT shall have dual, parallel-piped fuel filters.

e. The MRT shall have an electric, fuel priming pump.

f. The MRT brake system shall be fully air operated.

g. The MRT shall be equipped with tubeless, steel, radial tires mounted on steel disc wheels. Tire and wheel assemblies shall be interchangeable at all positions. Tread design shall be of the non-directional on/off-highway type. An identical spare wheel and tire assembly shall be provided.

h. The MRT shall have a minimum 50 gallon fuel tank.

2.1.3 Low voltage electrical systems and warning devices.

a. The MRT shall have a 12 volt electrical and starting system.

b. The MRT shall utilize a single alternator charging system. The minimum alternator high idle output shall exceed, by 10%, the total simultaneous operation of all electrical components, except the hose/cable reel rewind motors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

c. The MRT battery system shall be the chassis manufacturer's , largest available, option in terms of Cold Cranking Amperage.

d. The MRT shall have non-glare white lighting at ladders and access steps where personnel work or climb during night operations. Ladder, step, and area lights shall be controlled by switches on the cab instrument panel and near the light source.

e. The MRT cab and compartments shall be provided with white lighting. Lights shall automatically illuminate when the respective doors are opened. Cab interior light levels shall be high enough for reading maps or manuals. The cab shall have an additional, separately switched, red interior light.

f. The MRT cab roof shall have a six inch, red element, strobe-type light bar, with both forward and side facing strobe heads. The light bar shall be separately switched from the warning light panel.

g. The MRT shall have two, lower forward, six inch, red element, strobe-type warning lights. The lights shall be separately switched from the warning light panel.

h. The MRT shall have two, upper rearward, six inch, red element, strobe-type warning lights. The lights shall be separately switched from the warning light panel.

i. The MRT shall have four, lower side facing, red element, strobe-type intersection warning lights. The lights shall be separately switched from the warning light panel.

j. The MRT shall have a high beam, alternating/flashing, headlight system. The headlight flasher shall be separately switched from the warning light panel.

k. When specified, the rearward, red strobe light lenses, shall be replaced with amber.

l. When specified, all red warning and strobe light lenses shall be replaced with blue.

m. The MRT shall be equipped with an electronic siren system. The amplifier unit shall include volume control and selection of "Radio", "PA", "Manual", "Yelp", "Wail", and "Hi-Lo" (European) modes, and a magnetic noise canceling microphone. The amplifier, microphone and controls shall be within reach of the driver and right front passenger. Siren activating foot switches shall be located in front of the driver and the right front passenger. The siren speaker shall be guarded, weather resistant, forward facing, and below the cab floor.

n. The MRT shall have high, side mounted work area floodlights on each side of the truck. Switches shall be located in both the work areas and on the cab instrument panel.

o. The MRT shall have a separate 15 amp circuit, with breaker, serving the cab for a purchaser provided radio system.

p. The MRT shall have a lighted, license plate bracket at the left rear of the truck.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

2.1.4 Driving and crew areas (Cab).

a. The MRT cab seating shall include a driver, and three crew seats. Grab handles or bars shall be provided within the cab, in order for cab passengers to stabilize themselves during cross country operations.

b. The driver's seat shall be an adjustable, air-suspension design. The three crew seat backs shall accept a one-hour capacity, Interspiro self-contained breathing apparatus (SCBA).

c. In addition to standard instrumentation, the following shall be provided:

1). Siren controls.

2). Master and individual warning light control switches.

3). Work light switch.

4). Compartment “Door Open” warning light and alarm.

5). Scene light activation warning light.

d. The cab climate control system shall provide adequate heat, defrost and fresh air at ambient design conditions down to -40 degrees F. Supplemental equipment may be integrated into the basic commercial system to meet the performance requirements.

e. When specified, provide a cab air conditioning system.

f. When specified, the outside rear view mirrors shall be heated.

2.1.5 Body, compartments and equipment mounting.

a. The MRT shall have an all aluminum or all stainless steel UB, with a minimum of 450 cubic feet of enclosed storage space. The UB shall be of a saddle design, over the chassis frame rails, to minimize the length of the vehicle. The UB shall include side and rear compartments to maximize the accessible spaces while standing on the ground.

b. The UB roof shall be covered with tread-plate and shall support the weight of a crew member without permanent deflection. The UB roof shall have an eight inch high, cargo tie-down rail around the perimeter.

c. The UB shall have a roof access ladder, with non-slip handrails and rungs. The first ladder rung shall not interfere with the departure angle of the truck and shall be no more than 22 inches above level ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

d. The UB roof shall have a storage rack for a 14 foot, two section extension ladder. The ladder rack shall be within reach of a crew member standing on the roof access ladder. The ladder rack shall have guides and pivots to allow a controlled removal of the ladder by one unassisted crew member.

e. All compartments shall have counterbalanced, non-locking, roll-up doors. Doors shall be fabricated of clear anodized aluminum with full-width bar type latches. Push button latches shall not be used. When an open door height exceeds six feet above the ground, assist straps shall be provided.

f. Compartment floors shall be accessible while standing on the ground and shall each support a 500 pound load without permanent deflection.

g. At least two pass-through compartments, with full width roll-out trays, shall be provided. Each tray shall support a 500 pound load and shall roll out four feet from either side of the UB. Each roll-out tray shall latch automatically in the closed and fully extended positions, and shall selectively latch at one or more intermediate positions on each side. One roll-out tray shall be large enough to support a Hurst, Diesel-Engine Powered, Rescue Tool Kit.

h. Compartments shall have an adjustable and removable shelf for every 18 inches of door opening. Roll-out trays shall meet a portion of this requirement. Shelf adjustments shall require only common hand tools, and shall not require fastener removal. Each shelf shall support 200 pounds without permanent deflection.

i. Compartments shall have replaceable scuff-plates at each door threshold. Scuff-plates shall be attached with flush-headed cap screws and nuts, and shall not be bonded.

j. Drip rails shall be located over individual or combined compartment doors.

k. Compartments shall be illuminated with vertical tube-type lights, with clear and shatterproof protective covers. The lights shall illuminate above and below the shelves.

l. One compartment shall include a rack for storage of eight, one-hour SCBA cylinders. The top of the highest, horizontally arranged rack or the top edge of a vertically arranged rack, shall be less than 66 inches above the ground.

2.1.6 Line voltage electrical system.

a. The MRT shall have an engine, flywheel, or torque converter direct-driven power take-off (PTO), minimum 12 Kilowatt (KW), 120/240 voltage, 60 hertz, generator. The PTO shall be activated from the driver's location.

b. The MRT shall have an on-board battery charger, providing a minimum of 15 amp output. The charger shall be powered from a labeled, covered, recessed, male, 120 volt, AC receptacle, located at the driver’s side front corner of the UB. A charge meter shall be installed next to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

receptacle. A minimum 50 foot long, three wire, 15 amp rated, 120 volt AC, power cable shall be provided.

c. When specified, the MRT engine and batteries shall be equipped with a winterization system, capable of engine starts at -40 degrees F. The winterization system shall be powered through a labeled, covered, recessed, male, 120 volt, AC receptacle, located at the driver's side front corner of the UB. A minimum 50 foot long, three wire, 15 amp rated, 120 volt AC, power cable shall be provided.

1). If the combined power requirements of the winterization system and the battery charger does not exceed 15 amps, a single electrical receptacle may be used. The battery charger shall be directly connected to the receptacle, while the winterization system shall have a labeled switch with an activation pilot light.

d. The MRT shall have six, 120 volt AC, 20 amp rated, electrical outlets, one each at the front corners of the UB, and two each at the rear corners of the UB. Each outlet shall have weatherproof cover(s) and shall provide two twist-lock and two conventional outlets.

e. The MRT shall have one electric cable reel, equipped with 200 feet of 20 amp, 600 volt, 90-degree C. insulated electrical cable, in the UB rear compartment (with the air hose reel). A four-way guide shall be provided. The cable shall have a rubber ball stop to prevent the end outlet box from striking the guide, during rewinding operations. The cable reel shall include electric and manual rewind provisions. A manual handle shall be stored in the compartments with the reel. The electrical cable end shall be provided with a weatherproof outlet box, with built-in circuit breakers, two twist-lock receptacles, and two conventional receptacles.

f. The MRT shall have a power elevating scene light, with a minimum of 3000 total wattage "instant-on" halogen lights, that stores on the UB roof . The light mast shall elevate to a minimum of 18 feet above the ground. The light shall power rotate at least 350 degrees. Light power shall be provided by the auxiliary generator. Light elevation, rotation and activation shall be controlled while standing on the ground. Pneumatic controls, if provided, shall include a permanently set air regulator, air control valves and a system air pressure gauge. The light system shall interlock to operate only with the truck engine and auxiliary generator operating. The truck horn shall be interlocked to blow continuously, if any attempt is made to move the vehicle with the mast extended.

g. Wiring routed through or into compartment spaces shall be protected from damage while loading or storing equipment within the space.

2.1.7 Air system.

a. The truck chassis brake system, air compressor, shall deliver a minimum of 15 cubic feet per minute (CFM). A checked, quick disconnect air fitting, shall maintain brake system pressure while the vehicle is not running and shall be located at the left, side front corner of the UB.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

b. The MRT shall be equipped with dual air horns, projecting through the front bumper. Air horns shall be activated by a steering wheel button and by a foot switch in front of the right front seat.

c. The MRT shall have one air hose reel, equipped with 150 feet of 1/2 inch inside diameter, 600 per square inch gauge (PSIG) minimum rated hose-line, mounted in the rear compartment (with the electric cable reel) near the center of the vehicle. A four-way guide shall be provided. The hose-line shall have a rubber ball stop to prevent the hose end from pulling through the guide, during rewinding operations. A 3/8 inch NPT fitting and female style quick disconnect shall be attached to the hose-line. The hose reel shall include electric and manual rewind provisions. A manual handle shall be stored in the compartments with the reel. A pressure-protected air supply, from the chassis air system, shall be connected to the hose reel.

2.1.8 Winch.

a. The MRT shall be equipped with a recessed, 12,000 pound-pull winch, behind the front bumper. The space between the cab and the bumper, and a winch cover shall be fabricated of tread-plate. The winch may be electric or hydraulic powered and shall have at least one forward and reverse speed of not less than 12 feet per minute. The winch shall be wound with a minimum of 125 feet of 3/8 inch galvanized aircraft cable, with a 36 inch end chain and hook. A four-way roller, cable guide shall be provided. A minimum 10 foot long remote control cable for winch operation shall be provided.

2.1.9 Finish.

a. Exterior surfaces of the MRT shall have a finish color of Red, Number 11136; Lime Yellow, Number 13670; or Forest Green, Number 24052, of FED-STD-595, as specified at time of purchase.

b. With Red or Lime Yellow finish colors, the cab upper body (from the bottom of windshield up) and roof shall be painted White, Number 17875 of FED-STD-595. Compartment interiors shall have a standard commercial finish. All polished metal and anodized parts, such as: mirrors, horns, light bezels, tread-plate, and roll-up compartment doors, shall not be painted. A horizontal, reflective band shall be applied around the truck in an approximate plane with the headlights. Offsets in the reflective band shall be made to maximize the length of reflective surface. The reflective band may be interrupted by bright metal trim or tread-plate. The reflective band pattern shall be seven inches wide with three reflective stripes (one inch white reflective, one inch body color, three inches white reflective, one inch body color, and one inch white reflective).

c. When Forest Green finish color is specified, all surfaces, including all normally bright metal and any interior surfaces visible with any compartment door open, shall be painted Forest Green. A four inch wide horizontal, black reflective band shall be applied around the truck in an approximate plane with the headlights. Offsets in the reflective band shall be made to maximize the length of reflective surface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

d. The MRT shall have an applied corrosion treatment, to a tropical level. The first production truck shall not have the corrosion treatment applied until after the initial tests and inspections are completed.

3. **REGULATORY REQUIREMENTS.**

3.1 The offeror/contractor is encouraged to use recovered materials in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

3.1.1 For the purpose of this requirement, recovered materials are those materials that have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the vehicle may be newly fabricated from recovered materials to the maximum extent practicable, provided the vehicle produced meets all other requirements of this CID. Used, rebuilt or re-manufactured components, pieces and parts shall not be incorporated.

4.. **QUALITY ASSURANCE PROVISIONS.**

4.1 Product conformance.

4.1.1 The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

4.2 Commercial item requirement:

4.2.1 The vehicle furnished must meet the "commercial item" definition, as specified in FAR 2.101, as of the date of award. The government reserves the right to ask the offeror/contractor to prove that their product meets the referenced commerciality requirements. The offeror/contractor shall provide two copies of their commercial, descriptive catalogs with their offer, as specified in Clause I106. The offeror/contractor shall identify all modifications made to their commercial model in order to meet the performance and descriptive requirements of the CID or referenced documents. In regard to the offered item, the offeror/contractor shall identify any/all variations from compliance with or modifications to the performance requirements of the CID or the referenced documents.

4.3 Contractor requirements.

4.3.1 The contractor shall provide, at the time of delivery, two sets of manuals, including operation, maintenance and parts, with each truck delivered. The part's manuals shall list the contractor's component part numbers and any sub-component manufacturer's part numbers, as applicable. Manuals shall be provided for review 30 days prior to the time of demonstration. The contractor shall provide a product familiarization video tape with each truck, that verbally and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

visually provides the users with all information required for operation and routine maintenance of the vehicle and its components, using the commercial manuals as a baseline.

4.4 Testing.

4.4.1 The contractor shall demonstrate the first production MRT for the purchaser, prior to delivery, at his facility. Review and inspection for compliance with the requirements of this CID, the referenced documents, and tests 4.4.3 through 4.4.6 shall be conducted. All production trucks shall perform tests 4.4.3 and 4.4.6.

4.4.2 Failure to comply with the requirements of this CID, reference documents, or the tests identified herein shall be cause for reconfiguration and re-demonstration. Causes for reconfiguration shall include: structural failure; non-correctable misalignments; component interference; conditions presenting a safety hazard to the user or maintainer: instability during operation; spillage of fuel or coolant; and overheating.

4.4.3 Examination of product. A check list of specific requirements from this CID and the referenced documents shall be compared to the final configuration of the MRT. Where specific certifications are required, copies shall be provided.

4.4.4 Performance test. The top speed, acceleration, braking, gradeability and the turning diameter, of paragraphs 2.1.1, for a fully loaded vehicle shall be demonstrated. If site conditions do not exist for gradeability, calculations will be accepted.

4.4.5 Sound test. Sound reading shall be taken at the inside and outside ear level of each seated position.

4.4.6 Operational test. Each compartment floor and shelf shall be uniformly loaded, to the individual maximum design capacity, up to a total of 5000 pounds. Each cab seat shall be loaded with 200 pounds. The fully loaded truck shall be driven over 10 miles of paved and ten miles of off-road terrain. All loads shall be removed and all surfaces inspected for permanent deflection.

5. **PACKAGING.**

5.1 Preservation and packaging shall be the minimum necessary to afford protection against corrosion, deterioration and physical damage during shipment from the supply source to the first receiving activity.

5.2 Unless otherwise provided in the contract, the truck shall be prepared for delivery by common carrier. An identification plate, permanently marked, shall be securely mounted at the driver's compartment. The identification plate shall contain the following information:

NOMENCLATURE
MANUFACTURER'S MAKE AND MODEL
MANUFACTURER'S SERIAL NUMBER

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

REGISTRATION NUMBER
NATIONAL STOCK NUMBER (provided by the purchaser)
VEHICLE CURB WEIGHT: kg (pounds)
PAYLOAD, MAXIMUM: kg (pounds)
GROSS VEHICLE WEIGHT (GVW): kg (pounds)
GROSS COMBINATION WEIGHT RATING: kg (pounds)
DATE OF DELIVERY (month and year)
WARRANTY (month and km (miles))
CONTRACT NUMBER
US PROPERTY

6. **NOTES.**

6.1 Options:

6.1.1 The purchaser shall specify the following at time of purchase:

a. If the rearward, red warning lights shall be replaced with amber, (see 2.1.3k)

b. If all red warning lights shall be replaced with blue, (see 2.1.3l)

c. If a cab air conditioning system shall be required, (see 2.1.4e)

d. If heated, outside rear view mirrors shall be required, (see 2.1.4f)

e. If a winterization system is required, (see 2.1.6c)

f. Finish color of vehicle (Red, Lime Yellow or Forest Green), (see 2.1.9a)

CUSTODIAN:
AIR FORCE - 99

REVIEWER:
DLA - CC

PREPARING ACTIVITY:
AIR FORCE - 84

AGENT:
AIR FORCE - 99

Project Number: 4210-0003

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waiver any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	A-A-59152	98/01/09

3. DOCUMENT TITLE

TRUCK, FIRE FIGHTING, (RESCUE), (MEDIUM RESCUE TRUCK (MRT))

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON *(If applicable)*	e. DATE SUBMITTED *(YYMMDD)*

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE *(Include Area Code)*	
WR-ALC\TILBA	(1) Commercial (912) 926-2192	(2) AUTOVON 468-2192
c. ADDRESS *(Include Zip Code)* 420 SECOND STREET, SUITE 100, ROBINS AFB GA. 31098-5609	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD FORM 1426, OCT 89 *(EF-V1)* *(PerFORM PRO)* PREVIOUS EDITIONS ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.