INCH-POUND

A-A-59153
07 Jan 2003

COMMERCIAL ITEM DESCRIPTION

TRUCK, FIRE FIGHTING, (RESCUE) (LIGHT RESCUE TRUCK)

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers a commercial light rescue truck. It has a 4x4 chassis with a diesel engine and an automatic transmission; a cab for at least three persons with four doors; and a utility body. The light rescue truck is intended to stow and transport forcible entry equipment, rescue equipment, and personnel for hazardous materials mitigation and containment and for structural, automotive, and aircraft occupant rescue, in both on- and off-road environments.

2. SALIENT CHARACTERISTICS. The light rescue truck shall be in accordance with the applicable requirements of the following chapters of National Fire Protection Association (NFPA) 1901, 1999 Edition, for Special Service Fire Apparatus:

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: WR-ALC/TILCC, 420 Second Street, Suite 100, Robins AFB, GA 31098-1640

AMSC N/A FSC 4210

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

Chapter	Title
1	Administration
2	General Requirements
8	Special Service Fire Apparatus
10	Chassis and Vehicle Components
11	Low-Voltage Electrical Systems and Warning Devices
12	Driving and Crew Area
13	Body, Compartments, and Equipment Mounting
21	Line Voltage Electrical Systems
24	Winches
25	Referenced Publications

2.1 Administration.

2.1.1 Environmental conditions.

2.1.1.1 Altitude. Unless otherwise specified (see 6.2), the vehicle shall be designed for operation at 2,000 feet above sea level.

2.1.1.2 Temperature range. The vehicle shall be capable of satisfactory storage and operation in temperatures ranging from 0° to 125° F. The vehicle shall be equipped with an engine coolant heater, which shall be powered through the electrical shoreline connection (see 2.6.2).

2.1.2 Foreign object damage. All loose metal parts, such as pins and valve caps, shall be securely attached to the vehicle with wire ropes or chains. "Dog tag" style beaded chains shall not be provided. Removable panels, if provided, shall be attached with captive fasteners.

2.1.3 Roadability.

2.1.3.1 Operating terrain. The vehicle shall operate on paved and graded gravel roads and off-road (cross country) terrain.

2.1.3.2 Acceleration. The fully loaded vehicle shall accelerate from 0 to 50 miles per hour (mph) within 25 seconds on a level, paved road.

2.1.3.3 Maximum speed. The fully loaded vehicle shall attain a minimum top speed of 65 mph on a level, paved road.

2.1.3.4 Gradeability. The fully loaded vehicle shall be able to maintain a speed of at least 5.0 mph while ascending any paved slope up to and including 30 percent.

2.1.4 Overall dimensions. Overall dimensions shall be the minimum consistent with the operational performance and the design constraints necessary to achieve the specified performance. Overall dimensions shall not exceed:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

Length	320 inches
Width	96 inches (excluding mirrors)
Height	102 inches (without light mast)
	116 inches (with light mast)

2.1.5 Turning diameter. The fully loaded vehicle shall have a wall to wall turning diameter of 80 feet maximum in both directions.

2.1.6 Angles of approach and departure. The fully loaded vehicle shall have angles of approach and departure of not less than 11°.

2.1.7 Manuals and video tape.

2.1.7.1 Technical manuals. The overall format for the manuals may be military specification, commercial, or a combination of both. Each technical manual shall have a title page. Line art shall be used to the maximum extent possible for illustrations and parts lists.

The contractor shall validate the technical manuals for accuracy prior to submission to the procuring activity for verification. The contractor shall submit one complete set to the procuring activity for verification at least 30 days prior to the first production test. Any changes or corrections noted by the procuring activity shall be corrected and updated pages or manuals shall be submitted to the procuring activity.

Once approved by the procuring activity, the contractor shall pack two complete sets with each vehicle. An additional two complete sets shall be submitted to the procuring activity for stock.

2.1.7.1.1 Operator's manual. The operator's manual shall include all information required for the safe and efficient operation of the vehicle, including any special attachments or auxiliary equipment. The operator's manual shall include at least the following:

a. Location and function of all controls and instruments shall be illustrated and fully described.

b. Safety information that is consistent with the safety standards established by the Occupational Safety and Health Administration (OSHA).

c. Checks and adjustments in preparation for placing the vehicle for service upon receipt from the contractor.

d. Preparation for shipment or storage.

e. Warranty information and period of the warranty for the complete vehicle and for any component warranty that exceeds the warranty of the complete vehicle. Addresses and telephone numbers shall be provided for all warranty providers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

f. General description of and step-by-step instructions for the operation of the vehicle and its auxiliary equipment.

g. Description of the post-operational procedures (draining, flushing, et cetera).

h. Checklists for the daily maintenance inspection and mission readiness checks that the operator is expected to perform.

i. Procedures for towing a disabled vehicle.

j. Schedules for required preventative maintenance and required periodic maintenance.

2.1.7.1.2 Service manual. The service manual shall identify any special tools and test equipment required and shall cover troubleshooting and maintenance as well as minor and major repair procedures. The text shall contain performance specifications, tolerances, and fluid capacities; current, voltage, and resistance data; test procedures; and such illustrations and exploded views as may be required to permit proper maintenance by qualified mechanics. The manual shall contain an alphabetical subject index as well as a table of contents. The service manual shall contain at least the following, where applicable:

a. Hydraulic schematic.

b. Pneumatic schematic.

c. Electrical schematic.

d. Winterization schematic.

e. Schedules for required preventative maintenance and required periodic maintenance.

f. Location, procedure, and interval for parts of the truck and equipment which require lubrication.

2.1.7.1.3 Parts manual. The parts manual shall include illustrations and exploded views, as needed, to properly identify all parts, assemblies, subassemblies, and special equipment. All components of assemblies shown in illustrations or exploded views shall be identified by reference numbers which correspond to the reference numbers in the parts lists. All purchased parts shall be cross-referenced with the original manufacturer's name and part number. The parts identification manual shall provide the description, length, dimensions, and quantity of each item used per vehicle. The manual shall contain a numerical index. The parts manual shall contain a list of all of the component vendor names, addresses, and telephone numbers referenced in the parts list.

2.1.7.2 Video tape. A product familiarization video tape shall be provided with each truck. The tape shall verbally and visually provide all information required for operation and routine

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

inspection and maintenance of the vehicle and its components, using the manuals as a baseline. An additional copy of the video tape shall be provided to the procuring activity.

2.1.8 Painting, plating, and corrosion control.

2.1.8.1 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, shall not be used in intimate contact with each other.

2.1.8.2 Finish. Exterior surfaces shall be prepared, primed, and painted with polyurethane paint in accordance with all of the paint manufacturer's instructions and recommendations. Unless otherwise specified (see 6.2), the exterior finish color shall be Candy Apple Red, Sikkens Color Number FLNA3021, DuPont Color Number 97902U or 4737U, PPG Color Number 71528 (the PPG name for this color is Cardinal Red), or equal. When specified, the exterior finish color shall be Forest Green, Color Number 24052 of FED-STD-595, or Desert Sand, Color Number 30313 of FED-STD-595.

a. For vehicles painted Candy Apple Red, the cab upper body (from the bottom of the windshield) and roof shall be painted White, Color Number 17875 of FED-STD-595. Compartment interiors shall have a standard commercial finish. All bright metal and anodized parts, such as mirrors, horns, light bezels, and treadplate, shall not be painted. Roll-up compartment doors may be painted to match body color or left unpainted.

b. For vehicles painted Forest Green or Desert Sand, all exterior surfaces, including all normally bright metal and anodized parts and any interior surfaces visible with any compartment door open (but not the interior of the cab), shall be painted body color. This includes compartment shelves and mounting hardware, but does not include items mounted in the compartments. Non-metallic materials may be black or gray.

2.1.8.3 Reflective stripes. Horizontal, reflective stripes in accordance with 13-9.2 of NFPA 1901 shall be applied around the vehicle in an approximate plane with the headlights. Offsets in the reflective stripes shall be made to maximize the length of reflective surface. Bright metal trim or anodized parts may interrupt the reflective stripes. The pattern shall be seven inches wide with three reflective stripes (one inch reflective, one inch body color, three inches reflective, one inch body color, and one inch reflective). The reflective stripes shall be white for vehicles painted Candy Apple Red and Desert Sand, and black for vehicles painted Forest Green.

2.1.9 Identification plate. A permanently marked identification plate shall be securely mounted at the driver's compartment. The identification plate shall contain the following information:

NOMENCLATURE
MANUFACTURER'S MAKE AND MODEL
MANUFACTURER'S SERIAL NUMBER
REGISTRATION NUMBER
NATIONAL STOCK NUMBER (NSN)
VEHICLE CURB WEIGHT: kg (pounds)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

PAYLOAD, MAXIMUM: kg (pounds)
GROSS VEHICLE WEIGHT (GVW): kg (pounds)
DATE OF DELIVERY (month and year)
WARRANTY (months and km (miles))
CONTRACT NUMBER

2.2 Chassis and vehicle components.

2.2.1 Capacity. The vehicle shall have a minimum Gross Vehicle Weight Rating (GVWR) of 17,500 pounds.

2.2.2 Engine. The vehicle shall have a diesel engine.

2.2.3 Exhaust system. The exhaust system outlet(s) shall be directed away from personnel accessing equipment compartments or the roof access ladder.

2.2.4 Brake system. The vehicle shall be equipped with hydraulic four-wheel disc brakes with an all-wheel antilock brake system.

2.2.5 Tires and wheels. The vehicle shall be equipped with single tires on the front axle and dual tires on the rear axle. The vehicle shall be equipped with tubeless steel belted radial tires with on/off-road type tread mounted on steel disc wheel assemblies. If all tire and wheel assemblies are identical, one spare tire and wheel assembly shall be provided. If two different tire and wheel assemblies are provided, two spare tire and wheel assemblies shall be provided, one of each configuration. Spare tires and wheels are not required to be mounted on the vehicle.

2.2.6 Fenders. Rear fenders and fender liners having tire chain clearance shall be provided.

2.2.7 Steering. The vehicle shall be equipped with power steering.

2.2.8 Transmission. A fully automatic transmission with a hydraulic torque converter and at least five forward speeds shall be provided. The normal driving range selector position shall provide at least four gear ratios without movement of the selector. The net torque capacity and the net power rating of the transmission shall exceed the output ratings of the engine.

2.2.9 Traction control. The vehicle shall be equipped with limited slip, automatic locking, or driver controlled locking differentials in the rear axle and between the axles.

2.2.10 Fuel tank. Fuel tank(s) having a minimum usable capacity of 36 gallons shall be provided. The location of the fuel tank(s) shall protect it (them) from mechanical damage during normal use of the vehicle.

2.2.11 License plate bracket. A lighted license plate bracket shall be provided at the left rear of the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

2.3 Low-voltage electrical systems. The vehicle shall have a 12 volt electrical and starting system.

2.3.1 Alternator. Two 115 amp alternators shall be provided. The alternators shall be in accordance with 11-3 of NFPA 1901. The minimum continuous electrical load shall include operation of the air conditioning system.

2.3.2 Batteries. Dual batteries rated at 78 amp-hours and 750 cold cranking amps (cca) minimum each shall be provided. Batteries shall be of the maintenance-free type; addition of water shall not be required during normal service life. The battery cover and vent system shall be designed to prevent electrolyte loss during service and to keep the top of the battery free from electrolyte.

2.3.3 Battery charger or conditioner. The vehicle shall have a DC taper type battery charger or an automatic battery conditioner, providing a minimum 15 amp output. The charger/conditioner shall be permanently mounted on the vehicle in a properly ventilated, accessible location. The charger/conditioner shall be powered from the electrical shoreline receptacle (see 2.6.2). A charging indicator shall be installed next to the receptacle. When a battery conditioner is provided, it shall monitor the battery state of charge and, as necessary, automatically charge or maintain the batteries without gassing, depleting fluid level, overheating, or overcharging.

2.3.4 Warning lights. All warning lights shall use strobe type or light emitting diode (LED) elements. The warning light system, related components, and devices shall be in accordance with 11-8 of NFPA 1901.

2.3.4.1 Light bar. An eight element strobe-type light bar, with both forward and side facing strobe heads, shall be mounted on or above the cab roof. Forward facing lenses shall be red-red-red-white-white-red-red-red, with the white lights switched off in blocking right-of-way mode. Rearward facing lenses shall be red-red-red-amber-amber-red-red-red. The light bar shall be separately switched from the warning light panel.

2.3.4.2 Warning light color. When specified (see 6.2), the rearward, red strobe lights shall be replaced with amber. When specified (see 6.2), all red warning and strobe lights shall be replaced with blue.

2.3.4.3 Headlight flashing system. A high beam, alternating/flashing, headlight system shall be provided. The headlight flasher shall be separately switched from the warning light panel.

2.3.5 Audible warning devices.

2.3.5.1 Siren. The vehicle shall be equipped with an electronic siren system. The amplifier unit shall include volume control and selection of "Radio," "PA," "Manual," "Yelp," "Wail," and "Hi-Lo" (European) modes, and a magnetic noise canceling microphone. The amplifier, microphone, and controls shall be within reach of the driver and right front passenger. Siren activating foot switches shall be located in front of the driver and the right front passenger. The siren speaker shall be rated at 100 watts minimum and shall be located in a guarded position in the front bumper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

2.3.6 Work lighting.

2.3.6.1 Cab interior lights. Cab interior light levels shall be sufficient for reading maps or manuals.

2.3.6.2 Compartment lights. White lighting sufficient to provide an average minimum illumination of 1.0 footcandle shall be provided in each compartment greater than 4.0 cubic feet and having an opening greater than 144 square inches. Where a shelf is provided, this illumination shall be provided both above and below the shelf. Lights shall automatically illuminate only when the respective doors are opened.

2.3.6.3 Ladder, step, walkway, and area lights. Non-glare white lighting shall be provided at ladders and access steps where personnel work or climb during night operations. These area lights shall be controlled with switches on the cab instrument panel and near the light sources.

2.3.7 Scene lights. The vehicle shall be equipped with four 12 volt, 150 watt quartz halogen scene lights, two on each side, mounted at the top front and rear corners of the body. Switches for the scene lights shall be located in both the work areas and on the cab instrument panel.

2.3.8 Radio circuit. The vehicle shall have a separate 30 amp circuit, with breaker and a wire routed to a space provided between the driver and crew chief for a purchaser provided radio.

2.4 Driving and crew areas.

2.4.1 Cab. The vehicle shall have a non-tilting cab for at least three persons with four doors. The space behind the driver's seat shall be reserved for customer mounted storage compartments. At least one grab handle shall be provided for each crew member, located inside the cab for use while the vehicle is in motion.

2.4.1.1 Seats. Individual seats shall be provided for the driver and all crew members. Each seat shall be provided with a Type 2 seat belt assembly (i.e., 3-point restraint) in accordance with Code of Federal Regulations (CFR) 49 CFR 571.209.

2.4.1.2 Cab interior sound level. The maximum sound level at any seat location shall not exceed 83 dBA without any warning devices in operation, as measured in accordance with 49 CFR 393.94(c), "Vehicular interior noise levels test procedure," except that the test shall be performed with the vehicle traveling at a steady speed of 45 mph on a level, hard, smooth surface road.

2.4.1.3 Windshield and windows. The windshield and windows shall be of tinted safety glass.

2.4.1.4 Mirrors. Outside rearview mirrors shall be installed on each side of the cab, mounted on fold-back brackets.

2.4.1.5 Climate control system. The offeror/contractor's standard heater/defroster system shall be provided. Unless otherwise specified (see 6.2), the offeror/contractor's standard air conditioning

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

system shall also be provided. In 100° F ambient temperature with 50 percent relative humidity and at maximum compressor speed, the air conditioning system shall cool the fully occupied cab to 75° F within 30 minutes.

2.4.1.6 Instruments and controls. Gauges shall be provided for oil pressure and coolant temperature. In addition to the instruments and controls required by 12-3.4 of NFPA 1901, a master warning light control switch and work light switch(es) shall be provided within convenient reach of the seated driver. A compartment "Door Open" warning light and intermittent alarm shall be provided; the alarm shall sound when a compartment door is open and the parking brakes are released or the transmission is in any position other than neutral.

2.5 Body, compartments, and equipment mounting.

2.5.1 Body. The vehicle shall have an all aluminum or all stainless steel utility body. Aluminum thickness shall be at least 0.125 inches; stainless steel thickness shall be at least 0.090 inches.

2.5.2 Compartments. The utility body shall have side and may have rear compartments with a minimum of 250 cubic feet of enclosed storage space. Compartment floors shall be accessible to crew members standing on the ground. The compartment floor areas shall support a minimum load of 700 pounds without permanent deformation and should support a load of 1,000 pounds without permanent deformation.

2.5.2.1 Compartment doors. Compartments shall have clear anodized aluminum, counterbalanced, non-locking, roll-up doors. Door latch handles shall be full-width bar type. Door straps shall be provided to assist in closing the compartment doors when the rolled up door height exceeds six feet above the ground.

2.5.2.2 Scuffplates. Replaceable scuffplates shall be provided to prevent body damage from sliding equipment in and out of the compartments. The scuffplates shall be attached at the compartment threshold with flush headed capscrews and nuts.

2.5.2.3 Drip rails. Drip rails shall be provided over each compartment door. If the drip rails are not integral with the body, they shall be of anodized extruded aluminum and shall have a bright finish for trucks painted Candy Apple Red.

2.5.2.4 Shelves. An adjustable and removable compartment shelf shall be provided for every 18 inches of each vertical compartment door opening. Shelving adjustments shall require no more than common hand tools, and shall not require disassembly of fasteners. Shelves shall support a minimum of 200 pounds without permanent deformation and should support a minimum of 500 pounds without permanent deformation. Each shelf shall be accessible to crew members standing on the ground or steps mounted on the vehicle. Each shelf shall have drain holes located so as to allow for drainage of any water from the stowed equipment.

2.5.2.5 Drainage mats. Each compartment floor and shelf shall be covered with a removable mat designed to allow for drainage of any water from the stowed equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

2.5.2.6 Pass-through compartments with roll-out trays. Two pass-through compartments with roll-out trays shall be provided. The length of each roll-out tray shall be the full interior width of the utility body and shall extend four feet from either side of the utility body. Each roll-out tray shall support a 500 pound load without permanent deformation and should support a 1,000 pound load without permanent deformation. The roll-out trays shall be adjustable for incremental vertical height. Slide out adjustments shall be accomplished without the use of tools. Automatic latches shall secure the stowed trays and shall prevent over-travel when fully extended. One roll-out tray shall support a customer provided and mounted diesel engine powered rescue tool kit.

2.5.3 Ladder storage compartment. The vehicle shall have a storage compartment within the utility body for a 14 foot, two section extension ladder. The storage compartment shall be located at the rear of the vehicle and shall permit removal of the ladder by a person standing on the ground.

2.5.4 SCBA storage rack. A rack for storage of eight SCBA one-hour bottles shall be installed in a compartment. The top of the rack shall not be higher than 66 inches above the ground.

2.5.5 Ladder, handrails, and walkways. The utility body roof shall be covered with treadplate that shall support the weight of a crew member without permanent deformation. The utility body roof shall have an 8-inch high cargo tie-down rail around the perimeter. The utility body shall have a roof access ladder, with non-slip handrails and rungs. All ladders, stepping, standing, and walking surfaces shall be in accordance with 13-7 of NFPA 1901. Handrails shall be provided in accordance with 13-8 of NFPA 1901.

2.6 Line voltage electrical system.

2.6.1 Auxiliary generator. An electric start, diesel engine driven, 4.5 kilowatt (KW) (continuous rating), 120/240 volt, 60 hertz generator shall be permanently mounted in a ventilated compartment on the truck. The generator fuel supply shall be in common with the truck engine.

2.6.2 Electrical shoreline connection. The battery charger/conditioner and engine coolant heater shall be powered from a covered, polarized, insulated, labeled, recessed, male, 120 volt AC auto-eject receptacle. It shall be located on the exterior of the vehicle, either adjacent to the driver's door or on the left side of the body forward of the rear wheel. A 50 foot long, three wire, 15 amp rated, 120 volt, AC power cable, with straight blade (non twist-lock) connectors, shall be provided.

2.6.3 Receptacles. Four 120 volt AC, 20 amp, electrical outlets shall be provided, one at each corner of the body. Each outlet shall have weatherproof cover(s) and shall provide one twist-lock receptacle and one conventional receptacle. The receptacles shall be powered by the auxiliary generator (see 2.6.1).

2.6.4 Cable reel. The vehicle shall be equipped with an electrical cable reel mounted in the rear compartment near the center of the vehicle. The reel shall be equipped with 200 feet of 20 amp, 600 volt, 90° C insulated electrical cable. The electrical cable shall be equipped with a rubber ball stop to prevent cable pull through during rewinding operations. A four-way roller guide

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

shall be provided for the cable reel to prevent chafing of cable insulation. The cable reel shall have an electric rewind motor with provisions for manual rewind in the event of motor failure; the manual rewind handle shall be securely stored near the cable reel. A weatherproof duplex outlet box, with built-in circuit breakers and twist-lock receptacles, shall be connected to the cable end. The cable reel shall be powered by the auxiliary generator (see 2.6.1).

2.6.5 Light mast. When specified (see 6.2), the vehicle shall be equipped with an elevating light mast with two 1,500-watt "instant-on" halogen lights. The light mast shall be of a free standing design, shall not require outriggers or guywires, and shall sustain a light mast tip load of 150 pounds. The light mast shall extend a minimum of 18 feet above the ground. It shall stop at any vertical height and the light head shall rotate at least 350° (it is not necessary for the head to rotate when it is in the stored position). Electrical power shall be provided by the auxiliary generator (see 2.6.1). The lights and light mast shall be operable by a person standing on the ground. The light system shall be interlocked to operate only while the engine is running. Pneumatic controls, if provided, shall include a permanently set air regulator, air control valves, and a system air pressure gauge. A red warning light shall flash continuously, in front of the driver, while the light mast is extended. The vehicle horn shall blow continuously if the transmission is placed in gear or the parking brake is released while the mast is extended.

2.7 Winch. A winch with at least 12,000 pound-pull shall be installed, recessed behind the front bumper. The winch shall be electric or hydraulic powered and shall have one or more forward and reverse speeds of not less than 15 feet per minute. The winch shall be equipped with a minimum 125 feet of 3/8-inch galvanized aircraft cable, with 36 inch end chain and hook. The winch shall include a four way cable guide. A 10 foot minimum remote control cable shall be provided for operation of the winch. If an extended bumper is used, a cover fabricated of treadplate shall be installed over the winch and the space between the cab and bumper.

2.8 Workmanship. The vehicle, including all parts and accessories, shall be fabricated in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes, burrs, defects, and sharp edges; accuracy of dimensions, radii of fillets, and marking of parts and assemblies; thoroughness of welding, brazing, soldering, riveting, and painting; alignment of parts; tightness of fasteners; et cetera. The vehicle shall be thoroughly cleaned of all foreign matter.

3. REGULATORY REQUIREMENTS.

3.1 The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS.

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First production inspection (see 4.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

b. Conformance inspection (see 4.3).

4.2 First production inspection. The first production vehicle shall be subjected to the examinations and tests described in 4.6.3.1 through 4.6.3.5.

4.3 Conformance inspection. Each production vehicle shall be subjected to the examinations and tests described in 4.6.3.1, 4.6.3.2.1, 4.6.3.2.2, 4.6.3.2.4, 4.6.3.3, and 4.6.3.5.

4.4 Product conformance. The products provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

4.5 Commercial item requirement. The vehicle furnished shall comply with the "commercial item" definition of FAR 2.101 as of the date of award. The government reserves the right to require the offeror/contractor to prove that their product complies with the referenced commerciality requirements and each salient characteristic of this CID.

The offeror/contractor shall provide an itemized technical proposal that describes how the proposed model complies with each salient characteristic of this CID; a paragraph by paragraph response to the salient characteristics section of this CID shall be provided. The offeror/contractor shall provide two copies of their commercial descriptive catalogs with their offer as supporting reference to the itemized technical proposal. The offeror/contractor shall identify all modifications made to their commercial model in order to comply with the requirements herein.

4.6 Inspection requirements.

4.6.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein shall be laboratory precision type, calibrated at proper intervals to ensure laboratory accuracy.

4.6.2 Test rejection criteria. Throughout all tests specified herein, the vehicle shall be closely observed for the following conditions, which shall be cause for rejection:

a. Failure to conform to design or performance requirements specified herein or in the contractor's technical proposal.

b. Any spillage or leakage of any liquid, including fuel, coolant, lubricant, or hydraulic fluid, under any condition, except as allowed herein.

c. Structural failure of any component, including permanent deformation, or evidence of impending failure.

d. Evidence of excessive wear.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

e. Interference between the vehicle components or between the vehicle, the ground, and all required obstacles, with the exception of normal contact by the tires.

f. Misalignment of components.

g. Evidence of undesirable roadability characteristics, including instability in handling during cornering, braking, and while traversing all required terrain.

h. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.

i. Overheating of the engine, transmission, or any other vehicle component.

j. Evidence of corrosion.

4.6.3 Detailed inspection requirements.

4.6.3.1 Examination of product. Each vehicle shall be examined to verify compliance with the requirements herein. A Government generated checklist that identifies each relevant requirement and the inspection results shall be used. Particular attention shall be given to materials, workmanship, dimensions, surface finishes, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of each vehicle function shall be verified. Each production vehicle shall be inspected to a reduced version of the checklist .

4.6.3.2 Road tests. The following tests shall be performed in accordance with 2-12 of NFPA 1901.

4.6.3.2.1 Acceleration test. Each vehicle shall be tested to demonstrate compliance with 2.1.3.2. For the first production truck, a time-distance recorder shall be used to record data for this test.

4.6.3.2.2 Maximum speed test. Each vehicle shall be tested to demonstrate compliance with 2.1.3.3. For the first production unit, a time-distance recorder shall be used to record data for this test.

4.6.3.2.3 Gradeability test. The first production vehicle shall be tested to demonstrate compliance with 2.1.3.4.

4.6.3.2.4 Service brake system test. Each vehicle shall be tested in accordance with 2-12.5 of NFPA 1901. For the first production truck, a time-distance recorder shall be used to record data for this test.

4.6.3.2.5 Turning diameter test. The fully loaded first production vehicle shall be tested in accordance with SAE J695 to demonstrate compliance with 2.1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

4.6.3.2.6 Roadability test. The fully loaded first production vehicle shall be driven over 10 miles of paved and 10 miles of off-road terrains. All loads shall be removed and all structure and surfaces shall be visibly inspected for failure or permanent deformation.

4.6.3.3 Low voltage electrical system performance tests. The vehicle shall be tested in accordance with 11-14 of NFPA 1901.

4.6.3.4 Cab interior sound level test. The cab interior sound levels of the first production vehicle shall be measured in accordance with 49 CFR 393.94(c), "Vehicular interior noise levels test procedure," except that the test shall be performed with the vehicle traveling at a steady speed of 45 mph on a level, hard, smooth surface road.

4.6.3.5 Line voltage electrical system testing. The vehicle shall be tested in accordance with 21-14 of NFPA 1901.

5. PACKAGING.

5.1 Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents.

6.1.1 Department of Defense and Federal documents may be obtained from the Document Automation and Production Service, Bldg 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia PA 19111-5094.

6.1.2 The Code of Federal Regulations (CFR) may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington DC 20402.

6.1.3 SAE documents may be obtained from SAE, Inc., 400 Commonwealth Drive, Warrendale PA 15096.

6.1.4 NFPA documents may be obtained from NFPA, Batterymarch Park, Quincy MA 02269-9101.

6.2 Ordering data. The contract or order should specify the following:

a. Altitude for which vehicle operation is to be designed, if greater than 2,000 feet above sea level (see 2.1.1.1).

b. Finish color required (Forest Green or Desert Sand in place of Candy Apple Red) (see 2.1.8.2).

c. Warning light color required (amber or blue in place of red) (see 2.3.4.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

d. If air conditioning is not required (see 2.4.1.5).

e. If an elevating light mast is required (see 2.6.5).

Custodian:
Air Force - 99

Preparing Activity:
Air Force – 84

Agent Activity:
Air Force – 99

(Project No. 4210-0657)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.