[INCH-POUND]
A-A-59157
February 27, 1998
SUPERSEDING
MS53045A
14 October 1982

COMMERCIAL ITEM DESCRIPTION

RING, SIDE, AUTOMOTIVE WHEEL FOR TACTICAL WHEELED VEHICLES

The General Services Administration has authorized the use of this Commercial Item Description for all federal agencies.

1. SCOPE. This CID covers wheel rings for pneumatic tire wheels for wheeled tactical vehicles.

2. SALIENT CHARACTERISTICS

2.1 Interface. The rings shall interface with wheels manufactured in accordance with MS53044 for tire sizes 9.00-20, 10.00-20, 11.00-20, and 12.50-20. Rings shall attach securely to the specified wheel and provide retention of the specified tires. The rings shall be removable with common tire tools.

2.2 Finish. When applicable, rings shall be cleaned, treated, and primed with appropriate commercial methods. The finished item color shall be green. The finished item shall be chemical agent resistant. Rings shall show no evidence of corrosion when tested in accordance with ASTM B117, the exposure time shall be as specified in the contract (see 6.2).

2.3 Radial fatigue. When assembled with the appropriate disc and rim assembly, the wheel and ring assembly shall pass dynamic radial fatigue test requirements per SAE J267 with an 11.00-20 tire.

2.4 Cornering fatigue. The disc and rim assembly with which the ring described herein is intended to be used shall pass the dynamic cornering fatigue test requirements per SAE J267.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: U.S. Army Tank-automotive and Armaments Command, ATTN: AMSTA-TR-E/BLUE, Warren, MI 48397-5000.

AMSC N/A FSC 2530

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

3. REGULATORY REQUIREMENTS

3.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

3.2 Safety. The rings shall comply with Federal Motor Vehicle Safety Standards (FMVSS) 120.

4. QUALITY ASSURANCE PROVISIONS

4.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

4.2 Market acceptability. The item offered must have been sold to the Government or commercial market.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

6. NOTES

6.1 Source of documents.

6.1.1 Government documents. The Code of Federal Regulations (CFR) and FMVSS may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC, 20402. Copies of MS53044, "Wheel, Pneumatic Tire", may be obtained from Defense Automated Printing Service, Bldg 4D (Customer Service), 700 Robbins Avenue, Philadelphia, PA 19111-5094.

6.1.2 Non-Government documents. Copies of SAE J267, "Wheels/Rims - Trucks - Test Procedures and Performance Requirements", may be obtained from the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096. Copies of ASTM B117, "Standard Practice for Operating Salt Spray (Fog) Apparatus", may be obtained from the American Society for Testing and Materials, 100 Barr Harbor Drive, W. Conshohocken, PA 19428-2959.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this CID.
b. Issue of Department of Defense Index of Standards and Specifications (DoDISS) to be cited in the solicitation, and if required, the specific issue of individual documents referenced.
c. Exposure time for test per ASTM B117.
d. Selection of applicable level and packaging requirements.

6.3 Cross reference data. The following is a cross reference of old MS part numbers to the new CID number.

CID number	MS53045 part number	Ord drawing number	Nominal rim size
N/A	MS53045-2	7389626	16x6.5
A A 59157	MS53045-3	7389061	20x7.5
N/A	MS53045-4	7353671	20x10
N/A	MS53045-5	7355441	24x10

6.4 Wheel construction. Wheels for the rim size corresponding to the CID part number noted in 6.3 have previously been constructed in accordance with Army Drawings 7389618, 7389621, and 7388820.

6.5 Finish. In the past, the finishing procedure cited on Army Drawing 7389061 has proved successful in providing sufficient corrosion protection for the rings.

6.6 Quality assurance requirements. Historically, quality assurance requirements (QAR) 7389061 have applied to this item.

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - MC
Air Force - 99

Review Activities:
Air Force - 84
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITIES:
GSA-FSS

Preparing Activity:
Army - AT

(Project 2530-0401)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:04Z
Check the source to verify that this is the current version before use.