MIL-F-51174A(MU)
31 March 1967
SUPERSEDING
MIL-F-51174(MU)
1 June 1964

MILITARY SPECIFICATION
FILTER UNIT, GAS-PARTICULATE, 12 CFM, ARMORED AMBULANCE, M14

1. SCOPE

1.1 This specification covers a small gas-particulate filter unit.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-636	-	Box, Fiberboard.
PPP-T-76	-	Tape, Pressure-Sensitive Adhesive Paper, (For Carton Sealing).

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-P-130	-	Paper, Wrapping, Laminated and Creped.
MIL-P-51070	-	Purifier, Air, M2A2.
MIL-I-51175	-	Installation Kit, Gas-Particulate Filter Unit, Armored Vehicle, Ambulance, M37.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:51Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

DL5-19-1828	-	Filter Unit, Gas-Particulate, 12 CFM, Armored Ambulance, M14. (All drawings referenced in this specification except D150-2-1, are listed on the above Edgewood Arsenal drawings).
D150-2-1	-	Marking Diagram for Shipping Containers.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-19-1828 or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the filter unit shall conform to the specifications and drawings listed on Drawing DL5-19-1828 and subsidiary drawings.

3.2 Workmanship. The filter unit shall be free of damage, such as bent, chipped, or burred metal parts and cracked, kinked or torn rubber parts or foreign matter, such as dirt, oil or viscous materials.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Regular production.

4.2.1 Lotting. A lot shall consist of the filter units produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions. However, no more than one lot of air purifiers shall be represented in any one lot of finished filter units.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:51Z
Check the source to verify that this is the current version before use.

4.2.2 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection.

4.2.3.1 For examination. Sample filter units and the level A preparation for delivery thereof shall be examined in accordance with the classification of defects and MIL-STD-105.

4.2.3.2 Classification of defects.

(a) Filter unit, gas-particulate, 12 cfm, armored ambulance, M14 DL5-19-1828).

Categories		Defects
Critical:		None defined
Major:		AQL 1.0 percent defective
	101	Component missing or incorrectly assembled
	102	Marking incorrect, missing, or illegible
	103	Workmanship (3.2)

(b) Preparation for delivery.

Categories		Defects
Critical:		None defined
Major:		AQL 2.5 percent defective
	101	Intermediate packaging incorrect
	102	Loose package
	103	Marking incorrect, missing or illegible

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:51Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Cleaning and drying. The components comprising a filter unit shall be cleaned and dried in accordance with MIL-P-116. Cleaning process C-1 and any of the drying procedures listed in cited specification shall be used.

5.2 Preservation and packaging, level A.

5.2.1 Unit packaging.

5.2.1.1 Hose. Fittings attached to hose shall be cushioned by wrapping with greaseproof barrier material conforming to type II, grade A, class 2 of MIL-B-121 or with laminated or creped wrapping paper conforming to MIL-P-130. The wraps shall be secured in place by either tying or taping.

5.2.1.2 Installation kit. The kit shall be preserved and unit packaged in accordance with level A requirements of MIL-I-51175.

5.2.1.3 Air purifier. The air purifier shall be packaged in accordance with the level A requirements of MIL-P-51070.

5.2.1.4 Headpiece. The headpiece placed within its carrier in the manner as specified with method IC-1 or IC-3 of MIL-P-116.

5.2.1.5 Technical publications. Technical publications shall be packaged in accordance with method IC-1 or IC-3 of MIL-P-116.

5.2.2 Intermediate packaging.

5.2.2.1 Container 1. The contents of container 1 shall consist of: two 2-foot lengths of hose, two 4-foot lengths of hose, two 6-foot lengths of hose, two 9-foot lengths of hose, one assembly consisting of two 6-foot lengths of hose, and technical publications. These items unit packaged as specified in 5.2.1.1 and 5.2.1.5 shall be intermediately packaged together in a W5c, style RSC, fiberboard box, conforming to PPP-B-636. The required lengths of hose shall be loosely coiled within the box. If required, internal cushioning and blocking shall be used to make a tight package. The unit packaged technical publications shall be placed inside the box on top of the packaged hose. The top and bottom flaps of the box shall be closed by taping in accordance with the appendix of PPP-B-636 for interior boxes, except that pressure-sensitive tape conforming to PPP-T-76 shall be used.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:51Z
Check the source to verify that this is the current version before use.

5.2.2.2 Container II. The contents of container II shall consist of one installation kit packaged as specified in MIL-I-51175.

5.2.2.3 Container III. The contents of container III shall consist of one air purifier packaged as specified in 5.2.1.3.

5.2.2.4 Container IV. Six headpieces, unit packaged as specified in 5.2.1.4, shall be intermediately packaged together in a W5c, style RSC, fiberboard box conforming to PPP-B-636. If required, internal cushioning and blocking shall be used to make a tight package. The top and bottom flaps of the box shall be closed by taping in accordance with the appendix to PPP-B-636 for interior boxes, except that pressure-sensitive tape conforming to PPP-T-76 shall be used.

5.3 Packing. Level shall be as specified (see 6.2).

5.3.1 Level A. One of each of containers I, II, III and IV specified in 5.2.2 shall be packed in a V3c, style RSC, fiberboard box conforming to PPP-B-636. In addition to the specified closure requirements, all box seams, including the manufacturer's joint, shall be taped as specified in the appendix. As an alternative, tape conforming to PPP-T-76 may be used. When metal banding is used, it shall be galvanized.

5.3.2 Level C. One of each of containers I, II, III and IV specified in 5.2.2 shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Containers shall be in accordance with Uniform Freight Classification rules or regulations of other carriers applicable to the mode of transportation.

5.4 Marking. In addition to any special marking required by the contract or order, unit packages shall be marked in accordance with MIL-STD-129. The exterior shipping container shall be marked in accordance with Drawing D150-2-1.

5.5 Repair parts. When this item is being procured for stockage and issue as a repair part, preservation, packaging, packing and marking shall be as specified on the repair parts packaging data sheet (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:51Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The filter unit covered by this specification is intended to remove toxic particles and gases from air supplied to wounded personnel while being evacuated by an armored ambulance.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Level of packing required.

6.3 Component specifications. The component specifications for the M14 Filter Unit are:

Title	Number
Carrier, Hospital Protector Headpiece, M12	MIL-C-14041
Coupling Half, Quick Disconnect	MIL-C-51073
Fan, Centrifugal, 12 CFM	MIL-F-50084
Filter, Gas, 12 CFM, M12A1	MIL-F-14512
Filter, Particulate, 12 CFM, M13	MIL-F-52011
Headpiece, Hospital Collective Protector, M13A1	MIL-H-51182
Hose: for Filter Units	MIL-H-14506
Installation Kit, Gas-Particulate Filter Unit, Armored Vehicle, Ambulance, M37	MIL-I-51175
Precleaner, Air Purifier, M1A1	MIL-P-50085
Purifier, Air, M2A2	MIL-P-51070
Separator, Dust	MIL-S-50087
Valve, Outlet, C19	MIL-V-51195

6.4 Packaging data sheet. The packaging data sheet is identified by the Federal stock number for this item and should be ordered from the Commanding Officer, Edgewood Arsenal, ATTN: SMUEA-TSE-DD, Edgewood Arsenal, Maryland 21010.

Custodian:

Army - MU

Preparing activity:

Army - MU (EA)

Project No. 4240-A279

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:51Z
Check the source to verify that this is the current version before use.

TO DETACH FORM - CUT ON THIS LINE

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119 R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4853, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:51Z
Check the source to verify that this is the current version before use.