MILITARY SPECIFICATION

RESERVOIR SYSTEM, FABRIC, COLLAPSIBLE, 25,000 BBL, PETROLEUM: PACKAGING OF

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for methods, materials, and procedures for the preservation, packing, and marking of Reservoir System, Fabric, Collapsible, 25,000 BBL, Petroleum (NSN 5430-00-015-0883).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

RR-C-271	- Chains and Attachments, Welded, Weldless.
PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-676	- Boxes, Setup.
PPP-P-40	- Packaging and Packing of Hand Tools.
PPP-T-60	- Tape: Packaging, Waterproof.

FSC 5430

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-V-3	- Valves, Fittings, and Flanges (Except for Systems Indicated Herein): Packaging of.
MIL-C-104	- Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	- Preservation-Packaging, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-P-775	- Packaging of Hose, Hose Assemblies, Rubber, Plastic, Fabric, or Metal (Including Tubing); and Fittings, Nozzles, and Strainers.
MIL-C-3131	- Cordage: Preparation for Delivery of.
MIL-C-6183	- Cork and Rubber Composition Sheet; for Aromatic Fuel and Oil Resistant Gaskets.
MIL-A-7021	- Asbestos Sheet, Compressed, for Fuel, Lubricant, Coolant, Water, and High Temperature Resistant Gaskets.
MIL-P-10388	- Pipe Fittings: One or More Ends Grooved.
MIL-P-10603	- Pumps and Pumping Units, Centrifugal, Power-Driven, for Water, Packaging of.
MIL-P-11087	- Pipe, Steel: Grooved, Threaded, or Plain Ends.
MIL-F-17280	- Fitting, Marine, Minesweeping, Non-magnetic.
MIL-C-52938	- Cover, Air-Supported, for 25,000 Barrel, Embankment-Supported, Fuel Reservoir.
MIL-R-52937	- Reservoir, Fabric, Collapsible, 25,000 Barrel, Petroleum.
MIL-A-28624	- Auger, Earth, Portable, Hand Held, Two man, Gasoline Engine Driven.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

MIL-STD-163	- Steel Mill Products, Preparation for Shipment and Storage.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 1616 P Street, NW, Washington, DC 20036.)

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects (see 6.4).

3.2 Preproduction pack. The contractor shall furnish a preproduction pack for examination within the time frame specified (see 6.2) to prove, prior to starting production packaging, that the applied preservation, packing, and marking comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3). The preproduction pack may be accomplished utilizing either the preproduction model or a

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

production model. If the preproduction model is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the preproduction model and the production model.

3.3 Preservation. Preservation shall be Level A or Commercial as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Preservatives. Preservatives specified herein shall conform to the applicable specifications listed in and shall be applied in accordance with MIL-P-116.

3.3.1.2 Unprotected surfaces. Unpainted exterior metal surfaces requiring the application of a contract preservative in accordance with MIL-P-116 and not specifically specified herein shall be coated with Type P-1 preservative.

3.3.1.3 Reservoir. Each complete reservoir and all items issued with the reservoir shall be preserved in accordance with the Level A requirements of MIL-R-52937.

3.3.1.4 Cover. Each complete cover and all items issued with the cover shall be preserved in accordance with the Level A requirements of MIL-C-52938.

3.3.1.5 Pump. Each complete pump and all items issued with the pump shall be preserved in accordance with the Level A requirements of MIL-P-10603.

3.3.1.6 Auger. Each complete auger shall be preserved in accordance with the Level A requirements of MIL-A-28624 except components not specifically specified shall be preserved in accordance with MIL-P-116, using the most appropriate method and the box for consolidated packaging shall be Class Weather-Resistant.

3.3.1.7 Pipe and pipe fittings. Pipe and pipe fittings with grooved ends shall have the ends protected as specified in MIL-P-11087 or MIL-P-10388. Other fittings shall be preserved in accordance with MIL-V-3.

3.3.1.8 Rope. Rope shall be prepared in accordance with the Level A packaging requirements of MIL-C-3131.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

3.3.1.9 Wire rope fittings. Wire rope fittings shall be preserved in accordance with the Level A preservation and packaging requirements of MIL-F-17280.

3.3.1.10 Wire rope and steel reinforcing bars. Wire rope and steel reinforcing bars shall be preserved in accordance with MIL-STD-163.

3.3.1.11 Cutting punch, knife, expanding and tamping bar, and rigid splice for tamping bar. Each item shall be preserved in accordance with the Level A preservation and packaging requirements of PPP-P-40.

3.3.1.12 Pressure gage. Each pressure gage shall be individually preserved in accordance with MIL-P-116, Method IC-2, using the contractor's commercial carton or a close-fitting box conforming to PPP-B-566 or PPP-B-676, variety, style, type, and class optional.

3.3.1.13 Blower assemblies. Drive belts shall be released from tension and all openings into the blower motor sealed with tape conforming to PPP-T-60, Type IV.

3.3.1.14 Control panel, heater, vapor meter, and soil test probe. Each item shall be individually preserved in accordance with MIL-P-116, Method IIb. The inner container shall be the contractor's standard commercial carton or a close-fitting box conforming to PPP-B-636, Class Domestic. The outer container shall conform to PPP-B-636, Class Weather-Resistant.

3.3.1.15 Electric motor. The spare electric motor shall be preserved as specified for the control panel.

3.3.1.16 Flowmeter. Openings into the flowmeter shall be sealed with plastic or metal caps or with material conforming to MIL-B-121, Type I, Grade A, Class 1 or 2 and secured in place with tape conforming to PPP-T-60, Type IV. The flowmeter shall then be placed in a close-fitting box conforming to PPP-B-601, Overseas Type, style optional.

3.3.1.17 Gaskets. Gasket material furnished in sheet form shall be protected in accordance with the Level A packaging requirements of MIL-A-7021 or MIL-C-6183 as applicable. The muffler gasket shall be contained between two pieces of fiberboard, of a size slightly larger than the gasket, and preserved in accordance with MIL-P-116, Method IC-1 or IC-3.

3.3.1.18 Gasket sealing compound and vent tieup stake. Neither item shall require preservation, but shall be consolidated with other items as specified in 3.3.1.28.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

3.3.1.19 Ground rod. The ground rod with attachments shall be placed and cushioned in a close-fitting box conforming to PPP-B-636, W6c, style optional. Box closure shall be in accordance with the appendix to the box specification.

3.3.1.20 Magnetic starter and time delay relay. The spare magnetic starter and time delay relay shall each be preserved in accordance with MIL-P-116, Method IIb. The inner container shall be the contractor's standard commercial carton or in a close-fitting box conforming to PPP-B-566 or PPP-B-676, variety, style, type, and class optional. The outer container shall conform to PPP-B-636, Class Weather-Resistant.

3.3.1.21 V-belts. Spare V-belts shall be individually preserved in accordance with MIL-P-116, Method IC-1 or IC-3.

3.3.1.22 Plastic sheet and strip. Plastic film shall be placed in a close-fitting box conforming to PPP-B-636, W5c, style optional. Box closure shall be in accordance with Method V in the appendix to the box specification. In place of the above, plastic film supplied in a commercial carton may be preserved in accordance with MIL-P-116, Method IC-2.

3.3.1.23 Chains and attachments. Chains and attachments shall be preserved in accordance with RR-C-271.

3.3.1.24 Hoses and hose assemblies. Hoses and hose assemblies shall be preserved in accordance with the Level A requirements of MIL-P-775.

3.3.1.25 Anchor assemblies. All expanding anchors shall be placed together and all threaded rods shall be placed together in separated close-fitting boxes conforming to PPP-B-601, Overseas Type, style optional or PPP-B-621, Class 2, style optional. Blocking and bracing of the contents within the box to prevent movement shall be provided. Box closure shall be in accordance with the appendix to the applicable box specification. Strapping shall not be required.

3.3.1.26 Nuts, cap screws, and washers. Items of like description shall be preserved together in accordance with MIL-P-116, Method IC-1 or IC-2 as applicable to the quantity issued. Items preserved Method IC-2 shall be contained in the contractor's commercial carton or a close-fitting box conforming to PPP-B-566 or PPP-B-676, variety, style, type, and class optional or PPP-B-636, Class Domestic.

3.3.1.27 Other components. Other components not specifically mentioned herein requiring protection from corrosion or physical or mechanical damage shall be preserved as specified for components of similar design and construction, or preserved in accordance with MIL-P-116, using the most appropriate method.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

3.3.1.28 Consolidation. Components requiring the protection of a wood box to prevent loss or damage or to aid in segregation, erection, or ease of accomplishing the packing specified in 3.4 shall be packed in boxes conforming to PPP-B-601, Overseas Type, style optional or PPP-B-621, Class 2, style optional, in quantities not to exceed the weight limitation of the box. The contents shall be blocked, braced, and anchored within the box to prevent movement or damage. Strapping shall not be required.

3.3.2 Commercial. Components of the reservoir system shall be preserved in a manner to assure protection against deterioration and damage from the contractor to the initial destination.

3.4 Packing. Packing shall be Level A or Commercial as specified (see 6.2).

3.4.1 Level A.

3.4.1.1 Reservoir. Each complete reservoir and all items issued with the reservoir shall be packed in accordance with the Level A requirements of MIL-R-52937.

3.4.1.2 Cover. Each complete cover and all items issued with the cover shall be packed in accordance with the Level A requirements of MIL-C-52938.

3.4.1.3 Pipe. Pipe, 240 inches long, shall be shipped loose. All other pipe shall be packed in a crate as specified in 3.4.1.4.

3.4.1.4 Other components. All other components not specified in 3.4.1.1, 3.4.1.2, and 3.4.1.3 shall be packed together in one or more crates as applicable. The crates shall conform to MIL-C-104, Type I, Class 1 or 2, Style a. The blower assemblies shall be secured, in an upright position, to the crate base by bolting. Arrangement of the other components and methods of securing to the crate base shall be in a manner to provide minimum cube and low center of gravity. Blocking, bracing and anchoring of the components shall be in accordance with the appendix to the crate specification and in accordance with the appendix to the crate specification and in accordance with MIL-STD-1186.

3.4.2 Commercial. Components of the reservoir system shall be packed in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings. Containers shall comply with Uniform Freight Classification rules or National Motor Freight Classification rules.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

3.5 Marking.

3.5.1 Military. Marking for military levels of protection shall be in accordance with MIL-STD-129.

3.5.2 Commercial. Marking for commercial packaging shall reflect as a minimum, the item name, National Stock Number, quantity, contract number, and appropriate address markings on each shipping container or loose component. The marking shall be applied with a waterproof material, shall be legible, and shall provide a definite contrast.

3.6 Workmanship. Workmanship shall be such as to provide maximum protection to the reservoir system components by application of the requirements specified herein, to prevent corrosion, deterioration, and mechanical or physical damage during handling, shipment, and storage.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects specified in 4.4.3. Presence of one or more defects shall be cause for rejection of the preproduction pack.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.4.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.3 Examination. Samples selected in accordance with 4.4.2 shall be examined for the defects marked "X" for the applicable level in Table I. Acceptable Quality Level (AQL) shall be 2.5 percent defective.

Table I. Classification of Defects

No.	Defects	Level	
		A	Commercial
101.	Materials, methods, or containers not as specified. Each incorrect material, method, or container shall constitute one defect.	X	X
102.	Unprotected exterior metal surfaces not coated with preservative as specified.	X	-
103.	Reservoir not preserved and packed in accordance with referenced document.	X	-
104.	Cover not preserved and packed in accordance with referenced document.	X	-
105.	Pump and pump components not preserved in accordance with referenced document.	X	-
106.	Auger and auger components not preserved in accordance with the referenced documents.	X	-
107.	Pipe and pipe fittings not preserved in accordance with the referenced documents.	X	-
108.	Rope not preserved in accordance with the referenced document.	X	-
109.	Wire rope fittings not preserved in accordance with the referenced document.	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z.
Check the source to verify that this is the current version before use.

Table I. Classification of Defects (Cont'd)

No.	Defects	Level	
		A	Commercial
110.	Wire rope and steel reinforcing bars not preserved in accordance with the referenced document.	X	-
111.	Handtools not preserved in accordance with the referenced document.	X	-
112.	Pressure gages not preserved as specified.	X	-
113.	Drive belts not released from tension and blower motor not sealed as specified.	X	-
114.	Control panel, heater, vapor meter, and soil test probe not preserved as specified.	X	-
115.	Spare electric motor not preserved as specified.	X	-
116.	Flowmeter not sealed and placed in box as specified.	X	-
117.	Gasket material not protected in accordance with the referenced documents.	X	-
118.	Ground rod with attachments not placed and cushioned within the box specified.	X	-
119.	Magnetic starter and time delay relay not preserved as specified.	X	-
120.	Spare V-belts not preserved as specified.	X	-
121.	Plastic sheet and strip not preserved as specified.	X	-
122.	Chains and attachments not preserved in accordance with the referenced document.	X	-
123.	Hoses and hose assemblies not preserved in accordance with the referenced document.	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

Table I. Classification of Defects (Cont'd)

No.	Defects	Level	
		A	Commercial
124.	Anchor assemblies not placed in a box and secured as specified.	X	-
125.	Nuts, cap screws, and washers not preserved as specified.	X	-
126.	Consolidation not as specified.	X	-
127.	Packing not as specified.	X	-
128.	Marking missing, illegible, incorrect, or incomplete.	X	X

5. PACKAGING

(This section not applicable to this specification.)

6. NOTES

6.1 Intended use. It is intended that this specification cover the preservation, packing, and marking requirements of Reservoir System, SC 5430-97-CL-E02 and shall be used for direct reference in contracts or orders.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of the preproduction pack (see 3.2).
(c) Degree of preservation and packing required (see 3.3 and 3.4).

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the contractor of his obligation to preserve, pack, and mark the reservoir system in accordance with this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.1).

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 5430-A116

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research and
Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-R-52928(ME) Reservoir System, Fabric, Collapsible, 25,000 BBL, Petroleum: Packaging of

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.