MILITARY SPECIFICATION

STAND, ATOMIC WARHEAD SECTION: H4234

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of stand entitled Stand, Atomic Warhead Section: H4234 which is used with the Sprint warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-I-6866	- Inspections, Penetrant Method of.
MIL-W-22248	- Weldments, Aluminum and Aluminum Alloy.

DRAWINGS

ORDNANCE CORPS

8889038	- Pillow Block.
8889040	- Plate, Pivot.
8889041	- Plate, Indexing.
8889042	- Pivot Plate Assembly.
8889044	- Plate, Pivot Indexing.
8889045	- Frame.
8889049	- Block, Rim Stand.
8889050	- Stand, Atomic Warhead Section H4234.
8889053	- Block, Spacer Stand.
8889055	- Plate.
9239259	- Beam Assembly.
9242950	- Fixture Load H4234, Warhead Simulator.
9266999	- Crate, Wood, Packing for Stand, Atomic Warhead Section H4234.

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

FSC 1190

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The stand shall comply with all requirements specified on the drawing (dwg) 8889050, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Proof load. The stand will support an approved load of 1250 minus 50 pounds arranged so that 440 minus 10 pounds is equally supported by the "stand-on" platform. The total load shall be applied for 6 ± 1 minute without damage. In addition, the balance of the load of 790 ± 20 pounds shall possess the identical mounting features and center of gravity of a warhead section (Sprint) and be capable of being oriented in all of its 8 designated positions without touching the frame of the stand. The stand with its load also shall be capable of being rotated 360° without any of its 4 wheels binding and shall not move when its two floor locks are released. Testing shall be as described in 4.4.1.

3.6 Welds. Welding shall be in accordance with MIL-W-22248, when tested as specified in 4.4.2.

3.7 Penetrant. Penetrant shall be in accordance with MIL-I-6866, when tested as specified in 4.4.2.

3.8 Workmanship.

3.8.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.8.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.8.3 Burrs. Parts shall be free from burrs.

3.8.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.8.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 2 complete assemblies (see dwg 8889050) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Proof load (see 3.5)		X
3. Welds (see 3.6)		X
4. Penetrant (see 3.7)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Pillow block (see dwg 8889038).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect perpendicularity (2 places)	Gage
102.	Incorrect width of slot	Gage
103.	Evidence of protective finish in areas excluded by note on dwg	Visual
104.	Improper weldments	Visual
105.	Evidence of poor workmanship (see 3.8)	Visual
106.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Damaged protective finish exposing base metal or improper	Visual

4.3.2.1.2 Plate, pivot (see dwg 8889040).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect diameter of large hole (1)	Gage
102.	Incorrect symmetry	Gage
103.	Incorrect taper	Gage
104.	Evidence of poor workmanship (see 3.8)	Visual
105.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.3 Plate, indexing (see dwg 8889041).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Mislocation of hole (8)	Gage
	102. Incorrect diameter of hole (8)	Gage
	103. Incorrect diameter of center hole	Gage
	104. Countersink missing in hole (8)	Visual
	105. Evidence of poor workmanship (see 3.8)	Visual
	106. Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

4.3.2.1.4 Pivot plate assembly (see dwg 8889042).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Improper welding (see 3.6)	Visual
	102. Evidence of poor workmanship (see 3.8)	Visual
	103. Evidence of protective finish on areas excluded by note on dwg	Visual
	104. Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

4.3.2.1.5 Plate, pivot indexing (see dwg 8889044).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Incorrect diameter of hole	Gage
	102. Incorrect symmetry	Gage
	103. Incorrect taper	Gage
	104. Evidence of poor workmanship (see 3.8)	Visual
	105. Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.6 Block, rim, stand (see dwg 8889049).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect inside radius	Gage
102.	Incorrect diameter of hole (2)	Gage
103.	Incorrect angle (Sec A-A)	Gage
104.	Evidence of poor workmanship (see 3.8)	Visual
105.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

4.3.2.1.7 Block, spacer stand (see dwg 8889053).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect angle (View AA)	Gage
102.	Incorrect radius	Gage
103.	Incorrect width of oval shaped hole (2)	Gage
104.	Evidence of poor workmanship (see 3.8)	Visual
105.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

4.3.2.1.8 Plate (see dwg 8889055).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Mislocation of countersunk hole (6)	Gage
102.	Incorrect diameter of countersunk hole (6)	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

103.	Countersink missing, incomplete, damaged (6 places)	Visual
104.	Incorrect pitch diameter of thread (min) (2 places)	Gage
105.	Incorrect width of oval shaped hole (2)	Gage
106.	Incorrect length	Gage
107.	Evidence of poor workmanship (see 3.8)	Visual
108.	Incorrect symmetry (2 places)	Gage
109.	Objective evidence relating to material missing or improper (see 3.1)	Visual

Minor: None defined.

4.3.2.1.9 Beam assembly (see dwg 9239259).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Incorrect size of fillet weld	Gage
102.	Improper weldment	Visual
103.	Areas described in note on dwg not free of protective finish	Visual
104.	Evidence of poor workmanship (see 3.8)	Visual
105.	Components damaged, loose, missing, improper or improperly assembled	Manual/Visual
106.	Incorrect symmetry	Gage
107.	Incorrect concentricity (min diameter)	Gage
108.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Protective finish damaged exposing base metal or improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.10 Frame (see dwg 8889045).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect location of pillow block hole (4)	Gage
102.	Incorrect parallelism of top surface	Gage
103.	Improper weldment	Visual
104.	Area described in note on dwg not free of paint	Visual
105.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

4.3.2.1.11 Stand, atomic warhead section H4234 (see dwg 8889050).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Components missing, damaged, improper, loose, or improperly assembled	Manual/Visual
102.	Evidence of poor workmanship (see 3.8)	Visual
103.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Marking missing, improper, illegible or misplaced (see 3.4)	Visual
202.	Protective finish damaged exposing base metal (only when required by component drawing)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.12 Crate, wood, packing for stand, atomic warhead section H4234 (see dwg 9266999 base).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Component, missing, damaged, loose, improper or is improperly assembled	Visual/Manual
102.	Insufficient torque (100 ± 10 inch pounds) on bolt (4) to secure ring	Gage
103.	Incorrect length at base	Gage
104.	Incorrect width	Gage
105.	Incorrect dia of thru hole (2)	Gage
106.	Construction not in compliance with applicable notes on dwg	Manual/Visual
107.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.8)	Visual

4.3.2.1.13 Crate, wood, packing for stand, atomic warhead section H4234 (see dwg 9266999 cover).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect inside dimension (2 places)	Gage
102.	Component, missing, damaged, loose, improper or is improperly assembled	Manual/Visual
103.	Construction not in compliance with applicable notes on dwg	Manual/Visual
104.	Insufficient torque (50 ± 5 inch pounds) in screw to secure cover to base	Gage
105.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.14 Preparation for delivery (see dwg 9266999).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Packaging not in compliance with instructions	Manual/Visual
	102. Marking, missing, improper, illegible, or improperly located	Visual
	103. Incorrect total weight	Gage
	104. Strap loose, misrouted, improper (before cover is assembled to base)	Manual/Visual
Minor:		
	201. Evidence of poor workmanship (see 3.8)	Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Proof load	Major

This test is not considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Proof load. Each stand shall be tested in accordance with 4.4.1. If any item fails to comply with 3.5, the item shall be rejected and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major and Minor characteristics and tests. Inspection and testing shall be performed with the acceptance test equipment, operating instructions and calibration instructions prepared by the contractor. The contractor shall obtain approval of such designs, operating instructions and special calibration instructions as specified in 6.3 prior to use on the contract.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.4.1 Proof load. The load shall be installed as described in 3.5 and torque per dwg 9242950. While the load is supported by the stand, operate the stand to determine conformance to 3.5 and after 6 ± 1 minute remove load and examine for damage (see 6.4).

4.4.2 Welds. Inspection criteria to determine conformance of fillet welds and weldments are defined in MIL-W-22248 and specifically under "Standards of Acceptance" and "Inspection", as applicable. Penetrant inspection shall be in accordance with Specification MIL-I-6866, Type I method.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The stand shall be packaged in accordance with dwg 9266999 using the specified moisture barrier.

5.1.2 Level C. The stand shall be packaged in accordance with dwg 9266999 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The stand shall be packed in accordance with dwg 9266999.

5.3 Marking. Marking shall be as specified in accordance with dwg 9266999.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.2.1). Data specified in 4.3.2.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

6.4 *Damage. A defect that is detectable by visual examination. Typical defects are as follows: Crack in weldment, damaged threads, deformed structural member, cracked structural member, damaged finish exposing base metal; marking obliterated.

*A 5X magnifying glass may be used while examining for damages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-2308, dated 30 May 1972.

Custodian:
Army - (AR)

Preparing activity:
Army - (AR)

Project No. 1190-A103

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.