NOT MEASUREMENT SENSITIVE

MIL-S-52836A(ME)
6 February 1992
SUPERSEDING
MIL-S-52836(ME)
22 November 1974

MILITARY SPECIFICATION

SUPPLEMENTARY SET, BRIDGE, TROOP SUPPORT,

PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the preservation, packing, and marking marking of the Troop Support Bridge Supplementary Set, SC 5420-97-CL-E51.

2. APPLICABLE DOCUMENTS

2.1 Government Documents.

2.2 Specifications and standards, and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed it the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-566 - Boxes, Folding, Paperboard.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A AREA PACK

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:35Z
Check the source to verify that this is the current version before use.

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock Corner.
PPP-B-636	- Boxes, Shipping Fiberboard.
PPP-B-1055	- Barrier Material, Waterproofed, Flexible.
PPP-P-40	- Packaging and Packing of Hand Tools.
PPP-T-60	- Tape: Packaging, Waterproof.

MILITARY

MIL-C-104	- Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	- Preservation, Methods of.
MIL-H-775	- Hose, Rubber or Fabric (Including Tubing); and Fittings, Nozzles and Strainers,Packaging of.
MIL-H-3280	- Hoist, Chain, Manually Operated, Packaging of.
MIL-F-3747	- Flashlights: Plastic Case, Tubular (Regular,Explosion-Proof, Explosion-Proof Heat Resistant, Traffic Directing, and Inspection-Light).
MIL-L-4387	- Lubrication Dispensing Equipment Accessories.
MIL-T-12173	- Traveler, Bicycle.
MIL-T-12442	- Tower, Cable, Anchor.
MIL-C-14518	- Connector, Bridle Line: Sheave Type.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-163	- Steel Mill Products, Preparation for Shipment and Storage.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government Documents. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted ate those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents no listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY OF TESTING AND MATERIALS (ASTM)

B 660	- Packaging/Packing of Aluminum and Magnesium Products, Standard Practice for.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:35Z
Check the source to verify that this is the currentversion before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Order Section, 2200 Mill Road, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Material. Material shall be as specified herein and in the applicable specifications and standards. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3 Preservation and packaging. Preservation shall be Level A or C as specified (see 6.2).

3.3.1 Level A.

Source: https://assist.dla.mil -- Downloaded: 20260-22T21:35Z
Check the source to verify that this is the current version before use.

3.3.1.1 Preservatives. Preservatives specified herein shall conform to applicable specifications noted in MIL-P-116 and shall be applied in accordance with MIL-P-116.

3.3.1.2 Unprotected surfaces. Unpainted or otherwise unprotected exterior metal surfaces or components, such as bolts, nuts, pins, exposed threads or any other unprotected exterior metal surfaces not specified herein requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative.

3.3.1.3 Blocking, bracing, and cushioning. Unless otherwise secured, boxed contents shall be blocked, braced, and cushioned to prevent movement and damage of the contents and container. Cushioning material shall be nonabrasive and water resistant.

3.3.1.4 Grease gun adapters. The adapters shall be preserved in accordance with the level A requirements of MIL-L-4387.

3.3.1.5 Hose adapters. The hose adapters shall be preserved in accordance with MIL-H-775, level A.

3.3.1.6 Aluminum sheet. The aluminum sheets shall be preserved as specified in ASTM B 660.

3.3.1.7 Anchors. The anchors shall be placed in a box conforming to PPP-B-601, domestic type, grade B or PPP-B-621, class 1. The boxes shall be provided without skids. Movable parts of the anchors shall be securely tied to the stock or shank. The boxes are not required to be strapped.

3.3.1.8 Tackle blocks. The tackle blocks shall be placed in boxes as specified in 3.3.1.7.

3.3.1.9 Rafting brackets. The rafting brackets shall be placed in boxes as specified in 3.3.1.7. The brackets shall be wrapped with a nonabrasive, nonwater absorbing material to prevent damage.

3.3.1.10 Wire rope clamps. The 1/2-inch clamps shall be placed in a fiberboard box conforming to PPP-B-636, V3c, with a method V closure in accordance with the appendix to the box specification. The 1-inch clamps shall be packaged in a box specified in 3.3.1.7.

3.3.1.11 Clevis assemblies. The clevis assemblies shall be placed in boxes as specified in 3.3.1.7.

3.3.1.12 Bridle connectors. The bridle connectors shall be preserved as specified in MIL-C-14518, level A.

3.3.1.13 Flashlights. The flashlights shall be preserved as specified in MIL-F-3747 for level A except intermediate packaging shall be for a quantity of six flashlights.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:35Z
Check the source to verify that this is the current version before use.

3.3.1.14 Chain hoists. The chain hoists shall be preserved in accordance with MIL-H-3280, level A and placed in the chests provided.

3.3.1.15 Holdfast assemblies. Each holdfast assembly shall be placed in boxes as specified in 3.3.1.7.

3.3.1.16 Hose assemblies and hose hardware. The hose assemblies and hose hardware shall be preserved in accordance with the level A requirements of MIL-H-775.

3.3.1.17 Matting kit. The matting kit shall be preserved in accordance with the contractor's recommendation. Wooden boxes shall be as specified in 3.3.1.7. Fiberboard boxes shall conform to PPP-B-636, class weather resistant with a method V closure in accordance with the box specification appendix. The weight and size of the boxes shall not exceed the limitations given in the applicable box specification.

3.3.1.18 Steel pickets. The steel pickets shall be placed in boxes conforming to PPP-B-621, class 1 with double ends. The double ends shall be made by the addition of reinforcing boards of the same thickness as the end boards, placed with the direction at right angles to that of the end boards and nailed to them with the nails clinched. The sides, top, and bottom of the box shall be nailed to the reinforcing boards in addition to the nailing required by the box specification. The pickets shall be packed in layers with the ends alternated in each layer. The boxes shall be provided without skids.

3.3.1.19 Pump. The pump shall be filled to the operating level with fluid recommended for operation and the pump activated to insure complete coating of the interior surfaces of the assembly. The fluid shall be drained and all openings plugged or covered with tape conforming to PPP-T-60, type IV. Exterior surfaces of the pump requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The pump assembly shall be packaged in a box conforming to PPP-B-636, W5c with a method V closure in accordance with the appendix to the box specification.

3.3.1.20 D-rings. The D-rings shall be placed in a fiberboard box conforming to PPP-B-636, V3c, with a method V closure in accordance with the box specification appendix.

3.3.1.21 Rope. Each reel of rope shall be wrapped with waterproof barrier material conforming to PPP-B-1055, H-1, H-5 or M-1. The shrouds shall be securely stapled to the reels and lashed circumferentially with cord or rope.

3.3.1.22 Spring scale. The spring scale shall be placed in a fiberboard box conforming to PPP-B-636, W6c with a method V closure in accordance with the box specification appendix.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:35Z
Check the source to verify that this is the current version before use.

3.3.1.23 Shackles. The shackles shall be placed in a fiberboard box conforming to PPP-B-636, W5c and closed method V of the box specification appendix.

3.3.1.24 Sling assemblies and snatch blocks. The sling assemblies and snatch blocks shall be coated with type P-1 preservative in accordance with MIL-P-116. The sling assemblies and snatch blocks shall be placed in boxes as specified in 3.3.1.7.

3.3.1.25 Reflective tape. Each roll of tape with instructions for application shall be placed in its own container. Each roll shall be held in suspension within its respective container by a centering device. The four rolls shall then be placed in a box conforming to PPP-B-566.

3.3.1.26 Rope thimbles. The thimbles shall be placed in the most compact manner in a fiberboard box conforming to PPP-B-636, W5c for 1/2-inch thimbles and V3c for 1-inch thimbles. The boxes shall be closed in accordance with the box specification appendix, method V.

3.3.1.27 Leak test tool. The leak test tool shall be placed in a fiberboard box conforming to PPP-B-636, W6c and the box closed by method V of the box specification appendix.

3.3.1.28 Cable anchor tower. The cable anchor tower shall be preserved as specified for level B of MIL-T-12442. The boxes shall be provided without skids, and strapping of the boxes is not required.

3.3.1.29 Bicycle traveler. The bicycle traveler shall be preserved as specified for level A of MIL-T-12173 and placed in a box as specified in 3.3.1.7.

3.3.1.30 Wire rope. The reels of wire rope shall be preserved in accordance with MIL-STD-163.

3.3.1.31 Tools. Tools shall be preserved in accordance with the level A requirements of PPP-P-40.

3.3.1.32 Consolidation. Components placed in fiberboard and paperboard boxes and components requiring additional protection shall be consolidated in boxed as specified in 3.3.1.7.

3.3.2 Level C. The chain hoists shall be placed in the chests provided. Preservation of the other components shall be sufficient to afford protection against deterioration and damage during shipment from the contractor to the initial destination.

3.4 Packing. Packing shall be level A or C as specified (see 6.2).

3.4.1 Level A. The components of the bridge supplementary set preserved as specified in 3.3, shall be packed in a crate conforming to MIL-C-104, type I,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:35Z
Check the source to verify that this is the current version before use.

Style a, class optional. Blocking, bracing and anchoring of the contents shall be in accordance with the appendix of the crate specification and MIL-STD-1186.

3.4.2 Level C. The bridge supplementary set preserved as specified in 3.3, shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

3.5 Marking. In addition to any special marking specified in the contract or purchase order (see 6.2), marking shall be in accordance with MIL-STD-129.

3.6 Workmanship. Workmanship shall be such as to provide maximum protection by application of the requirements specified herein to prevent deterioration and damage during handling, shipment, and storage.

3.7 Depreservation guides. Two depreservation guides shall be prepared. One copy shall be placed in a waterproof envelope marked "Depreservation Guide" and the envelope secured in a conspicuous location. The other copy shall be preserved with other instructional material and the pack marked to indicate: "A depreservation guide is inside." Unless otherwise specified, DA Form 2258 - Depreservation Guide for Vehicles and Equipment" shall be used (see 6.2 and 6.4).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of section 3. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the government to acceptance of defective material.

4.1.2 Material inspection. The contractor is responsible for insuring that supplies and materials are manufactured, examined, and tested in accordance with referenced specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:35Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. Inspections shall be classified as follows:

a. First article pack inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article pack inspection.

4.3.1 Examination. The first article pack shall be examined for the defects specified in 4.4.4. Presence of one or more defects shall be cause for rejection.

4.3.2 Test. The level A first article pack of the crated components shall be subjected to the railroad car impact test specified in MIL-STD-1186, appendix A. The test car shall strike a string of five empty cars with draft gear extended and brakes set at a speed of not less than 10 nor more than 11 miles an hour. Any shifting of contents, visible damage to the contents, loosening or breaking of anchoring, blocking, or bracing within the container shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in three stages as follows:

a. The first stage shall include inspection of materials, methods of preservation, interior markings and blocking, bracing and cushioning of packages prior to closing.
b. The second stage shall include inspection of materials and marking after package closure and the method of securing the items to the crate base.
c. The third stage shall include inspection of materials and markings after closing the crate.

4.4.2 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.4.3. Sampling. Sampling for inspection shall be in accordance with MIL-STD-105. Samples shall be determined by using tables I and IIa of MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the following defects. One or more defects shall be cause for rejection.

101. Materials, methods and containers not as specified. Each incorrect material, method or container shall constitute one defect (see 3.3).
102. Unprotected exterior metal surfaces not preserved as specified for level A (see 3.3).

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:35Z
Check the source to verify that this is the currentversion before use.

103. Components not preserved in accordance with referenced documents for level A (see 3.3.1.1).
104. Wooden boxes not furnished without skids for level A (see 3.3.1.7, 3.3.1.18, and 3.3.1.28).
105. Fiberboard boxes not closed as specified for level A (see 3.3.1.10, 3.3.1.17, 3.3.1.19, 3.3.1.20, 3.3.1.22, 3.3.1.23, 3.3.1.26, and 3.3.1.27).
106. Flashlights not intermediate packaged in the quantity specified for level A (see 3.3.1.13).
107. Chain hoists not placed in the chests provided (see 3..3.1.14).
108. Steel pickets not placed in alternate layers as specified for level A (see 3.3.1.18).
109. Interior surfaces of the pump not preserved as specified for level A (see 3.3.1.19).
110. Pump openings not plugged or covered as specified for level A (see 3.3.1.19).
111. Rope reels not wrapped as specified for level A (see 3.3.1.21).
112. Consolidation not as specified for level A (see 3.3.1.32).
113. Shipping container not as specified for level A (see 3.4.1).
114. Blocking and bracing not as specified for level A (see 3.4.1).
115. Packing not as specified by referenced documents for level C (see 3.4.2).
116. Marking illegible, incorrect, or incomplete for levels A or C (see 3.5).
117. Workmanship not as specified for levels A or C (see 3.6).
118. When other than DA Form 2258 is to be used (see 3.7).

5. PACKAGING

(This section is not applicable to this specification.)

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. This specification is intended to be used for direct reference in contracts or orders for the preservation, packing, and marking of the Troop Support Bridge Supplementary Set (SC 5420-97-CL-E51).

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article pack is required and time frame required for submission of the first article pack (see 3.1).
d. Level of preservation and packing required (see 3.3 and 3.4).

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:35Z
Check the source to verify that this is the current version before use.

e. Any special marking (see 3.5).
f. When other than DA Form 2258 is to be used (see 3.7).

6.3 First article pack. The first article pack may be accomplished utilizing either the first article model or a production model. If the preproduction model is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government, to facilitate comparison between the preproduction model and the production model. Any changes or deviations of production packs from the approved first article pack will be subject to the approval of the contracting officer. Approval of the first article pack will not relieve the contractor of his obligation to preserve, pack, and mark the pumps and accessories in accordance with this specification.

6.4 Depreservation guides. The contracting officer should arrange to furnish the necessary copies of DA Form 2258, when requested by the contractor (see 3.7).

6.5 Subject term (key word) listing.

Marking and packing
Packing
Preservation

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 5420-A367

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-S-52836A(ME)	2. DOCUMENT DATE (YYMMDD) 920206

3. DOCUMENT TITLE Supplementary Set, Bridge, Troop Support, Packaging of

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (if applicable) (2) AUTOVON	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. NAME Gerry Harlow	b. TELEPHONE (Include Area Code) (1) Commercial (703) 664-1806	(2) AUTOVON 354-1806
c. ADDRESS (Include Zip Code US Army Belvoir RDE Center ATTN: STRBE-TSE Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:35Z
Check the source to verify that this is the current version before use.