INCH-POUND

MIL-R-39016/10F
AMENDMENT 1
9 September 1991

MILITARY SPECIFICATION

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, SPDT,
LOW LEVEL TO 1.0 AMPERE
(SENSITIVE, 40 MILLIWATTS, COIL OPERATE POWER AT 25°C)

This amendment forms a part of MIL-R-39016/10F, dated 20 July 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Requirements, resistive, delete in its entirety and substitute:

"Resistive:
1.0 ampere at 28 V dc.
250 milliamperes at 115 V ac 60 and 400 Hz case not grounded.
100 milliamperes at 115 V ac 60 and 400 Hz case grounded."

Requirements, overload (high level only), delete and substitute:

"Overload (high level only): Two times rated current. Not applicable to ac load ratings."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - AS, OS, SH
Air Force - 99
DLA - ES
NSA - NS

User activities:
Navy - MC
Air Force - 11, 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0869-04)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:34Z
Check the source to verify that this is the current version before use.