INCH-POUND

MIL-R-39016/13H
AMENDMENT 1
10 July 1992

MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT,
LOW LEVEL TO 2 AMPERES (0.150-INCH TERMINAL SPACING)

This amendment forms a part of MIL-R-39016/13H, dated 13 May 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Requirements, contact data, load ratings, resistive: Delete footnote 1/ at the end of the sentence on lines 3 and 4. At bottom of page, delete footnote 1/ in its' entirety. Also, in load ratings, resistive: Delete "60 to 400 Hz" and substitute "60 and 400 Hz".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 17
DLA - ES

User activities:
Army - AR
Navy - AS, MC, OS, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0896-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:36Z
Check the source to verify that this is the current version before use.