NOTE The document identifier and heading has been changed on this page to reflect that this is a performance specification There are no other changes to this document The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised

INCH-POUND

MIL-PRF-39016/14D
AMENDMENT 1
10 July 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 4PDT
LOW LEVEL TO 2 AMPERES (0 150-INCH TERMINAL SPACING)

This amendment forms a part of MIL-R-39016/14D, dated 20 July 1988 and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 3

Requirements, contact data, load ratings, high level (relay case grounded), resistive Delete "400 Hz life test not required for qualification testing "

CONCLUDING MATERIAL

Custodians
Army ER
Navy - EC
Air Force - 85

Review activities
Army - AR
Navy - AS, OS, SH
Air Force - 99
DLA - ES

User activities
Navy - MC
Air Force 19

Preparing activity
Navy - EC

Agent
DLA ES

(Project 5945-0896-03)

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:36Z
Check the source to verify that this is the current version before use.