NOTE The document identifier and heading has been changed on this page to reflect that this is a performance specification There are no other changes to this document The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised

INCH POUND

MIL-PRF-39016/6K
AMENDMENT 1
10 July 1992

PERFORMANCE SPECIFICATION SHEET

RELAYS ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT
LOW LEVEL TO 2 AMPERES (0 200-INCH TERMINAL SPACING)

This amendment forms a part of MIL-R-39016/6K, dated 15 February 1991 and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 4

Requirements, contact data load ratings high level (relay case grounded), resistive Delete after (60 and 400 Hz) footnote 2/, (two places) Delete in it's entirety, footnote 2/ at the bottom of the page

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - AR
Navy - AS
Air Force - 85 99
DLA - ES

User activities
Navy - MC, OS, SH
Air Force - 19

Preparing activity
Navy - EC

Agent
DLA - ES

(Project 5945-0896-01)

DISTRIBUTION STATEMENT A Approved for public release distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:32Z
Check the source to verify that this is the current version before use.