NOTE The document identifier and heading has been changed on this page to reflect that this is a performance specification There are no other changes to this document The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised


MIL-PRF-39016/8F
20 JULY 1988
SUPERSEDING
MIL-R-39016/8E
10 February 1984

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, SPDT, LOW LEVEL TO 0 5 AMPERE (LATCHING)

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification and the latest issue of MIL-R-39016



Inches	mm	Inches	mm	Inches	mm
001	0 03	031	0 79	280	7 11
002	0 05	035	0 89	335	8 51
003	0 08	200	5 08	370	9 40
017	0 43	275	6 99		

NOTES


1 Dimensions are in inches
2 Metric equivalents are given for general information only
3 Unless otherwise specified tolerance is ± 010 (0 25 mm)
4 Terminal numbers shown above for reference only Numbers do not appear on relay
5 Relays shall have a plus (+) sign placed on the circuit diagram as shown
6 All leads shall be electrically insulated from the case
7 Coil symbol optional in accordance with MIL-STD-1285
6 Circuit diagram shown on part is the terminal view

FIGURE 1 Dimensions and configuration

(F) denotes changes

DISTRIBUTION STATEMENT A Approved for public release distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:33Z
Check the source to verify that this is the current version before use.



Inches	mm
.001	0.03
.002	0.05
.003	0.08
.012	0.30
.016	0.41
.017	0.43
.031	0.79
.035	0.89
.100	2.54
.150	3.81
.200	5.08
.275	6.99
.335	8.51
.370	9.40
.398	10.11

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
4. Spreader pads shall be certified to MIL-M-38527, M38627/05-003, or M38627/05-013.
5. Dimensions and tolerance shown for the bottom view of the spreader pad are for the center to center locations of the holes in the spreader pad.
6. Shape optional within the envelope dimension.
7. Coil symbol optional in accordance with MIL-STD-1285.
8. Relays shall have a (+) sign placed on circuit diagram as shown.
9. All leads shall be electrically insulated from the case.
10. Circuit diagram shown on part is the terminal view.
11. Terminal numbers shown above for reference only. Numbers do not appear on relay.

FIGURE 2. Dimensions and configuration relay with spreader pad attached.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:33Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

CONTACT DATA:

Load ratings:

High level (relay case grounded):

Resistive: 0.5 ampere at 28 V dc.
500 milliamperes at 115 V ac 400 Hz case not grounded.
250 milliamperes at 115 V ac 60 Hz case not grounded.
100 milliamperes at 115 V ac 60 and 400 Hz case grounded.
Inductive load: 0.2 ampere at 28 V dc with 0.32 henry inductance.
Lamp: 0.10 ampere at 28 V dc.

Low level: 10 to 50 µA at 10 to 50 mV dc or peak ac.

Intermediate current: Applicable.

Contact resistance or voltage drop:

(F) Initial: 0.125 ohm maximum (0.150 ohm maximum with spreader pad attached).

High level:

During life: Not more than 5 percent of open circuit voltage.
(F) After life: 0.225 ohm maximum (0.250 ohm maximum with spreader pad attached).

Low level:

During life: 33 ohms maximum.
(F) After life: 0.175 ohm maximum (0.200 ohm maximum with spreader pad attached).

Intermediate current:

During: 1 ohm maximum.
(F) After: 0.225 ohm maximum (0.250 ohm maximum with spreader pad attached).

Contact bounce: 1.5 milliseconds maximum (applicable to failure rate level "L").

Contact stabilization time: 2.0 milliseconds maximum (applicable to failure rate levels "M", "P", and "R").

Overload (high level only): Two times rated current.

(F) Neutral screen: Applicable.

COIL DATA: See table I.

Operate time: 1.5 ms maximum over temperature range with rated voltage.
Release time: Not applicable.

ELECTRICAL DATA:

Insulation resistance: 10,000 megohms minimum at 500 V dc, except the resistance between coil and case at high temperature shall be 1,000 megohms minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:33Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage:

	Sea level V rms (60 Hz)	Altitude V rms (60 Hz)
Between case, frame, or enclosure and all contacts both in the energized and deenergized positions	500	125 All terminals to case
Between case, frame, or enclosure and coil(s)	500	
Between all contacts and coil(s)	500	
Between open contacts in the energized and deenergized positions	500	
Between contact poles	500	
Between coils of dual coil relays	500	

ENVIRONMENTAL DATA:

Temperature range: -65°C to +125°C.

(F) Vibration (sinusoidal): MIL-STD-202, method 204. Contact chatter shall not exceed 10 microseconds maximum for closed contacts, and 1 microsecond maximum closure for open contacts.

(F) Vibration (random): MIL-STD-202, method 214, test condition IG. Contact chatter shall not exceed 10 microseconds maximum for closed contacts, and 1 microsecond maximum closure for open contacts. Applicable to qualification and group C testing only.

(F) Shock (specified pulse): MIL-STD-202, method 213, test condition B (75 g's). Contact chatter shall not exceed 10 microseconds maximum for closed contacts, and 1 microsecond maximum closure for open contacts.

Magnetic interference: Applicable.

Resistance to soldering heat: Applicable.

Acceleration: Applicable.

Salt atmosphere (corrosion): In accordance with method 1041, MIL-STD-750.

PHYSICAL DATA:

Terminal strength (Method 211, MIL-STD-202):

Pull test: Test condition A, 1 pound pull.
Bend test: Test condition C, 1/2 pound load.
(F) Twist test: As specified in MIL-R-39016.

Solderability: Applicable.

Dimensions and configuration: See figures 1 and 2.

Weight: 2.27 grams (0.08 ounce) maximum, 2.52 grams (0.089 ounce) maximum with spreader pad attached.

Seal. Hermetic.

(F) Minimum marking: Military part number, "J" with the date code (example J8530), circuit diagram, manufacturer's name or source code

LIFE TEST REQUIREMENTS:

(F) High level 100,000 cycles per relay
Low level 100,000 cycles plus 900,000 cycles mechanical life

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:33Z
Check the source to verify that this is the current version before use.

PART NUMBER: M39016/8- (dash number from table I and suffix letter designating failure rate level).

(F) TABLE I. Dash numbers and characteristics. 1/ 2/

Dash number 3/				Coil voltage (V dc) 4/		At 25°C		At 125°C
Lead length 1.500 min 5/	Lead length .187 ±.010	Lead length .500 min	Spreader pad (fig 2) 6/	Rated	Max	Coil resistance ohms ±10%	Specified pickup (latch/reset) value (voltage) (V dc)	Specified pickup (latch/reset) value (voltage) (V dc)
013	014	025	031	5.0	6.0	61	2.5	3.5
015	016	026	032	6.0	8.0	120	3.5	4.5
017	018	027	033	9.0	12	280	5.3	6.8
019	020	028	034	12	16	500	7.0	9.0
021	022	029	035	18	24	1,130	10.5	13.5
023	024	030	036	26.5	32	2,000	14.5	18

1/ Each relay possesses high level and low level capabilities. However, relays previously tested or used above 10 mA resistive at 6 V dc maximum or peak ac open circuit are not recommended for subsequent use in low level applications.

2/ WARNING: When latching relays are installed in equipment, the latch and reset coils should not be pulsed simultaneously. Coils should not be pulsed with less than the nominal coil voltage and the pulse width should be a minimum of three times the specified operate time of the relay. If these conditions are not followed, it is possible for the relay to be in the magnetically neutral position.

3/ The suffix letter L, M, P, or R to designate the applicable failure rate level shall be added to the applicable listed dash number. Failure rate level (percent per 10,000 cycles): L, 3.0; M, 1.0; P, 0.1; R, 0.01. Example, 013L - - - 030R.

4/ CAUTION: The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.

5/ 1.500 leads are inactive for new design.

6/ Relays supplied with spreader pads (-031 through -036) shall have the pad rigidly attached.

QUALIFICATION INSPECTION:

Qualification inspection and sample size: See table II.

(F) TABLE II. Qualification inspection and sample size. 1/

Single submission	Group submission	
18 units plus 1 open unit for level L at C = 0 2/ 33 units plus 1 open unit for level M at C = 0 2/ Qualification inspection as applicable	M39016/8-030	18 units plus 1 open unit for level L at C = 0 2/ 33 units plus 1 open unit for level M at C = 0 2/ Qualification inspection as applicable
	M39016/8-025 M39016/8-026 M39016/8-027 M39016/8-028 M39016/8-029	2 units each part number Qualification inspection, group II

1/ For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on MIL-R-39016/27, MIL-R-39016/28, and MIL-R-39016/30 may be used in addition to MIL-R-39016/8 data. Prior to performance of retention of qualification testing, the relay manufacturer shall preselect the sampling plan.

2/ The number of units required for qualification testing will be increased as required in group V, table II, MIL-R-39016, if the relay manufacturer elects to test the number of units permitting one or more failures. Prior to performance of qualification testing, the relay manufacturer shall preselect the sampling plan.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:33Z
Check the source to verify that this is the current version before use.

Initial qualification of relays supplied with spreader pads (-031 through -036), shall be tested as specified below:

Perform the following tests as specified in the qualification inspection table of MIL-R-39016, in the order shown below:

Ⓕ Before installation of pad, screening, visual and mechanical examination (internal), thermal shock, resistance to solvents, vibration (sinusoidal), vibration (random), shock (specified pulse), acceleration, terminal strength, magnetic interference (when specified), capacitance (when specified), coil life (applicable to continuous duty relays only), resistance to soldering heat, salt spray (corrosion), overload (applicable to high level relays only), life, terminal strength, and intermediate current.

After installation of pad, perform the following tests as specified in the qualification inspection table of MIL-R-39016, in the order shown below:

Ⓕ Insulation resistance, dielectric withstanding voltage, static contact resistance, specified pickup (latch/reset) value (voltage), coil resistance, operate and release time, contact dynamic characteristics, coil transient suppression (when specified), solderability, seal, visual and mechanical inspection (external).

Qualification inspection (reduced testing for previously qualified relays) for relays supplied with spreader pads (-031 through -036): Two units of the 26.5 volt rated coil voltage (-036) shall be tested as specified below:

Before installation of pad, perform the following tests as specified in the qualification inspection table of MIL-R-39016 in the order shown below:

For failure rate level L only: Screening.

Ⓕ For failure rate levels M, P, and R: Vibration (sinusoidal) test duration shall be 10 minutes, vibration (random), particle impact noise detection (P.I.N.D., when specifed), screening.

After installation of pad perform the following tests as specified in the qualification inspection table of MIL-R-39016 in the order shown below:

Ⓕ Insulation resistance, dielectric withstanding voltage, static contact resistance; specified pickup (latch/reset) value (voltage), coil resistance, operate and release time, contact dynamic characteristics, coil transient suppression (when specified), solderability, seal, visual and mechanical inspection (external).

Group A testing for relays supplied with spreader pads (-031 through -036), shall be tested as specified below:

Ⓕ Before installation of pad, perform subgroup 2 of group A tests.

Ⓕ After installation of pad, perform subgroups 3 and 4 of group A tests.

Qualification inspection (reduced testing): See table III.

If the relays produced for MIL-R-39016/8 are similar in construction and design except for the diodes and headers, as applicable, to the relays produced for MIL-R-39016/27, MIL-R-39016/28, or MIL-R-39016/30, then reduced testing for qualification of MIL-R-39016/8 relays may be performed concurrent with or subsequent to successful qualification of MIL-R-39016/27, MIL-R-39016/28, or MIL-R-39016/30.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:33Z
Check the source to verify that this is the current version before use.

Ⓕ TABLE III. Qualification inspection (reduced testing).

Examination or test
2 units each coil voltage Group II of qualification inspection table 1 unsealed sample unit for internal examination

SUPERSESSION DATA:

Supersession data: See table IV.

TABLE IV. Supersession data. 1/

Superseded part no. M5757/39-	New part no. M39016/8- 2/	Superseded part no. M39016/8-	New part no. M39016/8- 2/
001	015	001	013
002	017	002	014
003	019	003	015
004	021	004	016
005	023	005	017
006	016	006	018
007	018	007	019
008	020	008	020
009	022	009	021
010	024	010	022
011	013	011	023
012	014	012	024

1/ Dash numbers -013, -015, -017, -019, -021, and -023 are inactive for new design and are for support of existing equipment design only.

Ⓕ 2/ Complete part number shall contain suffix letter L, M, P, or R to designate failure rate level (see 3/ of table I). A part with any failure rate supersedes the applicable MIL-R-5757 part.

Cross-reference for Government logistical support: See table V.

TABLE V. Cross-reference for Government logistical support.

Superseded part no. M5757/39-	New part no. M39016/8-	Support with part no. M39016/8-	Superseded part no. M39016/8-	New part no. M39016/8-	Support with part no. M39016/8-	New part no. M39016/8-	Support with part no. M39016/8-
001	015	015	001	013	013	025	025
002	017	017	002	014	025	026	026
003	019	019	003	015	015	027	027
004	021	021	004	016	026	028	028
005	023	023	005	017	017	029	029
006	016	026	006	018	027	030	030
007	018	027	007	019	019	031	031
008	020	028	008	020	028	032	032
009	022	029	009	021	021	033	033
010	024	030	010	022	029	034	034
011	013	013	011	023	023	035	035
012	014	025	012	024	030	036	036

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:33Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
(F) Air Force - 85

Review activities:
Army - AR
Navy - AS, OS, SH
(F) Air Force - 99
DLA - ES
NSA - NS

User activities:
Navy - MC
(F) Air Force - 11, 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0757-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:33Z
Check the source to verify that this is the current version before use.