NOTE The document identifier and heading has been changed on this page to reflect that this is a performance specification There are no other changes to this document The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised

INCH-POUND

MIL PRF 39016/9H
AMENDMENT 4
23 June 1993
SUPERSEDING
AMENDMENT 3
21 September 1993

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT, LOW LEVEL TO 1 0 AMPERE

This amendment forms a part of MIL-R-39016/9H, dated 15 November 1989, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

FIGURE 1 Delete " 335/ 275 DIA" and substitute " 370 MAX"

PAGE 5

Load ratings, resistive, delete in its entirety and substitute

"Resistive

1 0 ampere at 28 V dc
250 milliamperes at 115 V ac 60 and 400 Hz case not grounded
100 milliamperes at 115 V ac 60 and 400 Hz case grounded "

Overload (high level only), delete and substitute

"Overload (high level only) Two times rated current Not applicable to ac load ratings "

PAGE 8

* TABLE II, footnote 1/, delete and substitute

"1/ Figure 1 only - For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on MIL-R-39016/11 /15, /16, /20 and /21 may be used in addition to MIL-R-39016/9 data Qualification to figure 1 automatically qualifies round relays to figure 2

"Figure 2 only - For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on MIL-R-39016/11 /15, /16, /20, and /21 may be used in addition to MIL-R-39016/9 data Prior to performance of retention of qualification testing the relay manufacturer shall preselect the sampling plan "

PAGE 10

Group A testing for relays supplied with spreader pads delete both paragraphs and substitute

"Perform seal test immediately, preceding the subgroup 3 electrical tests Relay leads shall be formed and the mounting pad removed before the seal test After the seal test the mounting pad shall be rigidly attached to the relay and the remaining group A tests performed "

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:34Z
Check the source to verify that this is the current version before use.

* Qualification inspection (reduced testing) and sample size. Delete both paragraphs and substitute.

"Figure 1 only - If the relays produced for MIL-R-39016/9 are similar in construction and design except for the diodes and coil assembly, as applicable, to the relays produced for MIL-R-39016/11, /15, /16, /20, or /21, then reduced testing for qualification of MIL-R-39016/9 relays may be performed concurrent with or subsequent to successful qualification of MIL-R-39016/11, /15, /16, /20, or /21. For reduced testing, see table III.

"Figure 2 only - If the relays produced for MIL-R-39016/9 are similar in construction and design except for the diodes and coil assembly, as applicable, to the relays produced for MIL-R-39016/11, /15, /16, /20, or /21, then reduced testing for qualification of MIL-R-39016/9 relays may be performed concurrent with or subsequent to successful qualification of MIL-R-39016/11, /15, /16, /20, or /21 "

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Navy - AS
Air Force - 99
DLA - ES
NSA - NS

User activities:
Army - AR
Navy - MC, OS, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5945-0916-03)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T17:34Z
Check the source to verify that this is the current version before use.