NOT MEASUREMENT SENSITIVE

MIL-L-11484/210
14 January 1994
SUPERSEDING
MIL-L-11484/172 (IN PART)
9 July 1990

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, MERITORIOUS CIVILIAN SERVICE AWARD, ON-SITE INSPECTION AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

FINISH: Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Thickest Point): 0.080 inch ± 0.005 inch (0.203 cm ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:23Z
Check the source to verify that this is the current version before use.

2. The attaching device shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the label button.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0744)

User activities:
Other - OSIA

Source: https://assist.dla.mil -- Downloaded: 202640-17T17:23Z
Check the source to verify that this is the current version before use.