NOT MEASUREMENT SENSITIVE

MIL-L-11484/211
14 January 1994
SUPERSEDING
MIL-L-11484/179 (IN PART)
28 May 1991

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, OUTSTANDING CIVILIAN SERVICE AWARD (NON-CIVIL SERVICE), ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Thickest Point): 0.090 inch ± 0.010 inch (0.229 cm ± 0.025 cm)

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

Custodians:
Army - IH
Review activities:
DLA - CT

Preparing activity:
Army - IH
(Project No. 8455-0744)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:24Z
Check the source to verify that this is the current version before use.