NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/212D
23 June 2020
SUPERSEDING
MIL-DTL-11484/212C
31 August 2015

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, SUPERIOR CIVILIAN SERVICE, U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Silver Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 13.

DIMENSIONS:
DIAMETER: 5/8 inch (REF)
THICKNESS (At edge): 0.090 inch ± 0.010 inch

ATACHING DEVICE:
1. Attaching device shall be prong with pick and wing type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:24Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2020-377)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:24Z
Check the source to verify that this is the current version before use.