NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/215C
23 November 2020
SUPERSEDING
MIL-DTL-11484/215B
19 October 2015

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, SUPERIOR CIVILIAN SERVICE AWARD, DEFENSE COMMISSARY AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Pewter (Glass Beaded, Tin Plated)

DIMENSIONS:
HEIGHT (Overall): 25/32 inch (REF)
WIDTH (Overall): 11/16 inch (REF)
THICKNESS (At thickest point): 0.080 inch ± 0.010 inch

ATACHING DEVICE:
1. Attaching device shall be prong with pick and flat ball type clutch.

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Lapel button shall be lacquered.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:25Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-076)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:25Z
Check the source to verify that this is the current version before use.