MILITARY SPECIFICATION SHEET

SEMITRAILER, DUMP, COMMERCIAL

SIZE 10, REFUSE SPECIAL

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the refuse special dump semitrailer described herein shall consist of this document and the latest issue of Specification MIL-S-46777.

REQUIREMENTS:

1. The size 10 refuse special rear dump semitrailer shall be equipped with tandem (2-each) axles and as specified herein and in table I.

2. Size 10 (refuse special).

(a) Overal height, with the semitrailer unloaded, shall not exceed 144 inches excluding the bows and the canvas cover.
(b) Level bed height of the body floor shall not exceed 58 inches with the semitrailer unloaded.
(c) Inside body length and height shall be approximately 294 inches and 86 inches, respectively.
(d) Dump angle of the body shall be not less than 46 degrees.
(e) The body shall be of flat-front design with 10-inch radius front corners.
(f) The body shall be of high-strength, low-alloy (HSLA) steel with minimum nominal thickness of 0.1644 inch for floor plates and minimum nominal thickness of 0.1046 inch for side plates.
(g) Inside body width between the top of the sides shall be approximately 2 inches greater than at the bottom of the sides.
(h) Inside body width at the rear shall be approximately 6 inches greater than at the front.
(i) Catwalks of raised pattern or open antiskid grating shall be furnished along each side of the body and shall be hinged to fold against the sides so as to be within the legal highway width limit. The catwalks shall be in accordance with the SAE J185 and Department of Labor OSHA requirements. The catwalk location shall be approximately 3 feet below the top of the sides. Ladders shall be furnished on each side, at front and at rear. The rear ladders shall extend below the floor of the body to enable personnel to board the semitrailer from ground level. The lowest rung of ladders shall be not more than 30 inches from the ground.

FSC 2330

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:54Z
Check the source to verify that this is the current version before use.

(j) A chemically treated canvas or fabric reinforced vinyl tarpaulin to enclose the entire top of the body shall be furnished. All shock cords, fittings, and tiedowns shall be included.
(k) Removable top bows for support of the canvas or vinyl cover shall be provided. The bows shall be installed in sockets on the sides of the semitrailer.
(l) the tailgates shall be of the side-hinged, double-barndoor type with outside latches. The tailgates shall be watertight when closed and latched.

TABLE I. Weights and dimensions.

		Size 10
Mfgr's Rated GVWR		Min. 28,000 16.
Payload.		Min. 20,000 16
Axle Weight Limit.		
(a) Single Axle Rear Suspension		---------
(b) Multiple Axle Rear Suspension (each axle)		Max. 16,000 lb.
Overall Length.	(OAL) L108	Max. 359 in.
Overall Width.	(OAW) W103	Max. 98 in.
Overall Height.	(OAH) H153	Max. 144 in.
Ground Clearance, min, in.	(GC) H156	Min. 9.5 in.
Front Support Clearance, Radius.	(LWC) L498T	Min. 72 in.
Body:		
Struck capacity.	(SAE J741)	Min. 47 cu. yd
Heaped Capacity.	(SAE J741)	---------
Length of Body.		Min. 25 ft.
TBEA Hoist Classification.		Min. 90

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
Army - AT

Project 2330-0745-1

User activities:
Army - CE
Navy - MC, YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:54Z
Check the source to verify that this is the current version before use.