MIL-T-46744D(AT)
26 February 1986
Superseding
MIL-T-45744C(AT)
2 January 1980

MILITARY SPECIFICATION

TRAILERS, MAINTENANCE: 1000 and 2000 POUNDS PAYLOAD 2 WHEEL, COMMERCIAL

This specification is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers four types of commercial, 2 wheel, maintenance trailers. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

1.2 Classification. Trailers shall be of the type specified (see 6.2):

Type I	- Cable splicer, 1000-pound payload.
Type II	- Telephone-utility, 1000-pound payload.
Type III	- General purpose, 1000-pound payload.
Type IV	- Telephone-utility, 2000-pound payload.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC-2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* SPECIFICATIONS

FEDERAL

ZZ-T-381 - Tires, Pneumatic, Vehicular (Highway).

STANDARDS

* FEDERAL

FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles

MILITARY

* MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.

MS51336 - Lunette-Coupler, Drawbar, Ring.

MS51339 - Coupler, Drawbar, Ring - Offset.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.

Federal Motor Vehicle Safety Standards.

(Application for copies of DoT publications should be addressed to the Department of Transportation, Federal Highway Administration, Washington, D.C. 20591.)

* (Copies of specifications, standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DoDISS shall be the issue of the nongovernment document which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)

ANSI A14.1 - Safety Code for Portable Wood Ladders.

(Application for copies of ANSI publications should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

SAE, INC.
SAE Standards and Recommended Practices

*	J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (20 - 1,000 MHz).
	J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
	J588	- Turn Signal Lamps.
	J1067	- Seven-Conductor Jacketed Cable for Truck-Trailer Connections.
*	J1292	- Automobile, Truck, Truck-Tractor, Trailer and Motor Coach Wiring.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Yearbook.

(Application for copies should be addressed to The Tire and Rim Association, Inc., 3200 W. Market Street, Akron, OH 44313.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.2, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items which meet or exceed the requirements of this specification. All items shall be as represented in the trailer manufacturer's technical data, and special or mounted equipment shall be as represented in the equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be on file in the engineering offices of the procuring activity prior to delivery of the items. The vehicle shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture. The model furnished shall be not older than the manufacturer's current model on the date of invitation for bids.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. Treatment, painting, identification marking and data plates shall be in accordance with MIL-STD-1223. As specified by the procuring activity for the appropriate service (see 6.2), the vehicle exterior color and identification markings shall be in accordance with MIL-STD-1223.

* 3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

3.2 Weight and load distribution.

3.2.1 Payload. The rated payload capacity shall be not less than 1000 pounds for type I, II and III trailers and not less than 2000 pounds for type IV trailers. Requirements shall be met with the payload uniformly distributed over the load space.

3.2.2 Weight distribution. With the longitudinal axis of the trailer horizontal, the center of gravity of the trailer, without payload and with a uniformly distributed full rated payload, shall be forward of the axle. The vertical load on the lunette, with the trailer unloaded, shall be not greater than 200 pounds.

3.2.3 Gross weight. The gross weight shall consist of the weight of chassis and body with all attachments and the full rated payload uniformly distributed in the vehicle body load area. The gross weight of types I, II and III trailer shall be not more than 3000 pounds. The gross weight of type IV trailers shall be not less than 3500 pounds.

3.2.4 Ratings. Vehicle ratings shall be manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings must be submitted to the engineering office of the procuring activity. Minimum payload shall conform to 1.2 for the specified type, class and size of the vehicle.

3.3 Performance. Vehicle performance as specified in 3.3.1 through 3.3.5 shall be met by the trailer when fully equipped with all attachments and accessories, with rated payload uniformly distributed over the trailer load area and towed by a towing vehicle over improved and unimproved hard, uneven terrain. Vehicle shall show no evidence of failure or malfunction of trailer, components, attachments, and accessories.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* 3.3.1 Towing speed and trailing ability. The trailer shall follow the towing vehicle over dry, level, smooth, prepared, hard-surfaced roads at sustained speeds to 55 miles per hour (mph), and over dry, unimproved and gravel roads at speeds to 25 mph. The trailer shall follow the towing vehicle without exceeding the tracking deviations specified in Federal Motor Carrier Safety Regulation 393.70(a).

3.3.2 Turning ability. When coupled to a towing vehicle operating in its minimum turning circle, the trailer shall follow without cramping. The trailer shall be capable of moving through an angle of not less than 60 degrees in relation to a 96-inch wide towing vehicle without interference between vehicles. The angle shall be measured between the longitudinal axis of the trailer and the longitudinal axis of the towing vehicle at the lunette.

3.3.3 Suspension system. The axle, springs, accessories and components of the suspension system shall withstand the imposed loads without evidence of permanent set, part failure or malfunctioning under the operating conditions specified.

* 3.3.4 Service brakes. The service brakes, in conjunction with a towing vehicle (truck-trailer combination), under all conditions of loading, shall control, decelerate and stop the vehicle combination in accordance with Federal Motor Carrier Safety Regulation 393.52.

3.3.5 Parking brakes. The parking brakes shall hold the trailer with specified payload on a dry, hard-surfaced grade of not less than 30 percent when uncoupled from the towing vehicle, resting on the trailer's running gear and landing leg, and headed up and down the incline. The parking brake lever shall have sufficient moment arm to require not more than 30 pounds of effort for application and release.

3.4 Trailer components.

3.4.1 Frame. The trailer shall be equipped with a frame of all-steel welded construction with each main frame member in a one piece without splices or joints. A sufficient number of full-width crossmembers shall be furnished to assure stability and rigidity. Crossmembers shall be of full channel, pressed steel construction reinforced by gusset plates or brackets at point of attachment to longitudinal sills. Longitudinal sills shall be reinforced. The sprung weight of the loaded vehicle shall not impose a fiber stress greater than 50 percent of the yield strength of the materials used under mobile operating conditions specified herein (see 3.3). All parts of the chassis frame where welding is required shall be electrically welded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

3.4.1.1 Drawbar and coupling device. The trailer shall be equipped with a drawbar of the "A" frame type formed by the continuation of the trailer main frame side rails. The coupling device shall be a standard lunette ring conforming to MS-51336. The coupling device shall also be of the offset type conforming to MS-51339 to provide a 4-inch vertical range of adjustment. The lunette shall be positioned so that the longitudinal axis of the body is parallel to the lunette. With the trailer fully loaded and resting on the landing wheel, and with the lunette in its lowest position, the height to the centerline of the lunette shall be 25 inches, plus or minus 1 inch. The coupler shall conform to Federal Motor Carrier Safety Regulation 393.70(c).

3.4.1.2 Landing leg. The trailer shall have a folding landing leg with a permanently attached caster type landing wheel. The landing leg shall also be capable of telescopic movement with a permanently installed cranking handle. The landing leg and related parts shall withstand, without permanent deformation, the combined static and dynamic forces due to the impact during coupling and uncoupling operations. The landing leg shall operate freely and shall be protected from malfunctioning caused by foreign matter. The caster wheel shall be fitted with an anti-friction bearing. Means shall be provided to lubricate the landing leg assembly and wheel. When placed into travel position, the landing leg shall remain positively locked to provide ground clearance in the course of normal towing operations.

3.4.1.3 Safety chains. The trailer shall be equipped with two safety chains with eyes. The chains shall conform to Federal Motor Carrier Safety Regulation 393.70(d).

3.4.2 Suspension. The trailer shall be equipped with an individual wheel, semielliptical spring suspension system having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded as specified in 3.2. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted.

3.4.3 Axle. The trailer shall be provided with a single axle. The axle rating shall be at least equal to the load imposed on the axle, measured at the ground, with vehicle loaded as specified in 3.2.

3.4.4 Wheels, rims, tires and tubes. The trailer shall be equipped with single wheels and tires. Rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished. Tire and rim sizes shall be the same for all wheels on the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* 3.4.4.1 Tires. Steel belted radial, or when specified (see 6.2) bias ply tires, shall be furnished. Tires shall be tube or tubeless truck type with highway tread. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded as specified in 3.2. Tires shall conform to Tire and Rim Association recommendations, or to ZZ-T-381 with a size designation system the same as the Tire and Rim Association.

3.4.4.2 Inner tubes. When tube type tires are furnished, inner tubes shall be of heavy duty type, and shall be of proper size for the tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

* 3.4.4.3 Carrier for spare tire assembly. Unless otherwise specified (see 6.2), a carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. The carrier shall permit ready removal or installation of the spare assembly, using only the tools specified in 3.4.8. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material.

3.4.4.4 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished and stowed on the carrier.

* 3.4.4.5 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design, and load range (ply rating) as furnished on the axle of the vehicle.

3.4.5 Brakes.

* 3.4.5.1 Electric brakes. Unless otherwise specified (see 6.2), brakes shall not be furnished on type I, II and III vehicles. Unless inertia brakes are specified (see 3.4.5.2), type IV trailers shall be furnished with a 12-volt electric brake system. The brake system shall be wired in accordance with 3.4.6.4. The system shall include a manual controller kit for mounting on the dash of the towing vehicle, a controller kit for synchronizing the trailer electric brakes with the brakes of the towing vehicle, and an emergency breakaway kit. Kits shall be complete with all necessary parts (except storage battery for breakaway kit) and installation instructions. Unless otherwise specified, the synchronizing controller shall be for use with a towing vehicle equipped with hydraulic brakes. When specified (see 6.2), the synchronizing controller shall be for use with a towing vehicle equipped with air brakes. The kits shall be boxed, marked as to contents, and securely attached to the trailer for shipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

3.4.5.2 Inertia brakes. When specified (see 6.2), type IV trailer shall be furnished with an inertia (surge) applied hydraulic brake system in lieu of electric brakes. The inertia brake actuator, mounted on the tow bar, shall include a master cylinder, an accumulator chamber, and a hold-off spring to prevent brake applications caused by road shock or trailer pitching. The system shall provide for modulated brake applications, shall be protected against the entrance of foreign matter, shall include breakaway features conforming to Federal Motor Carrier Safety Regulation 393.43(d), and shall allow the trailer to be backed up without continued application of the trailer brakes.

3.4.5.3 Parking brakes. Manually applied parking brakes shall be furnished on all trailer types. The parking brakes shall conform to Federal Motor Carrier Safety Regulation 393.41. Provisions shall be made for slack adjustment. When brake cables are used, they shall be of corrosion-resistant steel. Lubrication fittings shall be provided.

3.4.5.4 Wheel chocks. When specified (see 6.2), four wheel chocks shall be provided. Wheel chocks shall be secured to the trailer with corrosion-resistant chains. Provisions for stowage in their respective areas shall be provided.

* 3.4.6 Lighting. The electrical lighting system shall be 12 volts. All vehicle lights, reflectors and wiring (including electric brakes) shall conform to Federal Motor Carrier Safety Regulations 393.15, 393.19, 393.22, 393.23, 393.25, 393.26, 393.27 through 393.30, 393.32, and 393.33. Lights and reflectors shall not be mounted on the vertical surface of rub rails (unless recessed and fully protected) or on vehicle bumpers. All 12-volt electrical wiring shall conform to SAE J1292.

3.4.6.1 Electrical receptacle. A trailer electrical receptacle conforming to SAE J560 shall be installed on the forward end of the drawbar. The receptacle shall have a spring loaded cover assembly. Conductors shall be connected and color coded as specified in SAE J560.

3.4.6.2 Electrical jumper cables. Unless otherwise specified (see 6.2), a coiled electrical jumper cable conforming to SAE J1067, with a cable plug at each end conforming to SAE J560, shall be provided. Both plugs shall be equipped with a grip for withdrawing from connector sockets. Stowage provisions, having an anti-theft feature and means for hanging the cable with the plugs pointing down, shall be provided. The cable shall be not less than 3 feet longer than the distance from the trailer electrical receptacle to the lunette.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

3.4.6.3 Turn signals. Turn signal lamps conforming to SAE J588 shall be furnished.

3.4.6.4 Brake wiring. Electric brakes shall be wired to the auxiliary circuit of the SAE J560 seven-conductor electrical connector. All wiring shall be properly mounted and secured with clamps. Wiring shall be heavy-wall thermoplastic insulated cable and shall be enclosed in conduit.

* 3.4.6.5 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551.

3.4.7 Bumper. A rear bumper shall be furnished. The bumper shall be as specified herein for the various body types. Rear end protection shall conform to Federal Motor Carrier Safety Regulation 393.86.

3.4.8 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly, and shall include at least a jack, jack handle and wheel nut wrench. The jack shall be of such closed height as to permit its location under the axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.4.9 Lubrication. All moving parts of the trailer normally requiring lubrication shall be provided with means for such lubrication.

3.4.9.1 Lubrication fittings. The lubrication fittings shall be standard commercial type with a surface-check ball.

3.4.10 Body mounting. The body shall be secured with U-bolts, twin studs, brackets or J-bolts and shall include a wood breaker strip.

3.4.10.1 U-bolts or twin studs. When U-bolts or twin studs are used, there shall be not less than three U-bolts or twin studs per side, each having 9/16-inch diameter with 5/8-inch minimum thread diameter. Tie-plates shall be at least 1/2 inch thick. The vehicle chassis frame shall be braced, using wood blocks at each mounting point unless the mounting point is located at a full depth frame crossmember. Blocks shall incorporate a keeper strap or groove for the mounting bolt, and shall be of a width and thickness to assure retention. Two tie-back straps shall be provided, one bolted to each side of the rear portion of the body sub-frame, to maintain body alinement on vehicle chassis. Forward body mounting bolts shall be located to the rear of the tapered portion of breaker strips (see 3.4.10.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

3.4.10.2 Brackets. When brackets are used, they shall be bolted to the web of the chassis frame rails. The body mounting brackets shall provide means for drawing down the body on the chassis rails and provisions shall be made to prevent lateral shifting of the breaker strips. Attachments shall not interfere with nor obstruct chassis components.

3.4.10.3 J-bolts. When J-bolts are used, there shall be not less than seven J-bolts per side, each not less than 3/8 inch in diameter. J-bolts shall encircle the lower chassis frame flange. Two tie-back straps as specified in 3.4.10.1 shall be provided. The forward J-bolts shall be located to the rear of the tapered portion of the breaker strips (see 3.4.10.4). Provisions shall be made to prevent lateral shifting of the breaker strips.

3.4.10.4 Breaker strips. A hardwood or dense southern yellow pine breaker strip, not less than 1-1/16 inches finished thickness, shall be installed between longitudinal sills and vehicle chassis frame.

3.5 Trailer types.

3.5.1 Type I (cable splicer). The body shall be of steel construction. The vehicle and the body shall conform to the dimensions in table I.

TABLE I. Dimensions, type I.

Overall:	
Vehicle length (maximum)	100 inches
Vehicle width (maximum)	70 inches
Ground clearance (minimum)	9 inches
Body inside:	
Length (minimum)	64 inches
Width (minimum)	44 inches
Height (minimum)	43 inches

3.5.1.1 Compartment arrangement. The trailer shall be equipped with the manufacturer's standard cable splicer body. The body shall be complete with fenders and shall provide for weathertight storage of all standard cable splicer equipment. The compartment arrangement of the body shall include:

(a) A shallow front compartment extending the full width and height of the trailer body, divided vertically to provide for hanging clothes and for shelf storage of small items.

(b) A horizontal compartment on both sides of the body, above the wheelwells, extending from the rear of the front compartment (see (a) above) to the rear of the body.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

(c) A compartment across the rear, between the wheelwells, and below the horizontal compartments, (see (b) above).
(d) A curbside compartment, near the front, and below the horizontal compartments (see (b) above).
(e) Shelf arrangement and partitioning of compartments shall be the manufacturer's standard for cable splicer trailers and shall include not less than two decks of small bins with adjustable partitions in the right side horizontal compartment (see (b) above).

3.5.1.2 Compartment doors. The compartment doors shall provide access to all portions of each compartment. Door closures shall be weatherproof when tested in accordance with 4.3.2. The doors shall have continuous rod or hem type heavy duty hinges, with stainless steel hinge pins and stainless steel, nylon, or nylon insert sockets. Latches shall have recessed handles. All doors shall be provided with cylinder type locks, operable with one key but not with the same key on more than one vehicle. Moving parts of latches and locks shall be constructed of, or plated with, corrosion-resistant material. Horizontal doors shall be provided with stays and shall be hinged and reinforced so as to permit use as a shelf and shall be capable of supporting a live load of not less than 25 pounds per square foot.

3.5.1.3 Rear bumper. A rear bumper, extending not less than 3 inches beyond the rear of the body, shall be furnished.

3.5.2 Type II (telephone-utility). The body shall be of steel construction, having a center load compartment, with cabinets on each side. When specified (see 6.2), the vehicle shall be furnished with a pipe rack on the top of the right cabinet, a standard pipe vise bracket and pipe rest on the right side of the cabinet, and shall have rope loops in lieu of adjustable shelves inside the left vertical cabinet. The vehicle and the body shall conform to the dimensions specified in table II.

TABLE II. Type II dimensions and loading requirements.

Overall:	
Vehicle length (maximum)	135 inches
Vehicle width (maximum)	80 inches
Ground clearance(minimum)	9 inches
Load space:	
Length (minimum)	75 inches
Width (minimum)	46 inches
Height (minimum)	26 inches
Cabinet space:	
Length (minimum)	75 inches
Height (minimum)	37 inches

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

Width (minimum)	14 inches
Volume (each side) (minimum)	30,000 cubic inches
Loading without permanent deformation:	
Load space floor - live load on any square foot of area (minimum)	500 pounds
Cabinet and shelves - live load on any square foot of area (minimum)	100 pounds

3.5.2.1 Bulkhead. A front bulkhead shall be provided. The bulkhead shall be constructed to the full height of the cabinets and shall be of not less than 18 gage (0.0478 inch) high-tensile steel or 16 gage (0.0598 inch) carbon steel reinforced for rigidity.

3.5.2.2 Tailgate. A tailgate shall be provided. The tailgate shall be constructed of not less than 18 gage (0.0478 inch) high-tensile steel or 16 gage (0.0598 inch) carbon steel reinforced for rigidity. The tailgate shall be hinged and equipped with supports for retention in horizontal position, flush with or slightly lower than the floor level.

3.5.2.3 Rear bumper. A rear bumper shall be provided. A safety-tread steel plate step, integrated with the rear bumper, extending across the width of the body and with a step surface not less than 10 inches deep, shall be provided. A toe plate extending from the top of the bumper to the bottom of the body shall be provided.

3.5.2.4 Cabinet material and construction. Cabinet headers shall be not less than 18 gage (0.0478 inch) high-tensile steel or 16 gage (0.0598 inch) carbon steel. Cabinet backs, partitions, and shelves shall be of not less than 20 gage (0.0359 inch) high-tensile steel or 18 gage (0.0478 inch) carbon steel. Cabinet doors shall be of not less than 20 gage (0.0359 inch) high-tensile or 18 gage (0.0478 inch) carbon steel, single thickness reinforced, or 22 gage (0.0299 inch) carbon steel, double panel reinforced.

3.5.2.5 Cabinet arrangement. Cabinet arrangement shall include full-height vertical cabinets with not less than two adjustable shelves on each side of the body at the front; a horizontal cabinet with not less than two decks of small bins with adjustable partitions on the right side of the body; and a horizontal cabinet with not less than one tray type shelf on the left side of the body.

3.5.2.6 Cabinet doors. Cabinet doors shall provide access to all portions of each cabinet. Door closures shall be weatherproof when tested in accordance with 4.3.2. Doors shall have continuous rod or hem type heavy duty hinges with stainless steel hinge pins and stainless steel, nylon, or nylon insert sockets. Latches shall have recessed

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

handles. All doors shall be provided with cylinder type locks, operable with one key but not with the same key on more than one vehicle. Moving parts of latches and locks shall be constructed of, or plated with, corrosion-resistant material. Horizontal doors shall be provided with stays and shall be hinged and reinforced so as to permit use as a shelf and shall be capable of supporting a live load of not less than 25 pounds per square foot.

3.5.2.7 Overhead racks and ladder. A 24-foot, two-section wooden extension ladder and removable overhead racks, with ladder brackets, shall be provided. The ladder shall conform to ANSI A14.1. The rear bow of the overhead rack shall be provided with pivoted ladder clamps for carrying, erecting, and using the extension ladder. Anchor points for the foot of the ladder shall be set into the step bumper and shall be not less than 3 inches deep. When erected using the rear bow and anchor points, the angle of the ladder with horizontal shall be between 75 and 85 degrees. A rope and pulleys for use in extending and retracting the ladder shall be provided.

3.5.3 Type III (general purpose). The body shall be of steel construction. The vehicle and the body shall conform to the dimensions in table III.

TABLE III. Dimensions, type III.

Overall:	
Vehicle length	90 ± 2 inches
Vehicle width (maximum)	70 inches
Ground clearance (minimum)	9 inches
Body inside:	
Length (minimum)	60 inches
Width (minimum)	30 inches
Height (minimum)	25 inches

3.5.3.1 Compartment arrangement. The trailer shall be equipped with the manufacturer's standard general purpose body. The body shall be weathertight when tested in accordance with 4.3.2. The body shall have a roof top which pivots on a continuous hinge the full length of the body, operable from the curbside, and which automatically holds up in fully opened position. A fold-down type curbside door, with continuous horizontal hinge, not less than 12 inches wide and the length of the body, shall serve as a work bench when in horizontal fold-down position. The door shall be on the upper half of the body and shall be supported by chains on both ends with sufficient capacity to hold up an equitable load imposed on the door. The door shall be lined with exterior plywood. Two bin type shelves, each the full length of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

body, 8 and 12 inches wide respectively, shall be furnished. The shelves shall be installed on the left side with the 8-inch shelf at the top and the 12-inch shelf below. The side door shall be flush with the body when closed. The top and side doors shall be provided with suitable hasp type locking devices. Locks are not required.

3.5.3.2 Rear bumper. A rear bumper, extending not less than 3 inches beyond the rear of the body, shall be furnished.

3.5.4 Type IV (telephone-utility). The body shall be of steel construction, having a center load compartment, with cabinets on each side. The body shall be equipped with a telescoping roof and tailgate enclosure, a pipe rack on top of the right cabinet, a standard pipe vise bracket and a pipe rest on the right side cabinet. The vehicle and body shall conform to the dimensions in table IV. The vehicle shall comply with the requirements specified for type II vehicles in 3.5.2.1 through 3.5.2.7 for bulkhead, tailgate, rear bumper, cabinet material and construction, cabinet arrangement, cabinet doors, overhead racks and ladder. Rope hooks in lieu of adjustable shelves shall be furnished inside the left vertical cabinet. The telescoping roof and tailgate enclosure (in addition to the cabinets) shall be weathertight when tested in accordance with 4.3.2.

TABLE IV. Type IV dimensions and loading requirements.

Overall:	
Vehicle length (maximum)	170 inches
Vehicle width (maximum)	80 inches
Ground clearance (minimum)	9 inches
Load space:	
Length (minimum)	102 inches
Width (minimum)	46 inches
Height (minimum)	26 inches
Cabinet space:	
Length (minimum)	102 inches
Height (minimum)	37 inches
Width (minimum)	14 inches
Volume (each side) (minimum)	40,000 cubic inches
Loading without permanent deformation:	
Load space floor - live load on any square foot of area (minimum)	500 pounds
Cabinet and shelves - live load on any square foot of area (minimum)	100 pounds

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust each vehicle for operational use including at least the following: alinement of wheels; inflation of all tires; adjustment of brakes; and complete lubrication of chassis and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observations of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.3.1 Performance test. The trailer, with and without rated payload, shall be tested for conformance to paragraphs 3.3.1 through 3.3.5. Subsequently, it shall be road tested for a distance of not less than 200 miles to determine conformance to the requirements of this specification. The road test shall be in accordance with Table V.

TABLE V. Road test.

Configuration	Road condition	Speed	Distance
w/o Rated Payload	Improved Roads	Up to 55 MPH	70 Miles
	Unimproved Roads	Up to 25 MPH	30 Miles
w/Rated Payload	Improved Roads	Up to 55 MPH	70 Miles
	Unimproved Roads	Up to 25 MPH	30 Miles

4.3.2 Water spray test. The trailer shall be subjected to a water spray test for approximately 15 minutes, after the road test. The spray shall be delivered by nozzles operating at 25 pounds per square inch (psi) nominal water pressure, sufficient in number and so placed (approximately 3 feet from body) to afford full coverage of sides, roof, front, rear, and undercarriage of vehicle. Evidence of water leakage shall be cause for rejection until leaks are corrected.

4.3.3 Vehicle weight. The first production vehicle, fully equipped, shall be weighed to determine net weight and distribution of net weight on the lunette and on the axle. The imposed loading on the lunette and axle will be computed using the net weight and the payload. Calculated imposed loads on lunette and axle will be utilized to ascertain that the suspension, axle and tires furnished are of adequate capacity to meet contractual requirements.

* 4.3.4 Radio frequency suppression verification. The vehicle manufacturer shall indicate on the questionnaire (commercial vehicle engineering data) if the vehicles will be suppressed to limit electromagnetic radiation in accordance with SAE J551.

4.3.5 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The supplier shall maintain the vehicle in a serviceable condition for the duration of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

4.3.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. Each production vehicle shall be tested for leaks in accordance with 4.3.2, except the duration of the test shall be not less than 5 minutes. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 has been accomplished.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from manufacturer's plant to initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The vehicles covered by this specification are intended for use by the Armed Services for carrying and storing, on site, tools and equipment commonly used for maintenance.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this specificaiton.
(b) Type of vehicle required (see 1.2).
(c) Identification of appropriate service for painting and marking (see 3.1.1.1).
(d) Concealed marking, if required (see 3.1.1.1).
(e) Rustproofing, if required (see 3.1.1.2).
(f) Tropical rustproofing, if required (see 3.1.1.2).
(g) Bias ply tires, if required (see 3.4.4.1).
(h) If a carrier for a spare tire assembly is not required (see 3.4.4.3).
(i) A spare wheel or rim, if required (see 3.4.4.4).
(j) A spare tire assembly, if required (see 3.4.4.5).
(k) If brakes are required on type I, II, and III vehicles (see 3.4.5).
(l) An air brake synchronizing controller, if required in lieu of a hydraulic brake synchronizing controller (see 3.4.5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

(m) Inertia type hydraulic brake system, if required in lieu of electric brakes (see 3.4.5.2).
(n) Wheel chocks, if required (see 3.4.5.4).
(o) If electrical jumper cable is not required (see 3.4.6.2).
(p) Tools, if required (see 3.4.8).
(q) Equipment, if required (see 3.5.2).

6.3 Identification of changes. The margins of this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AT

Preparing activity:
Army - AT
Project No. 2330-0912

*U.S. GOVERNMENT PRINTING OFFICE: 1986–605-036/41488

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.