NOT MEASUREMENT SENSITIVE

MIL-T-46744E(AT)
30 April 1993
SUPERSEDING
MIL-T-46744D(AT)
26 February 1986

MILITARY SPECIFICATION

TRAILERS, MAINTENANCE: 454 AND 910 KILOGRAM (1000 and 2000 POUND) PAYLOAD, TWO WHEEL, MODIFIED COMMERCIAL

This specification is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers four types of modified commercial, two wheel, maintenance trailers. Vehicles procured under this specification are commercial items which are required to be warranted by the manufacturer as specified in acquisition documents.

1.2 Classification. The trailer shall be one of the types listed in table I, as specified (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

TABLE I. Classification.

Type	Body type	Payload	
		Kilograms (kg)	Pounds
I	Cable splicer	454	(1000)
II	Telephone utility	454	(1000)
III	General purpose	454	(1000)
IV	Telephone utility	910	(2000)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS
FEDERAL
* W-B-131 - Battery Storage: Vehicular, Ignition, Lighting and Starting.

STANDARDS
FEDERAL
FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY
MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.
* MIL-STD-1595 - Qualification of Aircraft, Missile and Aerospace Fusion Welders.
MS 51336 - Lunette-Coupler, Drawbar, Ring.
MS 51339 - Coupler, Drawbar, Ring - Offset.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, Military Specifications and Standards, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

* DEPARTMENT OF DEFENSE
Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093.)

DEPARTMENT OF TRANSPORTATION (DOT)
Federal Motor Carrier Safety Regulations (FMCSR).
Federal Motor Vehicle Safety Standards (FMVSS).

* (Application for copies of DOT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)
Code of Federal Regulations, 29 CFR.

(Application for copies of OSHA publications should reference the Code of Federal Regulations, 29 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)
ANSI STANDARDS
ANSI A14.1 - Safety Code for Portable Wood Ladders.

(Application for copies of ANSI publications should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)
ASME Boiler and Pressure Vessel Code (BPVC)
Section IX - Qualification Standard for Welding and Brazing Procedures, Welders, Brazers, and Welding and Brazing Operators.

(Application for copies of ASME publications should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, NY 10017.)

* AMERICAN WELDING SOCIETY (AWS)
AWS B2.1 - Standard for Welding Procedure and Performance Qualifications.
AWS D1.1 - Structural Welding Code-Steel.

(Application for copies of AWS publications should be addressed to the American Welding Society, 2501 NW 7th Street, Miami, FL 31025.)

* THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)
Standards Manual.

(Application for copies of ETRTO publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann, 1060 Brussels, Belgium.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)
SAE Standards and Recommended Practices
J551 - Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30 - 1,000 MHz).
J560 - Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
J1067 - Seven-Conductor Jacketed Cable for Truck-Trailer Connections.
J1292 - Automobile, Truck, Truck-Tractor, Trailer and Motor Coach Wiring.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.
Year Book.

* (Application for copies of Tire and Rim Association Publications should be addressed to The Tire and Rim Association, Inc., 175 Montrose West Ave., Copley, OH 44321.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services).

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.7, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items which meet or exceed the requirements of this specification. All items shall be as represented in the trailer manufacturer's technical data book. Special or mounted equipment shall be as represented in the equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material identical to that furnished to the authorized company representatives for selection of vehicle models and components, and shall be available to the engineering offices of the procuring activity, prior to delivery of the items. The vehicle shall be a standard commercial trailer, of a model sold to a significant number of buyers other than the Government, in the course of normal business operations. The model furnished shall be not older than the manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Treatment and painting. The vehicle shall be treated and painted in accordance with MIL-STD-1223. As specified by the procuring activity for the appropriate military service (see 6.2), the exterior color shall be in accordance with MIL-STD-1223.

* 3.1.1.2 Marking and data plates. As specified by the procuring activity for the appropriate military service (see 6.2), identification markings and data plates shall be in accordance with MIL-STD-1223.

* 3.1.1.3 Rustproofing. The vehicle shall be rustproofed in accordance with FED-STD-297.

* 3.1.1.4 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher or the two systems shall be independent of each other. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard. If additional lights are added to the vehicle, the lights shall be selected from the trailer manufacturer's standard matching hardware.

* 3.1.1.5 Welders and welding. In addition to the requirements of 3.21.4, all welders employed in the fabrication of the trailer shall be certified, before any welding is accomplished, in accordance with MIL-STD-1595; the welding qualifications of the ASME BPVC, Section IX; or AWS B2.1 or D1.1. The certification that the welders have passed the qualification test shall be on file at the contractor's facility and shall be available for review by the Government.

* 3.1.1.6 Lubrication chart. An illustrated or schematic diagram type lubrication chart shall be provided on the trailer. The chart shall direct attention to all lubrication fittings and specify the range and grade of lubricants required for critical temperatures. The chart shall be permanently attached to the trailer in a readily visible location. The chart shall be inscribed on a plate conforming to composition A (class 1 or 2) or composition C of MIL-P-514.

* 3.1.1.7 Lunette. The coupling device specified in 3.11 shall be a lunette conforming to MS 51336. The coupling device also shall be of the offset type conforming to MS 51339 or shall provide equivalent vertical adjustment of not less than 100 mm (4-inches).

* 3.2 General design.

* 3.2.1 Federal Motor Vehicle Safety Standards. The vehicle shall comply with all Federal Motor Vehicle Safety Standards applicable to the type of trailer furnished and in effect on the date of manufacture.

* 3.2.2 OSHA and FMCSR regulations. The vehicle, with only furnished attachments, accessories and equipment, shall enable compliance by any user with all OSHA and FMCSR user regulations that are vehicle or vehicle equipment dependent. Regulations shall be those that are applicable to a commercial user of such a similar type, class and size of trailer for the same general use. See 6.1.

3.2.3 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the appropriate engineering office of the procuring activity.

* 3.2.4 Dissimilar metals. All dissimilar metals used throughout the vehicle shall be insulated from one another to prevent galvanic or electrolytic action.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* 3.2.5 Prohibited materials. Asbestos materials shall not be used in any form in any part of the vehicle. No item, part or assembly shall contain radioactive materials in which the specific activity is greater than 0.002 microcurie per gram or activity per item equals or exceeds 0.01 microcuries.

* 3.2.6 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

* 3.2.7 Lubrication. All moving parts of the trailer normally requiring lubrication shall be provided with means for such lubrication. The lubrication fittings shall be standard commercial type with a surface-check ball.

* 3.2.8 Safety. All equipment or exposed portions of the equipment which are subject to extreme temperatures and inclement weather and all rotating or reciprocating parts which are of such a nature or so located as to become a hazard to operating personnel shall be insulated, fully enclosed, or properly guarded.

3.2.9 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551.

* 3.3 Performance. The trailer shall evidence no part failure, deformation, permanent set or interference between parts when towed, both empty and when loaded as specified in 3.4:

(a) At speeds as great as 32 kilometers per hour (km/h) (20 miles per hour (mph)) over unimproved roads and reasonably hard uneven terrain;
(b) At speeds as great as 97 km/h (60 mph) over improved roads; and
(c) At speeds as great as 16 km/h (10 mph) on 10 percent side slopes on unimproved roads and reasonably hard uneven terrain.

* 3.3.1 Tracking ability. The trailer, coupled to a towing vehicle, shall follow the towing vehicle under the conditions specified in 3.3 without exceeding the tracking deviation specified in Federal Motor Carrier Safety Regulation 393.70(a).

* 3.3.2 Turning ability. When coupled to a towing vehicle operating in its minimum turning circle, the trailer shall follow without cramping or side slipping. The trailer shall be capable of moving through an angle of not less than 60 degrees in relation to a 2590 millimeters (mm) (102-inch) wide towing vehicle without interference between the two vehicles. The angle shall be measured between the longitudinal axis of the trailer and the longitudinal axis of the towing vehicle at the lunette. The ability of the trailer to meet this requirement shall be demonstrated actually or

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

graphically with a 2590 mm (102 inch) wide towing vehicle having its pintle at the extreme rear of the towing vehicle. Interference will be considered to exist if, at the 60 degree angle, any portion of the trailer 1300 mm (51 inches) or less from the lunette is forward of the pintle.

* 3.3.3 Service brakes. The service brakes, in conjunction with a towing vehicle (truck-trailer combination), under all conditions of loading, shall control, decelerate and stop the vehicle combination in accordance with Federal Motor Carrier Safety Regulation 393.52.

* 3.3.4 Parking brakes. The parking brakes shall hold the trailer with specified payload on a dry, hard surfaced grade of not less than 20 percent when uncoupled from the towing vehicle, resting on the trailer's running gear and landing leg, and headed up and down the incline. The parking brake lever shall have sufficient moment arm to require not more than 14 kg (30 pounds) of effort for application and release.

3.4 Payload. The rated payload capacity shall be not less than 454 kg (1000 pounds) for type I, II and III trailers and not less than 910 kg (2000 pounds) for type IV trailers. Requirements shall be met with the payload uniformly distributed over the length of the trailer.

3.4.1 Center of gravity. With the longitudinal axis of the trailer horizontal, the center of gravity of the trailer, both without payload and with a payload as specified in 3.4, shall be forward of the axle. The vertical load on the lunette, with the trailer unloaded, shall be not greater than 91 kg (200 pounds).

3.4.2 Gross weight. The gross weight shall consist of the weight of chassis and body with all attachments and the payload as specified in 3.4. The gross weight of types I, II and III trailer shall be not more than 1360 kg (3000 pounds). The gross weight of type IV trailers shall be not less than 1590 kg (3500 pounds).

* 3.5 Dimensions and clearances. The trailer, uncoupled from the towing vehicle, resting on its landing leg on level ground, without payload shall conform to the dimensions specified in 3.16, 3.17, 3.18, and 3.19, as applicable for the type of trailer specified.

3.6 Frame. The trailer shall have a frame of all steel welded construction with each main frame member in a one piece without splices or joints. A sufficient number of full width crossmembers shall be furnished to ensure stability and rigidity. Crossmembers shall be of full channel, pressed steel construction reinforced by gusset plates or brackets at points of attachment to longitudinal sills. Longitudinal sills shall be reinforced. The sprung weight of the loaded vehicle shall not impose a fiber stress greater than 50 percent of the yield strength of the materials used under the mobile operating conditions specified herein. All parts of the chassis frame where welding is required shall be electrically welded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* 3.6.1 Stress analysis. A stress analysis for the trailer, loaded as specified in 3.4, shall be performed. The stress analysis shall include shear and moment diagrams and deflection calculations. Stress calculations shall include complete analysis of the floor, crossmembers, and longitudinal frame members.

3.7 Axle. The trailer shall be provided with a single axle. The axle rating shall be at least equal to the load imposed on the axle, measured at the ground, with the vehicle loaded as specified in 3.4.

3.8 Suspension. The trailer shall be equipped with an individual wheel, semielliptical spring suspension system having a rated capacity at least equal to the load imposed on each member, measured at the ground, with the vehicle loaded as specified in 3.4. When suspension capacity is rated at the spring pads, unsprung weight shall be deducted.

* 3.9 Wheels, rims and tires. The trailer shall be equipped with single wheels and tires. Rims and tire ratings shall conform to Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations for the type and size of tires furnished. Multi-piece rims shall not be furnished.

* 3.9.1 Tires. Steel belted radial, tubeless, truck type tires, with highway tread shall be furnished. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the vehicle loaded as specified in 3.4. Tires shall conform to Tire and Rim Association or to European Tyre and Rim Technical Organisation recommendations.

* 3.9.2 Carrier for spare tire assembly. A carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. The carrier shall permit ready removal or installation of the spare assembly, using only the tools specified in 3.9.5. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier shall enable the safe removal and installation of the spare tire assembly from and to the vehicle and carrier without personnel positioning themselves or any part of their body under the spare tire assembly.

3.9.3 Spare wheel or rim. When specified (see 6.2), a spare wheel or rim shall be furnished and stowed on the carrier.

* 3.9.4 Spare tire assembly. When specified (see 6.2), a spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design, and load range (ply rating) as furnished on the axle of the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* 3.9.5 Tools. When specified (see 6.2), each vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly, and shall include at least a hydraulic jack, jack handle and wheel nut wrench. The jack shall be of such closed height as to permit its location under the axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking, shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of the wheel and tire assembly.

3.10 Brakes.

* 3.10.1 Electric brakes. Service brakes need not be furnished on type I, II and III vehicles. Type IV trailers shall be furnished with a 12-volt direct current (dc) electric brake system. The brake system shall be wired in accordance with 3.13.4. Brake linings shall be of nonasbestos materials. The system shall include a manual controller kit for mounting on the dash of the towing vehicle, and a controller kit for synchronizing the trailer electric brakes with the brakes of the towing vehicle. Unless otherwise specified, the synchronizing controller shall be for use with a towing vehicle equipped with hydraulic brakes. When specified (see 6.2), the synchronizing controller shall be for use with a towing vehicle equipped with air brakes. Kits shall be complete with all necessary parts and installation instructions. The kits shall be boxed, marked as to contents, and securely attached to the trailer for shipment.

3.10.2 Parking brakes. Manually applied parking brakes shall be furnished on all trailer types. The parking brakes shall conform to Federal Motor Carrier Safety Regulation 393.41. Provisions shall be made for slack adjustment. When brake cables are used, they shall be of corrosion-resistant steel. Lubrication fittings shall be provided.

* 3.10.3 Chock blocks and cradles. Two pairs of wood, plastic, or steel chock blocks with corrosion-resistant captive chains or cables and suitable cradles shall be installed on the trailer. The hook of each captive chain or cable shall be secured to a chock block cradle. The captive chains or cables shall be of a length sufficient to be wrapped around the cradle to hold the chock blocks in place during travel and to allow the wheels to be chocked in the front and the rear. The chock blocks shall be of sufficient size to prevent trailer movement while parked headed up and down a 30 percent slope with full rated payload.

* 3.11 Drawbar and coupling device. The trailer shall be equipped with a drawbar of the "A" frame type formed by the continuation of the trailer main frame side rails. The coupling device shall be a lunette conforming to 3.1.1.7. The lunette shall be positioned so that the longitudinal axis of the lunette is parallel to the trailer body. With the trailer fully loaded and resting on the landing wheel, and with the lunette in its lowest

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

position, the height to the centerline of the lunette shall be 635 mm ± 25 mm (25 inches ± 1 inch). The coupler shall conform to Federal Motor Carrier Safety Regulation 393.70(c).

3.12 Landing leg. The trailer shall have a folding landing leg with a permanently attached caster type landing wheel. The landing leg also shall be capable of telescopic movement with a permanently installed cranking handle. The landing leg and related parts shall withstand, without permanent deformation, the combined static and dynamic forces due to the impact during coupling and uncoupling operations. The landing leg shall operate freely and shall be protected from malfunctioning caused by foreign matter. The caster wheel shall be fitted with antifriction bearings. Means shall be provided to lubricate the landing leg assembly and the wheel bearings. When placed in the travel position, the landing leg shall remain positively locked to provide ground clearance in the course of normal towing operations.

3.13 Electrical system.

3.13.1 Lighting. The electrical lighting system shall be 12 volt dc. All vehicle lights, reflectors and wiring (including electric brakes) shall conform to Federal Motor Carrier Safety Regulations 393.9, 393.11, 393.15, 393.19, 393.22, 93.23, 393.25, 393.26, 393.27 through 393.30, 393.32, and 393.33. Lights and reflectors shall not be mounted on the vertical surface of rub rails (unless recessed and fully protected) or on vehicle bumpers. All electrical wiring shall conform to SAE J1292.

3.13.2 Electrical receptacle socket. An electrical receptacle socket conforming to SAE J560 shall be installed on the forward end of the drawbar. The receptacle shall have a spring loaded cover assembly. Conductors shall be connected and color coded as specified in SAE J560.

* 3.13.3 Truck-trailer electrical cable. A coiled electrical truck-to-trailer cable conforming to SAE J1067, with a cable plug at both ends conforming to SAE J560, shall be provided. Both cable plugs shall be equipped with a grip for withdrawing from the electrical receptacle sockets. Stowage provisions, having an anti-theft feature and means for hanging the cable with the plugs pointing down, shall be provided. The cable shall be not less than 910 mm (3 feet) longer than the distance from the trailer electrical receptacle to the lunette.

3.13.4 Brake wiring. Electric brakes shall be wired to the auxiliary circuit of the SAE J560 seven-conductor electrical connector. All wiring shall be properly mounted and secured with clamps. Wiring shall be heavy wall thermoplastic insulated cable and shall be enclosed in conduit.

* 3.13.5 Breakaway battery. On vehicles with electric brakes, a 12-volt battery shall be furnished to operate the brakes in the event of a breakaway from the towing vehicle. The battery shall be of the maintenance-free type

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

having the maintenance-free characteristics listed in W-B-131. The reserve capacity rating measured in accordance with SAE J537 shall be not less than 35 minutes. The cold cranking rating at -18 degrees Celsius (0 degrees Fahrenheit) measured in accordance with SAE J537 shall be not less than 160 amperes. A battery recharging circuit shall be wired through the first pin of the four-conductor electrical connector specified in 3.13.6. The second pin shall be return ground to the towing vehicle. A diode shall be installed in the system so that the electric current will not flow from the trailer battery to the towing vehicle system. A weatherproof battery box shall be furnished.

* 3.13.6 Breakaway battery wiring. The breakaway battery shall be wired to two conductors of a four-conductor electrical connector receptacle, Midland Model 23400 or equal. A second identical receptacle for mounting on the towing vehicle shall be furnished. The receptacles shall be polarized and weatherproof. A connecting cable, each end equipped with a mating plug, Midland Model 23403 or equal, shall be furnished. The cable shall be not less than 910 mm (3 feet) longer than the distance from the four-conductor receptacle to the lunette.

3.14 Bumper. A rear bumper shall be furnished. The bumper shall be as specified herein for the various body types. Rear end protection shall conform to Federal Motor Carrier Safety Regulation 393.86.

* 3.15 Body mounting. The body shall be secured with U-bolts, twin studs or brackets and shall include a wood breaker strip.

3.15.1 U-bolts or twin studs. When U-bolts or twin studs are used, there shall be not less than three U-bolts or twin studs per side, each having 14 mm (0.563 inch) diameter with 16 mm (0.625 inch) minimum thread diameter. Tie-plates shall be at least 13 mm (0.5 inch) thick. The vehicle chassis frame shall be braced, using wood blocks at each mounting point unless the mounting point is located at a full depth frame crossmember. Blocks shall incorporate a keeper strap or groove for the mounting bolt, and shall be of a width and thickness to assure retention. Two tie-back straps shall be provided, one bolted to each side of the rear portion of the body subframe, to maintain body alinement on the vehicle chassis.

3.15.2 Brackets. When brackets are used, they shall be bolted to the web of the chassis frame rails. The body mounting brackets shall provide means for drawing down the body on the chassis rails and provisions shall be made to prevent lateral shifting of the breaker strips. Attachments shall not interfere with nor obstruct chassis components.

3.15.3 Breaker strips. A hardwood or dense southern yellow pine breaker strip, not less than 25 mm (1 inch) finished thickness, shall be installed between longitudinal sills and the vehicle chassis frame.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

3.16 Type I (cable splicer) body. The body shall be of steel construction. The vehicle and the body shall conform to the dimensions in table II.

TABLE II. Dimensions, type I.

	mm	Inches
Overall:		
Vehicle length (maximum)	2540	(100)
Vehicle width (maximum)	1780	(70)
Ground clearance (minimum)	230	(9)
Body inside:		
Length (minimum)	1620	(64)
Width (minimum)	1120	(44)
Height (minimum)	1090	(43)

3.16.1 Compartment arrangement. The trailer shall be equipped with the manufacturer's standard cable splicer body. The body shall be complete with fenders and shall provide for weathertight storage of all standard cable splicer equipment. The compartment arrangement of the body shall include:

(a) A shallow front compartment extending the full width and height of the trailer body, divided vertically to provide for hanging clothes and for shelf storage of small items.
(b) A horizontal compartment on both sides of the body, above the wheelwells, extending from the rear of the front compartment (see (a) above) to the rear of the body.
(c) A compartment across the rear, between the wheelwells, and below the horizontal compartments, (see (b) above).
(d) A curbside compartment, near the front, and below the horizontal compartments (see (b) above).
(e) Shelf arrangement and partitioning of compartments shall be the manufacturer's standard for cable splicer trailers and shall include not less than two decks of small bins with adjustable partitions in the right side horizontal compartment (see (b) above).

3.16.2 Compartment doors. The compartment doors shall provide access to all portions of each compartment. Door closures shall be weatherproof. The doors shall have continuous rod or hem type heavy duty hinges, with stainless steel hinge pins and stainless steel, nylon, or nylon insert sockets. Latches shall have recessed handles. All doors shall be provided with cylinder type locks, operable with one key but not with the same key on more than one vehicle. Moving parts of latches and locks shall be constructed of, or plated with, corrosion-resistant material. Horizontal doors shall be provided with stays and shall be hinged and reinforced so as to permit use as a shelf and shall be capable of supporting a live load of not less than 120 kilogram per square meter (kg/m^2) (25 pounds per square foot).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

3.16.3 Rear bumper. A rear bumper, extending not less than 75 mm (3 inches) beyond the rear of the body, shall be furnished.

3.17 Type II (telephone utility) body. The body shall be of steel construction, having a center load compartment, with cabinets on each side. When specified (see 6.2), the vehicle shall be furnished with a pipe rack on the top of the right cabinet, a standard pipe vise bracket and pipe rest on the right side of the cabinet, and shall have rope loops in lieu of adjustable shelves inside the left vertical cabinet. The vehicle and the body shall conform to the dimensions specified in table III.

TABLE III. Type II dimensions and loading requirements.

Overall:		
Vehicle length (maximum)	3430 mm	(135 inches)
Vehicle width (maximum)	2030 mm	(80 inches)
Ground clearance (minimum)	230 mm	(9 inches)
Load space:		
Length (minimum)	1900 mm	(75 inches)
Width (minimum)	1170 mm	(46 inches)
Height (minimum)	660 mm	(26 inches)
Cabinet space:		
Length (minimum)	1900 mm	(75 inches)
Height (minimum)	940 mm	(37 inches)
Width (minimum)	360 mm	(14 inches)
Volume (each side) (minimum)	.49 cubic meters(m^3)	17.36 cubic ft(ft^3)
Loading without permanent deformation:		
Load space floor - live load on any square foot of area (minimum)	227 kg	(500 pounds)
Cabinet and shelves - live load on any square foot of area (minimum)	45 kg	(100 pounds)

3.17.1 Bulkhead. A front bulkhead shall be provided. The bulkhead shall be constructed to the full height of the cabinets and shall be of not less than 18 gage (1.214 mm) (0.0478 inch) high tensile steel or 16 gage (1.519 mm) (0.0598 inch) carbon steel reinforced for rigidity.

3.17.2 Tailgate. A tailgate shall be provided. The tailgate shall be constructed of not less than 18 gage (1.214 mm) (0.0478 inch) high tensile steel or 16 gage (1.519 mm) (0.0598 inch) carbon steel reinforced for rigidity. The tailgate shall be hinged and equipped with supports for retention in horizontal position, flush with or slightly lower than the floor level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

3.17.3 Rear bumper. A rear bumper shall be provided. A safety tread steel plate step, integrated with the rear bumper, extending across the width of the body and with a step surface not less than 250 mm (10 inches) deep, shall be provided. A toe plate extending from the top of the bumper up to the bottom of the body shall be provided.

3.17.4 Cabinet material and construction. Cabinet headers shall be not less than 18 gage (1.214 mm) (0.0478 inch) high tensile steel or 16 gage (1.519 mm) (0.0598 inch) carbon steel. Cabinet backs, partitions, and shelves shall be of not less than 20 gage (0.919 mm) (0.0359 inch) high tensile steel or 18 gage (1.214 mm) (0.0478 inch) carbon steel. Cabinet doors shall be of not less than 20 gage (0.919 mm) (0.0359 inch) high tensile or 18 gage (1.214 mm) (0.0478 inch) carbon steel, single thickness reinforced, or 22 gage (0.759 mm) (0.0299 inch) carbon steel, double panel reinforced.

3.17.5 Cabinet arrangement. Cabinet arrangement shall include full-height vertical cabinets with not less than two adjustable shelves on each side of the body at the front; a horizontal cabinet with not less than two decks of small bins with adjustable partitions on the right side of the body; and a horizontal cabinet with not less than one tray type shelf on the left side of the body.

3.17.6 Cabinet doors. Cabinet doors shall provide access to all portions of each cabinet. Door closures shall be weatherproof. Doors shall have continuous rod or hem type heavy duty hinges with stainless steel hinge pins and stainless steel, nylon, or nylon insert sockets. Latches shall have recessed handles. All doors shall be provided with cylinder type locks, operable with one key but not with the same key on more than one vehicle. Moving parts of latches and locks shall be constructed of, or plated with, corrosion-resistant material. Horizontal doors shall be provided with stays and shall be hinged and reinforced so as to permit use as a shelf and shall be capable of supporting a live load of not less than 120 kg/m^2 (25 pounds per square foot).

3.17.7 Overhead racks and ladder. A 7320 mm (24-foot), two-section wooden extension ladder and removable overhead racks, with ladder brackets, shall be provided. The ladder shall conform to ANSI A14.1. The rear bow of the overhead rack shall be provided with pivoted ladder clamps for carrying, erecting, and using the extension ladder. Anchor points for the foot of the ladder shall be set into the step bumper and shall be not less than 75 mm (3 inches) deep. When erected using the rear bow and anchor points, the angle of the ladder with horizontal shall be between 75 and 85 degrees. A rope and pulleys for use in extending and retracting the ladder shall be provided.

3.18 Type III (general purpose) body. The body shall be of steel construction. The vehicle and the body shall conform to the dimensions in table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

TABLE IV. Dimensions, type III.

	mm	Inches
Overall:		
Vehicle length	2290 ± 50	(90 ± 2)
Vehicle width (maximum)	1780	(70)
Ground clearance (minimum)	230	(9)
Body inside:		
Length (minimum)	1520	(60)
Width (minimum)	760	(30)
Height (minimum)	640	(25)

3.18.1 Compartment arrangement. The trailer shall be equipped with the manufacturer's standard general purpose body. The body shall be weathertight. The body shall have a roof top which pivots on a continuous hinge the full length of the body, operable from the curbside, and which automatically holds up in fully opened position. A fold down type curbside door, with continuous horizontal hinge, not less than 300 mm (12 inches) wide and the length of the body, shall serve as a work bench when in horizontal fold down position. The door shall be on the upper half of the body and shall be supported by chains on both ends with sufficient capacity to hold up an equitable load imposed on the door. The door shall be lined with exterior plywood. Two bin type shelves, each the full length of the body, 200 and 300 mm (8 and 12 inches) wide respectively, shall be furnished. The shelves shall be installed on the left side with the 200 mm (8-inch) shelf at the top and the 300 mm (12-inch) shelf below. The side door shall be flush with the body when closed. The top and side doors shall be provided with suitable hasp type locking devices. Locks are not required.

3.18.2 Rear bumper. A rear bumper, extending not less than 75 mm (3 inches) beyond the rear of the body, shall be furnished.

3.19 Type IV (telephone utility) body. The body shall be of steel construction, having a center load compartment, with cabinets on each side. The body shall be equipped with a telescoping roof and tailgate enclosure, a pipe rack on top of the right cabinet, a standard pipe vise bracket and a pipe rest on the right side cabinet. The vehicle and body shall conform to the dimensions in table V. The vehicle shall comply with the requirements specified for type II vehicles in 3.17 through 3.17.7 for bulkhead, tailgate, rear bumper, cabinet material and construction, cabinet arrangement, cabinet doors, overhead racks and ladder. Rope hooks in lieu of adjustable shelves shall be furnished inside the left vertical cabinet. The telescoping roof and tailgate enclosure (in addition to the cabinets) shall be weathertight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

TABLE V. Type IV Dimensions and loading requirements.

Overall:		
Vehicle length (maximum)	4320 mm	(170 inches)
Vehicle width (maximum)	2030 mm	(80 inches)
Ground clearance (minimum)	230 mm	(9 inches)
Load space:		
Length (minimum)	2590 mm	(102 inches)
Width (minimum)	1170 mm	(46 inches)
Height (minimum)	660 mm	(26 inches)
Cabinet space:		
Length (minimum)	2590 mm	(102 inches)
Height (minimum)	940 mm	(37 inches)
Width (minimum)	360 mm	(14 inches)
Volume (each side) (minimum)	0.66 m^3	(23.15 ft^3)
Loading without permanent deformation:		
Load space floor - live load on any square foot of area (minimum)	227 kg	(500 pounds)
Cabinet and shelves - live load on any square foot of area (minimum)	45 kg	(100 pounds)

3.20 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, the contractor shall service and adjust the vehicle for immediate operational use. The servicing and adjustment shall include at least the following:

(a) Inflation of all tires
(b) Adjustment of brakes
(c) A check for proper functioning of all lights
* (d) Filling and charging of batteries
(e) Complete lubrication with grades of lubricants recommended for ambient air temperature at the delivery point.

* 3.21 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Bolted, riveted and welded construction used shall be in accordance with the highest standards of the industry.

* 3.21.1 Metal fabrication. Metal used in the fabrication of the vehicle shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause damage to the metal. Shearing and chipping shall be done neatly and accurately. All bends of a major character shall be made with controlled means in order to ensure uniformity of size and shape.

* 3.21.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* 3.21.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

* 3.21.4 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease or other foreign matter. Weld shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are subjected to proof and service loading. See 3.1.1.5.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is respinsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of the product to specification criteria has been demonstrated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* 4.3 First production vehicle inspection. The first vehicle of each type produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance with the requirements of the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

* 4.3.1 Trailer weight. The trailer shall be weighed to determine the curb weight and the distribution of the curb weight on the lunette and the rear axle. The imposed loading on the lunette and rear axle, with payload, shall be computed using curb weight and the trailer payload distributed as specified in 3.4. The rated capacity of the axles, suspension system and tires shall be compared to the loads imposed on them to determine if they conform to contract requirements.

* 4.3.2 Road test. The first vehicle for each contract line item number (CLIN) under contract shall be road tested with and without payload. The road test shall be for the distance required in table VI, corresponding to the number of vehicles being procuring under the specific contract line item number (CLIN). The test shall be conducted by the contractor under the direction of Government representatives. The test shall be conducted over a test course approved by the procuring activity and meeting the requirements of table VII. The vehicle shall be inspected periodically during and at the completion of the test by the contractor.

TABLE VI. Road test distance.

Number of vehicles being procured	Road test distance km	(miles)
1 - 10	160	(100)
11 - 20	320	(200)
21 - 30	480	(300)
31 - 40	640	(400)
41 - 50	800	(500)
51 - 100	1600	(1,000)
101 - up	8050	(5,000)

TABLE VII. Test course requirements.

Type of road	Road test distance
Dirt	10 percent
Gravel	30 percent
Improved pavement	60 percent

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

* 4.3.2.1 Test course. The total test mileage shall be on roads and highways within the general geographic limits of the place of manufacture and adjoining states. Any special highway permits required shall be obtained by the contractor. The course shall be arranged to return the vehicle to the manufacturer's plant at the completion of each 1600 km (1,000 miles), if applicable, or at the completion of the test otherwise, for inspection and chassis servicing.

* 4.3.2.2 Test loads. The trailer shall be tested for 70 percent of the mileage with the trailer loaded as specified in 3.4 and for 30 percent of the mileage with the trailer empty. Average speeds during all road tests shall be as close as possible to those specified in 3.3.

* 4.3.2.3 Road test failure. The vehicle shall successfully complete the entire test. Failure of the vehicle to successfully complete the test shall be cause for nonacceptance of any of the contract quantity, pending correction of deficiencies and evidence of corrective action which shall prevent the recurrence of similar deficiencies in the contract quantity. Failure of the vehicle to successfully complete the test shall not constitute an excusable delay in meeting scheduled deliveries. The equipment shall be closely monitored throughout the test for interference with towing operations, and for instability as evidenced by poor tracking or uncontrollable sideslipping, skidding, swerving, or tilting. The equipment also shall be closely monitored for loosening of parts, interference between parts, leakage of fluids or lubricants, overheating of components, and for damage, permanent distortion, or excessive wear of parts and components. The equipment shall be disassembled to the extent necessary for inspection for unusual wear or damage to components. Substitution of a new trailer or replacement of a major component may require complete retest at the discretion of the Government representatives. Rejection of the test trailer shall be for damage or deficiencies, including but not limited to the following:

(a) Damage caused by collision
(b) Failure of any major component
(c) Vibration due to misalinement of wheels or frame
(d) Vibration due to the type of construction or mounting
(e) Evidence of abnormal tire wear due to misalinement or unbalance
(f) Failure of any vehicular safety device such as brakes or electrical circuits
(g) Evidence of structural weakness in any part of the vehicles, vehicle components, accessories or welds
(h) Loose mountings of parts or accessories due to workmanship or vehicular operation.

* 4.3.3 Brake tests. Brake tests to determine conformance to requirements shall be conducted during the road test. The brake tests shall be conducted with the fully loaded trailer coupled to a truck with a gross vehicle weight rating (GVWR) of not more than 6800 kg (15,000 pounds) for type I, II and III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

trailers and 10 900 kg (24,000 pounds) for type IV trailer. Failure of the vehicle combination to stop within the required 12 200 mm (40 feet) from a speed of 32 km/h (20 mph) shall be cause for rejection.

* 4.3.4 Turning ability test. A truck shall be coupled to the trailer and driven through turns up to 60 degrees to the towed vehicle, right and left, to determine conformance to 3.3.2. At the conclusion of five turns in each direction, the truck and the trailer shall be examined for evidence of binding, misalinement or other damage.

* 4.3.5 Parking brake test. To test parking brakes, the trailer, with rated payload, shall be placed on a grade, first headed up the grade and then headed down the grade, and tested to determine conformance to 3.3.5. These tests shall be conducted with the trailer disconnected from the towing vehicle and resting on the landing leg.

* 4.3.6 Electrical test. An electrical test shall be conducted to determine that all vehicle lights are functioning.

* 4.3.7 Water spray test. The trailer shall be subjected to a water spray test after the road test. The spray shall be delivered by nozzles operating at 172 kPa (25 pounds per square inch) (psi) nominal water pressure at the inlet to the nozzles. A sufficient number of nozzles, placed approximately 910 mm (3 feet) from the body, to afford full coverage of the sides, roof, front, rear, and undercarriage of the vehicle shall be used. The vehicle shall be subjected to the spray for not less than 15 minutes. Evidence of water leakage shall be cause for rejection until leaks are corrected.

* 4.3.8 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample, and shall be the last vehicle shipped on the contract. The contractor shall maintain the vehicle in an as new condition for the duration of the contract. Release of the first production vehicle for shipment prior to completion of the contract shall be at the discretion of the local Government Quality Assurance Representative (QAR).

* 4.3.9 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under the contract until corrective action has been taken.

* 4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting the performance requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Vehicle processing. The vehicle shall be processed for shipment, from the manufacturer's plant to the initial receiving activity, in accordance with manufacturer's standard commercial practice.

6. NOTES

* 6.1 Intended use. The vehicles covered by this specification are intended for Government use by to carry and then store, on site, tools and equipment commonly used for electrical and phone line construction and maintenance.

* 6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) Type of vehicle required (see 1.2).
(c) Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
(d) Identification of appropriate military service for painting and marking (see 3.1.1.1 and 3.1.1.2).
(e) A spare wheel or rim, if required (see 3.9.3).
(f) A spare tire assembly, if required (see 3.9.4).
(g) Tools, if required (see 3.9.5).
(h) An air brake synchronizing controller, if required in lieu of a hydraulic brake synchronizing controller (see 3.10.1).
(i) Additional equipment, if required for type II telephone utility trailer (see 3.17).

* 6.3 Subject term (key word) listing.

Breakaway battery
Chock blocks
Electric brakes
Landing leg
Non-tactical vehicle (NTV)
Safety chain
Trailer, cable splicer
Trailer, general purpose
Trailer, telephone utility
Welder's qualifications.

6.4 Identification of changes. The margins of this document are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire contents regardless of the marginal notations and relationship to the previous issue.

Custodian:
Army - AT

Preparing activity:
Army - AT

Project No. 2330-A133

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-46744E(AT)	2. DOCUMENT DATE (YYMMDD)

3. DOCUMENT TITLE TRAILERS, MAINTENANCE: 454 AND 910 KILOGRAM (1000 and 2000 POUND) PAYLOAD, TWO WHEEL, MODIFIED COMMERCIAL

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME US Army Tank Automotive Command Warren, Michigan 48397-5000 AMSTA-UED	b. TELEPHONE (Include Area Code) (1) Commercial: 313-574-6407 (2) AUTOVON: 786-6407
c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2025-10-22T06:49Z
Check the source to verify that this is the current version before use.