NOT MEASUREMENT SENSITIVE

MIL-T-46768D(AT)
5 November 1992
SUPERSEDING
MIL-T-46768C(AT)
5 May 1986

MILITARY SPECIFICATION

TRAILERS, LIVING QUARTERS: SELF-CONTAINED, MODIFIED COMMERCIAL

This specification is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers five sizes of self-contained, all metal aircraft type construction, travel trailers for use as living quarters. Trailers procured under this specification are commercial items which are required to be warranted by the manufacturer as specified in acquisition documents.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC-2330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

1.2 Sizes. Size of vehicle shall be determined by the minimum overall length and minimum gross weight rating, as specified in table I (see 6.2).

* TABLE I. Sizes.

	Overall length (minimum)		Gross weight rating (minimum)	
Size	millimeters (mm)	(feet)	kilograms (kg)	(pounds)
21	6400	(21)	2500	(5,500)
25	7600	(25)	3090	(6,800)
29	8840	(29)	3090	(6,800)
32	9750	(32)	3770	(8,300)
34	10 360	(34)	4041	(8,900)

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specification, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of specifications and standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

* A-A-393 - Extinguishers, Fire, Dry-Chemical, (Hand-Portable).

W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting and Starting.

STANDARDS

FEDERAL

FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

MIL-STD-810 - Environmental Test methods.

MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking, and Data Plate Standards.

MS 51336 - Lunette-Coupler, Drawbar, Ring.

MS 51339 - Coupler, Drawbar, Ring-Offset (Taper Shank).

MS 75020 - Connector Plug, Electrical - 12 Contact, Intervehicular, 28 Volt, Waterproof.

MS 75021 - Connector, receptacle, Electrical, 12 - Contact, Intervehicular, 28 Volt, Waterproof.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, Military Specifications and Standards, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

* DEPARTMENT OF DEFENSE
Department of Defense Index of Specifications and Standards (DODISS).

(Copies of the DODISS are available on a yearly subscription basis either from the Government Printing Office for hard copy, or microfiche copies are available from the Director, Navy Publication and Printing Service Office, 700 Robbins Avenue, Philadelphia, PA 19111-5093.)

DEPARTMENT OF TRANSPORTATION (DoT)
Federal Motor Carrier Safety Regulations.
Federal Motor Vehicle Safety Standards.

* (Application for copies of DoT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

* 2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

* THE EUROPEAN TYRE AND RIM TECHNICAL ORGANISATION (ETRTO)
Standards Manual

(Application for copies of ETRTO publications should be addressed to the European Tyre and Rim Technical Organisation, 32, Avenue Brugmann, 1060 Brussels, Belgium.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)
National Electric Code

(Application for copies of NEMA publications should be addressed to the National Electrical Manufacturers Association, 2101 "L" Street, N.W., Washington D.C. 20037.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA No. 501	- Standard for Recreational Vehicles.

(Application for copies of NFPA publications should be addressed to National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

SAE, INC.

SAE Standards and Recommended Practices.

J350	- Spark Arrester Test Procedure for Medium Size Engines (DoD adopted).
J551	- Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1000 MHz).
J560	- Seven-Conductor Electrical Connector for Truck-Trailer Jumper Cable.
J588	- Turn Signal Lamps.
J684	- Trailer Couplings, Hitches and Safety Chains.
J1067	- Seven-Conductor Jacketed Cable for Truck-Trailer Connections.
J1292	- Automobile, Truck, Truck-Tractor, Trailer, and Motor Coach Hiring.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

THE TIRE AND RIM ASSOCIATION, INC.

Year Book.

* (Application for copies of Tire and Rim Association publications should be addressed to The Tire and Rim Association, Inc., 175 Montrose West Ave., Copley, OH 44321.)

* (Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.6, the trailer shall be the manufacturer's current standard commercial model of all metal aircraft type

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

construction, with standard or optional items which meet or exceed the requirements of this specification. The trailer shall be travel type, intended for living quarters, and shall be completely self-contained. All items shall be as represented and rated in the manufacturer's sales information, including special or mounted equipment. The model furnished shall be not older than the manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Treatment and painting. The vehicle shall be treated and painted in accordance with MIL-STD-1223. As specified by the procuring activity for the appropriate service (see 6.2), the exterior color shall be in accordance with MIL-STD-1223.

* 3.1.1.2 Markings and data plates. As specified by the procuring activity for the appropriate military service (see 6.2), identification marking and data plates shall be in accordance with MIL-STD-1223. When specified (see 6.2), concealed markings shall be furnished.

* 3.1.1.3 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297.

3.1.1.4 Coupling device. When specified (see 6.2), the trailer shall be equipped with a lunette coupler ring conforming to MS 51336 and MS 51339. The lunette installation shall provide for a 100 mm (4-inch) vertical range of adjustment.

* 3.1.1.5 Blackout provisions. When specified (see 6.2), in addition to the manufacturer's standard drapes (see 3.5.11(f)), all windows and doors shall have blackout curtains, shades, or other means of preventing the interior light from being visible outside of the vehicle.

* 3.1.1.6 Brake lights. At least one pair of brake lights shall override the four-way emergency flasher or the two systems shall be independent of each other. Modifications to the manufacturer's standard product to accommodate this requirement shall not compromise conformance to any Federal Motor Carrier Safety Regulation referenced herein or to any Federal Motor Vehicle Safety Standard.

3.2 General design.

3.2.1 Safety standards. The plumbing, heating and electrical systems shall conform to National Fire Protection Association (NFPA) Standard No. 501. The vehicle and all furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

* 3.2.2 Dissimilar metals. All dissimilar metals used throughout the vehicle shall be insulated from one another to prevent galvanic or electrolytic action.

* 3.2.3 Prohibited materials. Asbestos materials shall not be used in any form in any part of the vehicle. No item, part or assembly shall contain radioactive materials in which the specific activity is greater than 0.002 microcurie per gram or activity per item equals or exceeds 0.01 microcuries.

* 3.2.4 OSHA and FMCSR regulations. The vehicle, with all furnished attachments, accessories and equipment, shall enable compliance by any user with all OSHA and FMCSR user regulations that are vehicle or vehicle equipment dependent. Regulations shall be those that are applicable to a commercial user of such a similar type, class and size of semitrailer for the same general use. See 6.1.

* 3.2.5 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

3.2.6 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings shall be available to the appropriate engineering office of the procuring activity. Minimum payload shall conform to 1.2 for the specified size of the vehicle.

3.2.7 Gross weight. Gross weight shall consist of curb weight, personal cargo, and full complement of fuel and water. Minimum gross weight rating shall conform to table I.

* 3.2.8 Weight distribution. The distribution of gross weight for the purpose of establishing suspension, axle, and tire capacities shall be determined with the payload distributed so that the load imposed on the hitch is between 10 and 15 percent of the specified gross weight rating.

3.2.9 Curb weight. The curb weight of the fully equipped trailer shall include the chassis weight and the weight of all attachments, accessories, and equipment and shall be the minimum practicable for the service intended.

3.3 Performance. Vehicle performance, as specified in 3.3.1 through 3.3.3, shall be met by the trailer when fully equipped with all attachments and accessories, completely serviced, and towed by a towing vehicle over improved and unimproved, hard, uneven terrain. The vehicle shall show no evidence of failure or malfunction of trailer, trailer components, attachments and accessories.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

* 3.3.1 Towing speed and trailing ability. While being towed over dry, level, smooth, improved and prepared hard-surfaced roads at sustained speeds up to 97 kilometers per hour (km/h) (60 miles per hour (mph)), and over dry, unimproved and gravel roads at speeds to 41 km/h (25 mph), the trailer shall follow the towing vehicle without exceeding the tracking deviations specified in Federal Motor Carrier Safety Regulation 393.70(a).

3.3.2 Turning ability. When coupled to a towing vehicle operating in its minimum turning circle, the trailer shall follow without cramping, and shall trail without interference with the towing vehicle. The trailer shall be capable of moving through an angle of not less than 60 degrees in relation to a 2440 (96-inch) wide towing vehicle without interference between vehicles. The angle shall be measured between the longitudinal axis of the trailer and the longitudinal axis of the towing vehicle at the lunette or ball hitch.

3.3.3 Service brakes. The service brakes shall comply with the performance requirements in Federal Motor Carrier Safety Regulation 393.52. The trailer brake system shall include an automatic breakaway feature conforming to Federal Motor Carrier Safety Regulation 393.43(d).

* 3.3.3.1 Automatic actuation. The trailer shall be equipped with an automatically actuated device to apply the vehicle brakes upon breakaway from the towing vehicle. The breakaway system shall conform to Federal Motor Carrier Safety Regulation 393.43.

* 3.3.4 Suspension system. The axle, springs, accessories and components of the suspension system shall withstand the imposed loads without evidence of permanent set, part failure or malfunctioning under the operating conditions specified.

3.4 Trailer components.

3.4.1 Frame. The frame shall be all steel construction and shall be designed to transport the weight of the trailer body with all equipment. The frame shall support the body full width.

* 3.4.2 Hitch assembly. Unless otherwise specified (see 3.1.1.4), the trailer shall be equipped with a standard ball hitch assembly, conforming to SAE J684, complete with mating ball for installation on the towing vehicle. Anti-sway bar(s) shall be provided. When specified, the trailer shall be equipped with a lunette coupler ring in accordance with 3.1.1.4.

3.4.3 Suspension. The suspension system and running gear shall have a rated capacity at least equal to the load imposed on each member, measured at the ground, with the trailer loaded as specified in 3.2.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

* 3.4.4 Axles. Size 21 through 32 trailers shall be of the four-wheel, tandem-axle type. Size 34 shall be of the six-wheel, tri-axle type. Axle ratings shall be at least equal to the load imposed on each axle, measured at the ground, with weight distributed as specified in 3.2.6.

* 3.4.5 Wheels, rims and tires. The trailer shall be equipped with wheels or rims, and tires, as specified herein. The rim and tire ratings shall conform to Tire and Rim Association or European Tyre and Rim Technical Organisation recommendations for the type and size of tires furnished. Rim sizes shall be the same for all wheels on the trailer. Tire size and load range (ply rating) shall be the same for all tires on the trailer. Multi-piece rims shall not be furnished. When specified (see 6.2), disc type wheels shall be furnished.

* 3.4.5.1 Tires. Tires shall be steel belted radial, tubeless type with highway tread. Tires shall have a rated capacity at least equal to the load imposed on each tire, measured at each wheel, at the ground, with the trailer loaded as specified in 3.2.6. Tires shall conform to Tire and Rim Association or to the European Tyre and Rim Technical Organisation recommendations.

3.4.5.2 Spare tire assembly. A spare tire assembly shall be furnished. The spare tire assembly shall include an inflated spare tire mounted on the spare wheel or rim. The spare tire shall be of the same size, tread design, and load range (ply rating) as furnished on the vehicle.

* 3.4.5.3 Carrier for spare tire assembly. A carrier for a spare wheel or rim and tire assembly shall be installed in a readily accessible location on the vehicle. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of or plated with corrosion-resistant material. The carrier shall enable the safe removal and installation of the spare tire assembly from and to the vehicle and carrier without personnel positioning themselves or any part of their body under the spare tire assembly. Carrier design shall enable removal or mounting of spare wheel assembly using only tools specified in 3.4.12.

3.4.6 Brakes.

* 3.4.6.1 Service brakes. The trailer shall be equipped with a 12-volt electric brake system wired in accordance with 3.4.7.2. Brake linings shall be asbestos free. The system shall include a manual controller kit for mounting on the dash of the towing vehicle, a controller kit for synchronizing the trailer electric brakes with the brakes of the towing vehicle, and an emergency breakaway kit. Kits shall be complete with all necessary parts and installation instructions. Unless otherwise specified, the synchronizing controller shall be for use with hydraulic brake equipped towing vehicles. When specified (see 6.2), the synchronizing controller shall be for

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

use with air brake equipped towing vehicles. The kits shall be boxed, marked as to contents, and securely stowed in the trailer for shipment.

* 3.4.6.2 Wheel chocks. Four wheel chocks shall be provided. Wheel chocks shall be secured to the trailer with corrosion-resistant chains. Provision for stowage in their respective areas shall be provided.

3.4.7 Electrical systems. The trailer shall be provided with 12-volt direct current (dc) and 120-volt alternating current (ac) electrical systems. A 120-volt ac and a 12-volt dc interior lighting system, including 120-volt ac convenience outlets, shall be provided. Exterior lighting system shall be 12-volt dc and shall conform to Federal Motor Carrier Safety Regulations 393.14, 393.19, 393.20, 393.22, 393.23, 393.25 (a, b, c and d), and 393.27 through 393.33. Lights and reflectors shall not be mounted on vehicle bumpers. Turn signal lamps shall conform to SAE J588. All 12 and 24-volt wiring shall conform to SAE J1292. All 120-volt ac wiring shall conform to the National Electric Code.

3.4.7.1 12-volt electrical receptacle. A trailer electrical receptacle with a spring-loaded cover assembly shall be installed on the forward end of the drawbar. The receptacle shall conform to SAE J560, with conductors connected and color coded as specified in SAE J560.

* 3.4.7.2 Brake wiring. Electric brakes shall be wired to the auxiliary circuit of the SAE J560 seven-conductor electrical connector. When a 24-volt receptacle system is furnished (see 3.4.7.5), means shall be provided to reduce the voltage of a tactical military design towing vehicle for proper operation of the electric brakes. All wiring shall be properly mounted and secured with clamps. Wiring shall be heavy wall thermoplastic insulated cable and shall be enclosed in conduit.

* 3.4.7.3 Electrical jumper cable. A pre-coiled electrical jumper cable conforming to SAE J1067, with a cable plug at each end conforming to SAE J560, shall be provided. Both plugs shall be equipped with a grip for withdrawing from connector sockets. Stowage provisions having an anti-theft feature and means of hanging the cable with the plugs pointing down shall be provided. The fully extended cable shall be not less than 910 mm (3 feet) longer than the distance from the trailer electrical receptacle to the lunette or ball hitch.

* 3.4.7.4 Battery. The trailer shall be furnished with not less than one heavy duty, deep cycle type, 12-volt battery. Battery(s) shall provide sufficient power for the 12-volt dc interior electrical system and shall have a total capacity of not less than 105 ampere hours at a 20 hour rate. Battery(s) shall be designed for deep discharge cycles. Provisions for charging the battery(s) from the towing vehicle, from the 120-volt ac electrical system, and the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

engine-generator shall be provided. The battery(s) shall be of the maintenance-free type having the maintenance-free characteristics listed in W-B-131.

3.4.7.5 24-Volt receptacle system. When specified (see 6.2), the trailer shall be equipped with a nominal 24-volt receptacle system. The receptacle shall have 12-contacts and a cover, shall conform to MS 75021-1, and shall be installed at the front of the trailer. The 12-contact receptacle shall be provided with resistance to each circuit to reduce the voltage of a tactical military design towing vehicle from a nominal 24 volts to 12 volts. The 24-volts, 12-contact receptacle shall be connected through the necessary resistors into the 12-volt trailer circuits as follows:

(A) Do not connect.
(B) Connect to yellow circuit.
(C) Do not connect.
(D) Connect to white circuit.
(E) Connect to black and brown circuits.
(F) Do not connect.
(H) Do not connect.
(J) Connect to green circuit.
(K) Connect to blue circuit.
(L) Do not connect.
(M) Connect to trailer electric brakes.
(N) Connect to trailer electric brakes.

Circuits B & J on tactical trucks are combination stop and turn indicator circuits. The normal 12-volt turn signal lights will function both as turn signals and stop lights and the normal 12-volt stop lights will not be in operation when the trailer is connected to a towing vehicle with a 24-volt power supply. Because of this condition, the stop light red conductor circuit is not connected to the 24-volt, 12-contact receptacle.

3.4.7.5.1 Resistor assembly. Each circuit resistor shall be selected to reduce the 28-volt dc regulated voltage of a tactical truck to within the maximum rated voltage of the trailer electrical components. The resistor assembly shall be located in a protective housing and provided with adequate ventilation or a heat sink to preclude overheating and any damage to resistors, wiring, or adjacent components.

3.4.7.5.2 Twelve-conductor jumper cable. A twelve-conductor jumper cable shall be furnished for trailers with a 24-volt receptacle system. The cable shall be equipped with a connector conforming to MS 75020-1 at one end and a connector conforming to MS 75020-2 at the other end. The cable shall be not less than 910 mm (three feet) longer than the distance from the trailer electrical receptacle to the lunette or ball hitch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

3.4.7.6 Alternating current system. The trailer shall be furnished with at least one outside weatherproof receptacle and cover for connection to an outside source of 120-volts ac. A connecting cable, minimum length of 7600 mm (25 feet), shall be furnished for the 120-volt system.

* 3.4.7.7 Engine-generator. An engine-generator set shall be provided to furnish auxiliary power for the air conditioner, the battery charger, and the 120-volt ac electrical system. The generator shall provide not less than 3000 watts of 120-volt, 60 hertz, single phase ac power. Unless a diesel engine is specified, the generator shall be powered by a propane fueled engine. The propane shall be furnished from the tanks specified in 3.5.11(c). When specified (see 6.2), an air-cooled, 4-cycle, diesel engine shall be furnished and shall include a fuel tank with sufficient fuel capacity to provide eight hours of continuous operation with a full generator load. The engine furnished shall include a 12-volt starting battery and an air cleaner. The exhaust system shall conform to Federal Motor Carrier Safety Regulation 393.83(a) and shall incorporate a spark arresting muffler. The muffler shall have an 80 percent arresting efficiency when rated in accordance with SAE J350. The generator shall be vibration isolated and shall be plate mounted. A remote control generator starting panel, located inside the trailer, shall be provided and shall include a start-stop switch, a battery ammeter, a running time meter, and an operating indicator light. The engine-generator set shall be suppressed to limit electromagnetic radiation in accordance with SAE J551.

3.4.7.7.1 Engine-generator compartment. The engine-generator shall be installed in an adequately ventilated, readily accessible compartment. The compartment shall be lined with a three-layer sound absorption barrier. The first and third layers shall be sound absorbent foam and the second layer shall be a transmission-loss barrier.

3.4.8 Landing leg. A retractable landing leg with caster landing wheel shall be provided on the tongue of the trailer, and shall be capable of supporting its portion of the trailer gross weight. The cranking handle shall be permanently installed. With the trailer resting in a level position on level ground, the landing leg and wheel shall be extendable to permit detaching trailer from the towing vehicle.

3.4.8.1 Landing leg supporting ability. With the trailer parked in a level position on level ground, the landing leg assembly shall support the loads imposed throughout the full extension of the landing leg.

3.4.9 Safety chains. Two safety chains shall be furnished. Chains shall conform to Federal Motor Carrier Safety Regulation 393.70(d).

3.4.10 Bumper. A rear bumper shall be furnished and shall conform to Federal Motor Carrier Safety Regulation 393.86.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

* 3.4.11 Stabilizer jacks. Four permanently installed, manually operated stabilizer jacks shall be provided. Two jacks shall be located at the front and two at the rear to permit four point stabilization of the trailer. The fully retracted stabilizer jacks shall not extend more than 89 mm (3.5 inches) below the trailer frame. With the trailer frame horizontal on level ground, the fully extended length of the front stabilizer jacks shall be not less than 25 mm (one inch) below ground level and the fully extended length of the rear stabilizer jacks shall be not less than 75 mm (3 inches) below ground level. A permanently mounted bubble level indicator shall be furnished to determine when the trailer is in a parked level position. The level indicator shall be mounted at the front of the vehicle.

3.4.12 Tools. The vehicle shall be furnished with tools required for exchanging a mounted tire assembly with the spare assembly and shall include at least a hydraulic jack, jack handle, and wheelnut wrench. The jack shall be of such closed height as to permit its location under axle, or other satisfactory lift point, at any wheel with the tire flat. The jack, without blocking shall be capable of raising any wheel of the loaded vehicle to a height adequate to permit removal and replacement of wheel and tire assembly.

3.5 Body. The trailer body shall be of aluminum alloy construction. The arrangement of the longitudinal and vertical wall members, roof supports, door and window opening frames, including the body skin, shall provide a body framework free of distortions when subjected to the operating and performance conditions specified (see 3.2). Design and construction shall be of aircraft, riveted type.

3.5.1 Exterior. The exterior skin shall be of aluminum alloy and shall completely cover the underbody. All exterior joints and seams shall be watertight and weatherproof.

3.5.2 Interior. Interior walls and ceilings shall be of vinyl laminated to aluminum alloy, except that the interior upper end liners may be of molded fiberglass or acrylonitride-butadiene-styrene (ABS) material.

3.5.3 Floor. The floor shall be of not less than 13 mm (0.5 inch) exterior grade marine plywood, covered with inlaid linoleum, vinyl linoleum or tile, or nylon or polyester carpeting.

3.5.4 Windows. Manufacturer's standard windows and screens shall be provided on the sides, front, and rear of the trailer. Windows shall be of tinted, double-pane construction. All joints and seams shall be watertight and weatherproof.

3.5.5 Door. A door opening shall be furnished toward the front on the curb side. The opening shall have a combination door and screen door, hinged separately, or shall have the screen in combination with a window, as part of the door. All joints and seams shall be watertight and weatherproof.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

3.5.6 Steps. Heavy duty, metal, fold-away type steps shall be provided at the entrance.

3.5.7 Insulation. The insulation shall be either fiberglass or foam type. The insulation shall not support combustion; sustain flame, mold or rot; sustain vermin; corrode metals; absorb odors; disintegrate under vibration; or settle and leave voids. Insulation material shall be homogeneous and uniform in density and thermal efficiency. Insulation material shall be capable of flexing more than its containing structure without tendency to crack or rupture. The roof, doors, walls, and floor shall be insulated.

3.5.8 Interior arrangement. The interior arrangement of the trailer shall be such that the bath area shall be in the rear of the trailer and shall be separate from the sleeping, living, and kitchen area. The kitchen area may be arranged along one side and the sleeping area along the opposite side of the trailer. The front portion of the trailer shall be arranged for work and dining.

3.5.9 Interior furnishings. Interior furnishings shall include at least the following:

(a) Kitchen area

(1) Combination gas-electric refrigerator, 170 liters (L) (6 cubic foot) minimum for sizes 21 and 25; 227 liters (8 cubic foot), for sizes 29 and 32; and 227 liters (8 cubic foot) or 283 liters (10 cubic foot) for size 34
(2) Four-burner gas range with oven
(3) Double stainless steel kitchen sinks with hot and cold water, with faucet(s)
(4) Non-powered ceiling vent above range
(5) Kitchen storage cabinets, lower and upper
(6) Electrical receptacle outlet above counter top, 120-volt ac
(7) Electric lights for kitchen area

(b) Bath area

(1) Mirrored cabinet at eye level
(2) Electrical receptacle, l20-volt ac, with ground fault protection
(3) Marine-type flush toilet with water saver feature
(4) Lavatory with hot and cold water, with faucet(s)
(5) Stall shower with hot and cold water, with faucet(s)
(6) Electric exhaust fan
(7) Electric lights for bath area

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

* (c) Bedroom area

(1) One 3/4-size bed for size A, one full size double bed for all other sizes
(2) Wardrobe closets
(3) Storage drawers
(4) Electric lights for sleep area

* (d) Work and dining area

(1) Convertible sofa bed opening to a minimum of a 3/4-size bed
(2) Work desk and file combination with chair
(3) Front lounge or sofa
(4) Drop-leaf table and two folding-type chairs
(5) Built-in telephone jack with mating plug
(6) Electric lights for work and dining area.
(7) Double electrical receptacle, 120-volt ac.

* 3.5.9.1 Special furnishings for size 25 through 34 trailer. Size 25 through 34 trailer shall include the interior furnishings specified in 3.5.9, except a bathtub and shower shall be provided in lieu of the stall shower specified in 3.5.9 (b) (5).

* 3.5.10 Interior furnishing details. Provisions shall be made to fasten any loose furnishings securely in place for traveling.

* 3.5.11 Other equipment. Other equipment shall be furnished as follows:

(a) Pressure water system with 190 L (50-gallon), minimum, storage tank
(b) Electrically operated air compressor or marine pump in pressure water system
(c) Two liquefied petroleum gas (LPG) tanks, each 14 kg (30 pound) minimum capacity, with provisions for securing on trailer hitch frame
(d) Gas water heater, 23 L (6-gallon) minimum
(e) Flexible sewer hose, 3050 mm (10-foot) minimum length, with stowage space
(f) Manufacturer's standard drapes on all windows
(g) Gas space heater, forced-air ducted type with wall thermostat
(h) Ceiling vent(s)
* (i) Liquid waste holding tank, 133 L (35-gallon) minimum
* (j) Body waste holding tank, 114 L (30-gallon) minimum (87 L (23-gallon) for size 21)
* (k) Fire extinguisher, 4.5 kg (10-pound) unit, with visible pressure gage and safety handle discharge conforming to class I, type I, size 10 of A-A-393. The unit shall be mounted in a quick-release type securing device and installed in a readily accessible location

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

* (l) Exterior electrical receptacle, 120-volt ac, with ground fault protection
* (m) Step light.

* 3.5.12 Air conditioning. The manufacturer's standard 120-volt, roof-mounted, recirculating type air conditioner shall be furnished. The system shall be capable of maintaining not more than 27° Celsius (°C) (80°F) dry bulb and 20°C (68°F) wet bulb temperature in a 38°C (100°F) outside ambient temperature under full solar radiation.

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government inspector, contractor shall service and adjust each vehicle for operational use including at least the following: proper adjustment of the brake system, proper functioning of all lighting, inflation and balancing of all tires, and complete lubrication of chassis and running gear with grades of lubricants recommended for the ambient air temperature at the delivery point.

3.7 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the highest standards of the industry.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examination and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.2.1 In-process rain test. The trailer shall be subjected to rain test to determine conformance to 3.5.1, 3.5.4, and 3.5.5. The rain test shall be performed in accordance with MIL-STD-810, Method 506.1, Procedure II, except reorienting the position of the test vehicle is not required. The test shall be performed prior to installation of interior walls and appurtenances.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformity with the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

4.3.1 Vehicle weight. The first production vehicle shall be weighed to determine curb weight and the distribution of curb weight on the lunette or ball hitch and axles. The total imposed loads on the lunette or ball hitch and axles with payload will be calculated to ascertain that the suspension, axles, and tires furnished are of adequate capacity to meet contractual requirements.

4.3.2 Road test. The trailer, coupled to a truck, shall be towed for a distance of not less than 80 kilometers (km) (50 miles), to verify the performance requirements of 3.3. At least 20 percent of this distance shall be over unimproved roads at speeds as great as 41 km/h (25 mph). The other 80 percent of this distance shall be over improved roads at speeds as great as 88 km/h (55 mph). Service brakes of the trailer shall be tested to verify conformance to 3.3.2 and the trailer shall be tested for turning and tracking ability to verify conformance to 3.3.1 and 3.3.3. After tests, the trailer shall be examined for evidence of misalinement, binding, or other malfunction.

4.3.3 Electrical test. An electrical test shall be conducted on the first production vehicle to determine that all vehicle lights and the electric brakes are functioning. In addition, when a 24-volt receptacle system is furnished (see 3.4.7.5) the circuits of the 12-contact receptacle shall be energized with 28-volt dc regulated voltage for a time sufficient to stabilize the temperature of the resistor assembly for not less than 15 minutes in an ambient temperature of not less than

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

25°C (77°F). After the test, the resistor assembly, including resistors, wiring, and adjacent components, shall be examined for evidence of overheating, deterioration, or damage.

4.3.4 Water system test. A hydrostatic test shall be applied to the in-place water supply system and water heater. This hydrostatic test will be deemed successful if pump pressure can be maintained on the system for 15 minutes with no evidence of leakage and no addition of air or water to maintain the pressure. Upon completion of test, lines and equipment shall be drained.

4.3.5 Production sample. Upon acceptance of the first production vehicle, it shall remain at the manufacturing facility as a production sample and shall be the last trailer shipped on the contract. The contractor shall maintain the trailer in a serviceable condition for the duration of the contract.

4.3.6 Failure. Failure of the first production vehicle to meet requirements of the contract shall be cause for the Government to refuse acceptance of all vehicles under contract until corrective action has been taken.

4.4 Inspection of production vehicles. The contractor's inspection system shall, as a minimum, assure that each vehicle conforms to the physical and dimensional requirements and is capable of meeting the performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 has been accomplished.

5. PACKAGING

5.1 Vehicle processing. The trailer shall be processed for shipment, from the manufacturer's plant to initial receiving activity, in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. Trailers covered by this specification are intended for general administrative use by the Government as mobile living quarters for personnel.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size of vehicle required (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.

* (c) Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
* (d) Identification of appropriate military service for painting (see 3.1.1.1).
* (e) Identification of appropriate military service for marking (see 3.1.1.2).
* (f) Concealed marking, if required (see 3.1.1.2).
(g) Rustproofing, if required (see 3.1.1.3).
(h) Military standard lunette, if required in lieu of ball hitch (see 3.1.1.4).
(i) Blackout curtains, if required (see 3.1.1.5).
(j) Disc type wheels, if required (see 3.4.5).
(k) Electric brake synchronizing controller for use with air brake equipped towing vehicle, if required (see 3.4.6.1).
(l) A 24-volt receptacle system, if required (see 3.4.7.5).
* (m) Diesel powered generator, in lieu of propane powered, if required (see 3.4.7.7).

* 6.3 Subject term (key word) listing.

Air conditioning
Black-out provisions
Hitch assembly
Landing leg
Lavatory
Resistor assembly
Stabilizer jack
Turning ability.

6.4 Identification of changes. The margins of this document are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, regardless of the marginal notations and relationship to the previous issue.

Custodian:
Army - AT

Preparing Activity:
Army - AT

Project No. 2330-A122

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:53Z
Check the source to verify that this is the current version before use.