MILITARY SPECIFICATION SHEET

BUR, SURGICAL, TUNGSTEN CARBIDE, 1.7 MM BY 12 MM HEAD, SIDE CUTTING, TAPERED (SHAPE C), LONG SHANK (LENGTH 3)

The complete requirements for acquiring the bur described herein shall consist of this specification sheet and the latest isssue of MIL-B-37959(DM).

REQUIREMENTS

Shall be a side cutting, tapered shape, long shank surgical buffing bur for use with the long bur guard in National Stock Number (NSN) 6515-01-116-8197 DRILL, BONE, PNEUMATIC.

Shall be a one-piece bur made of C2 grade tungsten carbide, hot isostatically pressed, with a grain size of 1 to 2 microns.

Shall be examined at 30X magnification for bur defects not readily perceptible to the naked eye.

Shall not break when 4 pounds force is applied transversely at tip with the bur supported at and to the rear of the safeline.

Shall be of the design and dimensions shown in figure 1 (7746).

This specification sheet covers the following NSN: 6515-01-139-7746.

Agent:
DLA-DM

Preparing Activity:
DoD-MB

(Project No. 6515-3017P)

FSC 6515

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:44Z
Check the source to verify that this is the current version before use.




FIGURE 1 (7746)

FIGURE 1 (7746). Bur, surgical, tungsten carbide, 1.7 mm by 12 mm head, shape C, length 3.

Source: https://assist.dla.mil -- Downloaded: 202610-21T11:44Z
Check the source to verify that this is the current version before use.