NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

FED. SUP. CLASS.

AUTOMATIC BATTERY CHARGER AND TESTER

1. This standard covers a battery charger and tester unit for servicing aircraft batteries, types MS-25210 (MS-25218) and MS-25211 (MS-25217).

2. The unit shall be fully automatic and shall consist of:

   (A) Charger: Which automatically limits current to 25 amperes plus or minus 10% (except initial surge) with adjustable automatic voltage limiting to 29.0 volts plus or minus 0.5 volts, with stepless static control, utilising no tubes or lamps.

   (B) Tester: A discharge unit with two position selector switch to give 17 amperes and 10 amperes at 22 volts.

   (C) Automatic Program Control: Charging and testing shall be automatically programmed as follows:

      (1) Discharge rate manually selected.

      (2) On-off switch turned on starting charger and timer.

         (a) Starting current limited to 25 amperes and will gradually taper to end value of 3 ± 1 amperes.

         (b) When current tapers to 3 ± 1 amperes charging is automatically discontinued, and the preselected discharge resistor is connected across the battery.

         (c) Discharge will be limited to two hours or until battery voltage drops to 19.0 volts $\pm$ 0.2 volts.

         (d) If voltage drops to 19.0 volts, unit will shut off and indicate battery failure.

         (e) If voltage does not drop to 19.0 volts within two hours, the battery will automatically go on charge and within three hours fully recharge the battery.

3. Housing. - The entire unit shall be enclosed in a single housing, essentially rectangular with approximate dimensions of 12" sides x 20" front x 20" height and a maximum weight of not more than 90 pounds, and maximum cubic content of 5,000 cu. in.

4. Controls and Indicators. - The unit shall be provided with indicators which will show condition of operation such that acceptance or rejection indicator will remain on until manually turned off. A "on-off" switch and discharge "selector" switch shall be provided, also a D.C. Ammeter and D.C. Voltmeter with scales of 0-30 and with an accuracy of 2%.

5. Input. - 115 volts plus or minus 10% single phase 60 c.p.s.

6. Output Cables and Connector. - 4 ft. output flexible cables (rubber coated - or equivalent) terminating in a MS-25182 connector. Unit shall also be equipped with sensing leads.

7. Following paragraphs of MIL-C-19454 not applicable:

   3.1, 3.4.7, 3.4.8, 3.4.13, 3.4.14, 3.4.15, 3.4.17, and following sub-paragraphs of 3.8: (a), (c), (f), (g), (h), (i), (m), (o).

8. Changes to applicable paragraphs of MIL-C-19454:

   (a) Paragraph 3.3.1 change (-55° to 65°C) to (15° to 50°C) for operating temperature, storage temperature range remains -55° to 65°C.

   (b) Paragraph 3.4.10 change 5/16" to 1/2".

APPROVED 11/9/57 REVISED

CUSTODIANS	OTHER INT.	MILITARY STANDARD	MS25278 (AER)
Navy - BuAer	A - N - AF -	AUTOMATIC BATTERY CHARGER AND TESTER	
PROCUREMENT SPECIFICATION MIL-C-19454		SUPERSEDES:	SHEET 1 OF 1

DD FORM 672-1
1 OCT 52

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:07Z
Check the source to verify that this is the current version before use.