



FED SUP CLASS
6140




OPTIONAL CONSTRUCTION









FOUR CELL UNIT — ELECTROLYTE - SULPHURIC ACID — THREE CELL UNIT

CHARGED AND DRY DASH NO	CHARGED AND DRY FIIN	CHARGED AND WET DASH NO	CHARGED AND WET FIIN	MFR SYM	MFR'S DESIGNATION	NOM VOLTS	NO OF PLS POS	NO OF CELLS	AMP HR CAP AT 8 HR RATE	WT IN LBS (APPROX) UNFILLED	WT IN LBS (APPROX) FILLED	MAX OVERALL DIMS PER UNIT L LENGTH	W WIDTH	H HEIGHT
-1		-2			7D /2	6	25	3	200 /2	67	85	16-7/8	7-5/8	10-7/8
-3		-4		CD	4MHD-9		9		76 TO 84	72	89	16-9/16	7-1/2	11
				ES	4KX-9A									
				GB	4CCMX-9R									
-5		-6		CD	4MHD-13		13		114 TO 126	116	136	22-11/16	7-1/2	11
				ES	4KX-13A									
				GB	4CCMX-13R									
-7		-8		CD	4CXSD-13		13		213 TO 220	157	204 /4	23-1/4	8-1/4	18-3/16
				ES	4MV-13D									
				GB	4KDZ-13R /5									
-9		-10		CD	4MHD-15		15		133 TO 147	140	160	25-11/16	7-1/2	11
				ES	4KX-15A									
				GB	4CCMX-15R									
-11		-12		CD	4MHD-17	8					184	28-3/4	7-1/2	11
				ES	4KX-17A									
				GB	4CCMX-17R									
-13		-14		CD	4CXSD						280 /4	28-1/8	8-5/8	17-5/8
				ES										
-15		-16							TO 189	182	216	28-1/8	8-7/16	11-3/8
-17		-18			4CCMX-21R /5		21		190 TO 210	203	235	28-1/8	10	11-3/8
-19		-20		CD	4MHD-23		23		209 TO 231	225	260	28-1/8	10	11-3/8
				ES	4KX-23A									
				GB	4CCMX-23R									
-21		-22		CD	4CXSD-25 /5		25		426 TO 440	300	400 /4	28-7/16	11-5/8	17-7/8
				ES	4MV-25D /5									
				GB	4KDZ-25E /5									

CANCELED AFTER 1 July 1982
NO SUPERSEDING STANDARD

NOTES:
1- MATERIALS AND DETAILS OF CONSTRUCTION ARE TO BE IN ACCORDANCE WITH MANUFACTURER'S COMMERCIAL PRACTICE
2- SAE TYPE DESIGNATION, IN ACCORDANCE WITH SPECIFICATION W-B-131. AMPERE HOUR CAPACITY AT 20 HOUR RATE.
3- DIMENSIONS IN INCHES.
4- THESE BATTERIES TO HAVE FULL CHARGE SPECIFIC GRAVITY OF 1.250, ALL OTHERS 1.280.
5- COPPER INSERTS IN TERMINAL POSTS AND INTERCELL CONNECTORS.
6- MFR'S SYMBOLS: CD - C & D BATTERIES INC. CONSHOHOCKEN, PA. - OR EQUAL
ES - ELECTRIC STORAGE BATTERY CO., 15 TH & CHESTNUT STS. PHILA. 2, PA. - OR EQUAL
GB - GOULD - NATIONAL BATTERIES INC., 467 CALHOUN ST., TRENTON, N.J. - OR EQUAL
7- INTENDED FOR ENGINE CRANKING, PARTIAL CYCLE SERVICE, STANDBY AND GENERAL SERVICES AS REQUIRED BY APPLICATION. BATTERIES ARE ARRANGED IN MULTIPLES TO OBTAIN REQUIRED VOLTAGE AND CAPACITY.
8- FEDERAL SUPPLY SERVICE, GENERAL SCHEDULE.
9- REFERENCE DOCUMENTS SHALL BE ISSUES IN EFFECT ON DATE OF INVITATION FOR BIDS.
10- THE MS PART NUMBER CONSISTS OF THE MS NUMBER PLUS THE DASH NUMBER. EXAMPLE MS35005-1

APPROVED 16 MARCH 1955 REVISED Ⓐ 1 JULY 1982

CUSTODIANS	OTHER INT.
ORD	A-SEA TE
DOCKS	N-AS MC
USAF	AF-USAF

PROCUREMENT SPECIFICATION: SEE NOTE 8

SUPERSEDES:

MILITARY STANDARD
BATTERY, STORAGE
INDUSTRIAL, LOCOMOTIVE AND MARINE

MS35005

SHEET 1 OF 1

DD FORM 1000 OCT 65 672-1

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:08Z
Check the source to verify that this is the current version before use.