
Reviewer/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS (FSC listing).
Navy MC9 YD+
Army EL+
AF 82+

FED. SUP CLASS
5975



DASH NO.	A	B	C	D	E	F	G
-1	2 1/16	.120	1/4	1 3/8	3/4	1/2	.120
-2	2 1/4	.135	1/2	1 7/16	1 1/8	5/8	.165
-3	2 9/16	.177	5/8	1 1/2	2 1/16	7/8	.165

NOTES:

1. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
2. THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
3. RING SHALL BE MADE FROM WIRE COMPLYING WITH FEDERAL SPECIFICATION QQ-W-409.
4. RING SHALL BE HOT DIP GALVANIZED IN ACCORDANCE WITH MILITARY SPECIFICATION MIL-Z-17871.

This military standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 18 JULY 58 REVISED (A) 10 May 1968

ALL DIMENSIONS IN INCHES

P.A. / Other Cust	TITLE	MILITARY STANDARD
EL / YD / 82	DRIVE RING (POLE LINE)	MS39045
PROCUREMENT SPECIFICATION MIL-H-55053	SUPERSEDES:	SHEET 1 OF 1

5975-0283

DD FORM 10 APR 64 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:45Z
Check the source to verify that this is the current version before use.