MIL-A-14730A (MU)
2 January 1969
SUPERSEDING
MIL-A-14730 (MU)
29 March 1968

MILITARY SPECIFICATION

ADAPTER-BOOSTER, BOMB, TAIL, M149
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the quality assurance provisions, and special requirements not covered by the drawings, for the loading, assembling and packing of one type of adapter-booster designated as Adapter-Booster, Bomb, Tail, M149.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-D-1000 - Drawings, Engineering and Associated Lists.
MIL-A-2550 - Ammunition and Special Weapons, General Specification for.
MIL-C-45662 - Calibration of Standards.
MIL-P-46464 - Pellets, Tetryl.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109 - Quality Assurance Terms and Definitions.

FSC: 1325

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

MIL-STD-1167 - Ammunition Data Cards.
MIL-STD-1168 - Lot Numbering of Ammunition.
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

9210873 - Container, Fiber, Amm., M342A1, for Adapter-Booster, Bomb, Tail, M147 or M149
9210874 - Box, Packing, Amm., for Adapter-Booster, Bomb, Tail, M147 or M149
9217288 - Adapter-Booster, Bomb, Tail, M149, Loading Assembly

AIR FORCE

1325-935-2070 - Adapter-Booster, Bomb, Tail, M149

PUBLICATIONS

ET-9217288 - Equipment Tabulation.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Materials.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Loaded assemblies.-The loaded assemblies shall comply with all requirements specified on Drawing (dwg.) 9217288 and with all requirements specified in applicable specifications.

3.3 Static functioning.-The adapter-booster, minus the booster cup assembly and the shock absorber, shall function high order immediately after temperature conditioning at minus 65 degrees,

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

plus or minus 5 degrees, Fahrenheit (F) when 11 foot pounds of energy is applied to the firing pin of a modified M905 fuze. The item shall be considered to have detonated high order when a .250 inch, or greater, depression has been formed in a 5 inch by 5 inch by 1 inch mild steel plate. The test shall be performed as specified in 4.3.2 (see 6.4).

3.4 Sealing of barrier bag.-When the barrier bag is required, all included air shall be removed prior to sealing.

3.5 Workmanship.-Loading and assembly shall be accomplished in a thorough, workmanlike manner. The assemblies, as they progress, shall be free of dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few slight scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection provisions.

4.2.1 Lot formation.-The term "lot" as used throughout this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing not affecting safety, performance, interchangeablity, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraphs of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspection listed shall be in accordance with 4.2.4.

4.2.2.1 Assembly, lead cup, prior to assembly to lead cup spacer (see dwg. 9217288).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Depth to charge	Gage	01001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	01002

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

4.2.2.2 Lead cup spacer assembly (see dwg. 9217288-1).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Lead cup missing	Visual	02001
102.	Cement on either end of lead cup	Visual	02002
Minor:	AQL 1.00 percent		
201.	Cement missing from periphery of lead cup	Visual	02003
202.	Evidence of poor workmanship (see 3.5)	Visual	02004

4.2.2.3 Booster casing assembly, prior to assembly of lead cup spacer (see dwg. 9217288-1).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Pellet missing	Visual	03001
102.	Disc missing	Visual-Manual	03002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	03003

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

4.2.2.4 Booster casing assembly (see dwg. 9217288-1).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Distance end to lead cup spacer, minimum	Gage	04001
102.	Pellet loose	Manual	04002
103.	Cement missing from thread (360 degrees), when applicable.	Visual	04003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	04004

4.2.2.5 Adapter-booster casing assembly (see dwg. 9217288-1).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Hole in adapter assembly missing or not aligned	Visual	05001
102.	Thread damaged to extent assembly may be affected	Visual	05002
103.	Cement on thread not visible (360 degrees), when applicable.	Visual	05003
Minor:	AQL 2.50 percent		
201.	Shock absorber insecure	Manual	05004
202.	Protective coating damaged	Visual	05005
203.	Marking missing, misleading or unidentifiable	Visual	05006
204.	Closing plug missing	Visual	05007
205.	Evidence of poor workmanship (see 3.5)	Visual	05008

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

4.2.2.6 Adapter-booster casing assembly, prior to assembly of booster casing assembly. (see dwg. 9217288-2).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Lead cup assembly missing.....	Visual	06001
102.	Pellet missing.....	Visual	06002
103.	Cement missing on thread of booster casing.....	Visual	06003
104.	Cement on either end of lead cup.....	Visual	06004
105.	Disc missing.....	Visual-Manual	06005
Minor:	AQL 1.00 percent		
201.	Cement missing from periphery of lead cup.....	Visual	06006
202.	Evidence of poor workmanship (see 3.5).....	Visual	06007

4.2.2.7 Adapter-booster casing assembly (see dwg. 9217288-2).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Gap excessive at booster casing.....	Gage	07001
102.	Pellet loose.....	Manual	07002
103.	Hole in adapter assembly missing or not aligned.....	Visual	07003
104.	Thread damaged to extent assembly may be affected.....	Visual	07004

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

Minor:	AQL 2.50 percent		
201.	Shock absorber insecure.....	Manual	07005
202.	Protective coating damaged.....	Visual	07006
203.	Marking missing, misleading or unidentifiable.....	Visual	07007
204.	Closing plug missing.....	Visual	07008
205.	Evidence of poor workmanship (see 3.5).....	Visual	07009

4.2.2.8 Booster cup assembly (see dwg. 9217288-1 and -2).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Pellet loose.....	Manual	08001
102.	Closing disc damaged.....	Visual	08002
103.	Closing disc seal missing.....	Visual	08003
Minor:	AQL 1.00 percent		
201.	Marking missing, misleading or unidentifiable.....	Visual	08004
202.	Evidence of poor workmanship (see 3.5).....	Visual	08005

4.2.2.9 Fiber container, prior to closing (see dwg. 9210873).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Fillers missing under booster..	Visual	09001
Minor:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

4.2.2.10 Fiber container, sealed (see dwg. 9210873).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Contents loose	Manual	10001
102.	Tape incomplete or badly wrinkled	Visual	10002
103.	Cuts, scuffs, gouges or checks which penetrate outer layer	Visual	10003
104.	Metal end loose or distorted	Visual-Manual	10004
Minor:	AQL 1.50 percent		
201.	Gap between body and cover in excess of 1/8 inch	Gage	10005
202.	Tear tab missing	Visual	10006
203.	Marking missing, misleading or unidentifiable	Visual	10007

4.2.2.11 Wood packing box (see dwg. 9210874).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Contents of box exposed	Visual	11001
102.	FSN number missing or misleading	Visual	11002
103.	Board broken	Visual	11003
104.	Hardware missing, broken or loose	Visual-Manual	11004
105.	Strapping missing, broken or loose	Visual-Manual	11005

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.50 percent		
201.	Marking missing, misleading or unidentifiable	Visual	11006
202.	Hardware improperly engaged	Visual	11007
203.	Car seal missing, unsealed or improperly positioned	Visual	11008

4.2.2.12 Insert, prior to closing (see dwg. 1325-935-2070), when applicable.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Unit missing	Visual	12001
Minor:	None defined.		

4.2.2.13 Barrier bag, (see dwg. 1325-935-2070), when applicable.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Included air not removed (see 3.4)	Visual	13001
102.	Seal missing or inadequate	Visual	13002
Minor:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

4.2.2.14 Wood packing box (see dwg. 1325-935-2070), when applicable.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Contents of box exposed	Visual	14001
102.	FSN number missing or misleading	Visual	14002
103.	Board broken	Visual	14003
104.	Strapping missing, broken or loose	Visual-Manual	14004
Minor:	AQL 0.65 percent		
201.	Marking missing, misleading or unidentifiable	Visual	14005

4.2.3 Testing

4.2.3.1 Booster pellets (see dwg. 8797333 or 9210421, as applicable) - Major defect - Code No. 15001 and 15002, respectively.-A sample shall be selected and be inspected and tested in accordance with Specification MIL-P-46464.

4.2.3.2 Lead charge preformed pellet. (see dwg. 9217288) Major defect Code No. 16001.-A sample of 20 units shall be selected from each lot for this determination which shall be performed as specified in 4.3.1.1. If one or more units fail in meeting the requirement, the lot shall be rejected.

4.2.3.3 Specific gravity of lead cup charge (see dwg. 9217288) Major defect - Code No. 16002.-A sample of 20 units shall be selected from each lot for this determination which shall be performed as specified in 4.3.1.2. If one or more units of the sample fails in meeting the requirement, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

4.2.3.4 Static functioning (see 3.3) - Major defect - Code No. 17001.-A sample of 24 units shall be selected from each lot for this test which shall be performed using the applicable equipment of 4.2.4 as specified in 4.3.2. Failure of two or more units in meeting the requirement shall reject the lot. If only one unit fails, a second sample of 24 additional units shall be selected and tested. Failure of one or more units of the second sample shall finally reject the lot. In the event a failure is caused by fuze failure, another test sample may be assembled, conditioned and tested.

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-9217288 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Calibration.-The contractor shall have available a set of master gages, standards and appropriate instruments for regularly scheduled calibrations of his acceptance inspection equipment. Records of such regularly scheduled calibrations shall be maintained by the contractor and made available for review by the Government. The calibration of gages, standards and instruments shall be in accordance with Specification MIL-C-45662.

4.3 Test methods and procedures.-The test method and procedures described in each of the following tests represents only one method and one procedure which has been proven in use and is approved by the Government for Government acceptance purposes. Producers and manufacturers have the option of using substitute methods and procedures only after obtaining Government approval. Government

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

approval will be based on an evaluation to determine that the substitute method and procedure will result in an equal or better quality evaluation than that specified herein.

4.3.1 Specific gravity

4.3.1.1 Preformed pellets.-The specific gravity of the lead charge preformed pellet shall be determined using the following formula:

$$\text{Specific gravity} = \frac{W}{12.8727\ D^2\ h}$$

W = weight of pellet in grams
D = diameter of pellet in inches
h = length of pellet in inches

To assure the accuracy of the above formula, it shall be necessary that diameter (D) and length (h) of the pellet be measured to the nearest one thousandth of an inch on a Dial Bench Comparator. In addition, pellets containing chips or broken edges shall not be used for this determination.

4.3.1.2 Lead charge as pressed in lead cup.-The specific gravity of the lead cup charge shall be determined as follows:

a. The loaded lead cup shall be weighed in air and the weight shall be recorded as A.

b. It shall then be weighed suspended in water at a temperature of 25°C, and the weight shall be recorded as B.

c. The difference in weight of the loaded lead cup shall be determined by subtracting B from A, (A-B) and the result recorded as C.

d. The tetryl composition shall be removed from the lead cup by washing it with acetone.

e. The empty lead cup shall be weighed in air and the weight shall be recorded as D.

f. The empty lead cup shall be weighed suspended in water at 25°C, and the weight shall be recorded as E.

g. The difference in weight of the empty lead cup shall be determined by subtracting E from D, (D-E) and the result recorded as F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

h. The weight of the tetryl composition shall be determined by subtracting the weight of the empty lead cup in air (D) from the loaded lead cup in air (A), and the weight shall be recorded as G, (A-D=G).

i. The specific gravity shall be determined as follows:

$$\text{Specific gravity} = \frac{GK}{(C-F)}$$

G = the weight of tetryl composition
K = specific gravity of water at $25^{\circ}/25^{\circ}C$
C = difference in weight of loaded lead cup
F = difference in weight of empty lead cup

4.3.2 Static functioning.-The M905 fuze shall be prepared for test by straightening the bent tabs of the housing assembly (the top of the fuze) and removing that assembly and the internal gear. They shall be discarded. The firing pin assembly and spring shall then be removed and retained. The fuze shall then be armed by turning the firing pin guide (the black coated component at the bottom of the cavity) in the clockwise direction until the shear pin of the rotor release assembly is severed and the rotor moves to the armed position (the red coated part of the rotor visible through the viewing window). A loaded M9 non-delay delay element shall then be inserted into and locked in the delay cavity by depressing the delay lock pin, properly positioning the element and releasing the pin. The fuze shall then be assembled into a loaded adapter-booster, less fuze adapter.

The test assembly shall then be temperature conditioned at the required temperature for 5 hours, minimum.

The firing pin assembly and spring shall be re-assembled and the assembly shall then be properly positioned in the applicable test equipment and functioned. Any assembly not meeting the requirement shall be classed defective.

NOTE: This test is very dangerous and must be performed behind a barricade. It is suggested a safety feature that will prevent premature detonation and not affect function be added to the M905 fuze firing pin for the protection of test personnel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging and marking

5.1.1 Level A.-The adapter-booster assemblies shall be packaged and marked in accordance with dwg. 9210873 or 1325-935-2070, as applicable.

5.2 Packing and marking

5.2.1 Level A.-The packaged assemblies shall be packed and marked in accordance with dwg. 9210874 or 1325-935-2070, as applicable.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. They should also be cited as references on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced inspection Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.

employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit one copy of final designs as a rolled set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable 5 digit Code Number contained in section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-NDll. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract: submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Government furnished items.-The procuring activity shall furnish sufficient quantities of loaded M9 non-delay delays and M905 fuzes for the performance of the tests. Each item shall be from accepted lots.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1325-A-338

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:38Z
Check the source to verify that this is the current version before use.