MILITARY SPECIFICATION

CARTRIDGE, 105MM: APERS-T, XM494E3 FOR 105MM GUN M68 LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of cartridge designated as Cartridge, 105MM: APERS-T, XM494E3.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspections by Attributes

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 202640-18T04:40Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

9204453 - Container, Ammo., Fiber, M563, for Cartridge, 105MM; APERS-T, XM494E3 for Gun M68
9204454 - Box, Packing, Ammunition, for Cartridge, 105MM, APERS-T, XM494E3 for Gun M68, in Fiber Container, M563
9229962 - Cartridge, 105MM, APERS-T, XM494E3
9229964 - Projectile, 105MM, XM603E1 Loading Assembly

PUBLICATIONS

ARMY

ET-9229962 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials ad parts shall be in accordance with applicable drawings and specifications.

3.2 Cartridges.-The cartridges shall comply with all requirements specified on Drawing (dwg.) 9229962 and with all requirements specified in applicable specifications.

3.3 Propellant weight.-The weight of the propellant shall not differ by more than plus or minus 0.25 ounce avoirdupois from that designated by the loading authorization for the particular lot of propellant used.

3.4 Proving ground.-The cartridge shall comply with the following requirements when tested as specified in 4.3.5.

3.4.1 Functioning.-The projectile shall exhibit satisfactory first function a minimum of 270 meters from the muzzle of the weapon and shall exhibit a satisfactory second function.

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:40Z
Check the source to verify that this is the current version before use.

3.4.2 Muzzle velocity.-The corrected muzzle velocity of the cartridge, when tested at ambient temperature, shall not be more than 2730 feet per second (f.p.s.) nor less than 2670 f.p.s. and the standard deviation shall not exceed 10.9 f.p.s.

3.4.3 Tracer functioning.-The tracer shall ignite and there shall be visible evidence of burning of the tracer composition to the point of fuze function.

3.4.4 Dye marker.-The functioning point of the projectile shall be clearly observable from the gun position by satisfactory dispersion of the dye marker.

3.4.5 Security.-There shall be no indication of metal parts separation in the gun bore or in flight prior to fuze functioning.

3.5 Workmanship

3.5.1 All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. All parts shall be free of chips, dirt, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

3.5.2 The painting and marking shall be restored by the assembling contractor on any components furnished to him painted and marked, when such painting and markings have been marred or obliterated.

3.5.3 Rotating bands.-Care shall be exercised at all times so that the rotating bands of the projectile are not nicked, burred or otherwise damaged.

3.5.4 Adhesive on threads.-Threads shall be clean and free of contaminant prior to the application of an adequate amount of thread adhesive. An adequate amount of adhesive consists of a quantity of adhesive present on the unengaged thread sufficient to cover at least 80 percent of the threaded surfaces after they are fully engaged and then disengaged as indicated by visual inspection (see 4.3.4).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection Provisions

4.2.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer in one unchanged process, in accordance with the same drawings, same drawing

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:40Z
Check the source to verify that this is the current version before use.

revisions, same specifications and same specification revisions. Changes to the process, specification, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots of components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot shall contain:

a. Projectile metal parts of one lot interfix number from one manufacturer.

b. Cartridge cases of one type of metal from one manufacturer in accordance with the same drawing revision, same specification and specification revision.

c. Propellant from not more than one lot.

d. Loaded fuzes of one lot interfix number from one manufacturer.

e. Loaded primers of one lot interfix number from one manufacturer.

f. Loaded relays of one lot interfix number from one manufacturer.

g. Loaded detonators of one lot interfix number from one manufacturer.

h. Loaded tracers of one lot interfix number from one manufacturer.

4.2.2 Examination.-Inspection for Critical defects (and Major defects, when so specified), shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 202640-18T04:40Z
Check the source to verify that this is the current version before use.

4.2.2.1 Relay and detonator assembly (see dwg. 9230474 covering a detail of dwg. 9229964).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	100 percent inspection		
101.	Detonator or relay improperly assembled	Visual	01001
Major:	AQL 0.40 percent		
102.	Contents loose	Visual-Manual	01002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	01003

4.2.2.2 Fuze adapter loading assembly (see dwg. 9229971 covering a detail of dwg. 9229964).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	100 percent inspection		
101.	Relay and detonator assembly missing	Visual	02001
Minor:	AQL 0.65 percent		
201.	Distance from shoulder to base of detonator housing, maximum, (max.)	Gage	02002

4.2.2.3 Projectile and fuze adapter assembly prior to assembling (see dwg. 9229964).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:40Z
Check the source to verify that this is the currenversion before use.

Major:	100 percent inspection		
101.	Detonator improperly assembled	Visual	03001
102.	Adhesive on detonator face.	Visual	03002
103.	Adhesive on fuze adapter thread inadequate (prior to assembling) (see 3.5.4) ...	Visual	03003

Minor: None defined.

4.2.2.4 Ejection charge loading assembly (see dwg. 9230008 covering a detail of dwg. 9229964).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Propellant weight incorrect	Scale	04001
102.	Bag torn or open in heat seal	Visual-Manual	04002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	04003

4.2.2.5 Projectile after installation of ejection charge loading assembly (see dwg. 9229964).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	100 percent inspection		
101.	Ejection charge loading assembly missing or improperly positioned	Visual	05001
Major:	AQL 0.40 percent		
102.	Any component including protective paper missing ..	Visual	05002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	05003

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:40Z
Check the source to verify that this is the current version before use.

4.2.2.6 Projectile prior to assembling plus and disc assembly (see dwg. 9229964).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Tracer missing or inverted.	Visual	06001
Minor: None defined.			

4.2.2.7 Projectile loading assembly (see dwg. 9229964).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	100 percent inspection		
101.	Adhesive on rear body threads inadequate (prior to assembling) (see 3.5.4).	Visual	07001
Minor:	AQL 1.0 percent		
201.	Marking missing, misleading or unidentifiable	Visual	07002
202.	Evidence of poor workmanship (see 3.5)	Visual	07003

4.2.2.8 Loaded primer prior to assembling to cartridge case (see dwg. 8847424 covering a detail of dwg. 9229962).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	One or more flash holes missing	Visual	08001
Major: None defined.			
Minor: None defined.			

4.2.2.9 Cartridge case prior to insertion of projectile (see dwg. 9229962)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			

Source: https://assist.dla.mil -- Downloaded: 202640-18T04:40Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Foil disc missing	Visual	09001

Minor: None defined.

4.2.2.10 Cartridge (see dwg. 9229962).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	100 percent inspection		
101.	Primer above flush	Gage	10001
Major:	AQL 0.40 percent		
102.	Distance from case lip to rotating band	Gage	10002
103.	Primer not staked	Visual	10003
Minor:	AQL 1.5 percent		
201.	Marking missing, misleading or unidentifiable	Visual	10004
202.	Projectile protective coating with total damaged area in excess of 1/4 square inch	Visual	10005
203.	Evidence of poor workmanship (see 3.5)	Visual	10006

4.2.2.11 Unsealed fiber container (see dwg. 9204453).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Any packing component missing or improperly assembled	Visual	11001
Minor:	AQL 1.5 percent		
201.	Cartridge cannot be removed by hand	Manual	11002
202.	Container cap cannot be removed by hand	Manual	11003

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

203.	Glue or asphalt on cartridge	Visual	11004

4.2.2.12 Sealed fiber container before placing in barrier bag (see dwg. 9204453).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Sealing tape incomplete	Visual	12001
102.	Container cut or damaged through all impregnated layers	Visual	12002
103.	Metal end loose or distorted	Visual-Manual	12003
Minor:	AQL 2.5 percent		
201.	Sealing tape tab length, min.	Gage	12004
202.	Contents loose	Manual	12005
203.	Gap between cover and body of container exceeds 1/8 inch	Gage	12006
204.	Cuts, scuffs or gouges in outer layers	Visual	12007
205.	Marking misleading or unidentifiable	Visual	12008

4.2.2.13 Wood packing box (see dwg. 9204454).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Barrier bag missing or torn on fiber container (prior to placing in box)	Visual	13001
102.	Box damaged exposing contents	Visual	13002
103.	Hardware or strapping missing, broken or loose ...	Visual-Manual	13003
104.	DOD symbol missing	Visual	13004

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:40Z
Check the source to verify that this is the currentversion before use.

Minor:	AQL 2.5 percent		
201.	Protective bag missing (prior to closing box) ...	Visual	13005
202.	Strapping or hardware improperly assembled	Visual-Manual	13006
203.	Handle missing or insecure	Visual-Manual	13007
204.	Car seal missing, unsealed or improperly positioned .	Visual-Manual	13008
205.	Marking misleading or unidentifiable	Visual	13009

4.2.3 Testing

4.2.3.1 Check test for deterioration of primer and detonator (see applicable primer and detonator specification) - Major defect - Code No. 08002.-If the total elapsed time between the original acceptance of any primer or detonator lot and the assembly of that lot into cartridges exceeds two years, or if the primer or detonator have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass, the check test for deterioration specified in the applicable loading specification immediately before the primers are assembled into the cartridges. The test shall be performed by the contractor on assemblies selected by the Government inspector at the facility assembling the complete cartridges (see 6.4).

4.2.3.2 Torque (see Drawing 9229964).

	Defect	Code No.
Projectile Body	Major	07004
Fuze adapter	Major	07005
Fuze	Major	07006
Plug & disc assembly	Major	07007

After the adhesive has set, twenty projectiles shall be randomly selected for this test. If any projectile fails to withstand the torque when tested in accordance with 4.3.1, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

4.2.3.3 Electrical resistance (see dwg. 9229962) - Major defect - Code No. 09002.-The cartridge cases with primers assembled shall be tested 100 percent for resistance of the primer circuit. Any case-primer assembly which fails to meet the requirement specified shall be classed defective and rejected. Testing shall be as specified in 4.3.2 using equipment in accordance with 4.2.4.

4.2.3.4 Propellant weight (see 3.3) - Major defect - Code No. 10007.-The propellant for each charge shall be weighed, identified, and check-weighed 100 percent. The check-weighing shall be accomplished independently of the original weighing using a different balance from that used to make the original weighing and, if performed manually, shall be performed by another operator. Any propelling charge which fails to comply with the applicable requirement shall be classed defective and shall be returned for correction and reweighing. Equipment shall be in accordance with 4.2.4.

4.2.3.5 Profile and alignment (see dwg. 9229962) - Major defect - Code No. 10008.-The cartridges shall be gaged 100 percent for profile and alignment. Any cartridge which fails to meet the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.6 Bullet pull (see dwg.9229962) - Major defect - Code No. 10009.-The sampling plan for this test shall be in accordance with Standard MIL-STD-414. Section B, Part II, Table B3, Code letter F and an AQL of 1.5 percent shall be used. The test shall be in accordance with 4.3.3.

4.2.3.7 Proving ground

4.2.3.7.1 For all lots produced a sample of 10 cartridges shall be randomly selected and tested in accordance with 4.3.5 to demonstrate compliance with the requirements of 3.4.

4.2.3.7.1.1 Lot rejection shall be in accordance with the criteria specified in the individual paragraphs below.

4.2.3.7.2 Rejection.-Functioning - Major defect - Code No. 14001.-If two or more cartridges fail to comply with the requirements of 3.4.1, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

4.2.3.7.3 Rejection.-Muzzle velocity - Major defect - Code No. 14002.-If the estimated percentage of cartridges have muzzle velocities falling outside the required limits based on MIL-STD-414, Section B, Part II, Table B-3, Code letter F exceeds that allowed by an AQL of 2.5 percent the lot shall be rejected. In addition, if the standard deviation of the sample cartridge muzzle velocities multiplied by the factor 0.65 exceeds the applicable requirement, the lot shall be rejected.

4.2.3.7.4 Rejection.-Tracer functioning - Major defect - Code No. 14003.-If two or more cartridges fail to comply with the requirement of 3.4.3, the lot shall be rejected.

4.2.3.7.5 Rejection.-Dye-marker - Major defect - Code No. 14004.-If two or more cartridges fail to comply with the requirement of 3.4.4, the lot shall be rejected.

4.2.3.7.6 Rejection - Security - Critical defect - Code No. 14005.-If any cartridge fails to comply with the requirement of 3.4.5, the lot shall be rejected.

4.2.4 Inspection Equipment.-Index of Inspection Equipment List Number ET-9229962 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the ET shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:40Z
Check the source to verify that this is the current version before use.

4.3 Testing

4.3.1 Torque test.-Application of the specified torque in the disassembling direction shall be applied. A thin line shall be drawn across the joint in question to aid in observing movement. The projectile shall be secured properly to avoid interference of other joints not under test.

4.3.2 Resistance.-The resistance shall be measured between the primer electrode and the cartridge case using an electrical circuit which limits the current through the primer to 20 milliamperes maximum, with the primer electrode as one contact point and the cartridge case as the other.

4.3.3 Bullet pull.-The security of the crimp of the cartridge case to the projectile shall be tested by applying a force in an axial direction at the rate of 0.100 to 0.125 inches per minute using test equipment in accordance with 4.2.4.

4.3.4 Adhesive on threads.-Ten projectiles shall be selected to obtain a standard for adequate adhesive quantity. Varying amounts of adhesive shall be applied to the male thread of the joint in a manner consistent with the proposed manufacturing application method. After application, the male component shall be fully engaged with the female component and then disassembled. Visual observation shall be used to determine that minimum quantity of adhesive necessary to comply with the requirements of 3.5.4. An additional ten verification samples shall be made with this quantity, and if seven or more meet the requirement, the quantity of adhesive shall be specified as the minimum allowed.

4.3.5 Proving ground.-These tests shall be conducted at a Government proving ground in accordance with the applicable Acceptance Test Procedures. The sample cartridges shall be fired in a gun for which the cartridge is standard and observation made for conformance to all applicable requirements.

4.3.5.1 Performance test.-The fuze on each sample cartridge to be fired shall be set for 400 meters. Radar or other appropriate instrumentation shall be used to determine compliance of first function, muzzle velocity and security with the applicable requirements. Tracer ignition and burning to fuze function and presence of dry marker indicating functioning point shall be readily observable without the use of instruments. Distance to second function shall be recorded for information.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level A.-The cartridges shall be preserved and packaged in accordance with dwg. 9204453.

5.2 Packing

5.2.1 Level A.-The containers shall be packed in accordance with dwg. 9204454.

5.3 Marking.-Marking shall be in accordance with dwgs. 9204453 and 9204454.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Cost of check tests.-The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test. The test shall be conducted at Government expense without cost to the contractor who loaded the primer or the contractor loading and assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., while the primers were under the jurisdiction of either contractor.

6.5 Submission of firing and test data.-In addition to the normal distribution of records for each lot of cartridges, when the item is procured by the Department of the Army, copies should be sent to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND2 (1 copy), SMUPA-DC10 (1 copy), Dover, New Jersey.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1315-A-586

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:40Z
Check the source to verify that this is the current version before use.