MIL-F-14761A(MU)
12 January 1970
SUPERSEDING
MIL-F-14761(MU)
21 May 1968

MILITARY SPECIFICATION

FUZE, TRAINING: XM555 AND TEST PLUG, TRAINING

1. SCOPE

*1.1 This specification covers special requirements, quality assurance provisions, and the preparation for delivery for one type of training fuze, used on Training Projectile: XM455.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.

* MILITARY

MIL-C-10464 - Cans, Hermetic, Sealing, Metal, Light Gage Tear Strip
MIL-I-23053 - Insulation, Tubing, Class I, .375 Inside Diameter, Color Yellow.

MIL-S-6872 - Soldering Process, General Specification for:

STANDARDS

MILITARY

BCYX 1.1 - 420429 - Screw, Lockwasher, Rd. Hd.
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

FSC 1110

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Components
MS-24629 - Screw, Tapping
MS-25178 - Cover, Electrical Connector
MS-35671 - Pin, Groove
MS-9021 - Packing, Preformed

*DRAWINGS

ORDNANCE CORPS

8850283 - Projectile, 155mm Training, XM455 with accessories
8850284 - Fuze, Training: XM555 and Test Plug, Training
8857452 - Fuze, Training, XM555
8857453 - Ring, Fuze Retaining
8857454 - Support, Fuze, Training
8857457 - Nose Housing and Selector Assembly
8857458 - Housing, Nose
8857462 - Connector, Receptacle, Electrical
8857464 - Adapter
8857466 - Screw, Assembled Washer
8857472 - Pin
8857476 - Switch, Option Selection
8857505 - Plug, Test, Training
8857506 - Wire Handle and Cleats
8861940 - Cap, Protective
8861941 - Cup, Nose
8861942 - Cushion, Bottom
8861944 - Cushion, Top
8861946 - Cushion, Support, Bottom
8861947 - Cushion, Support, Top
8861948 - Pad
8861955 - Can, Hermetically Sealed
8864047 - Container, Metal, Ammunition for Fuze, Training: XM555 with Test Plug
9220308 - Connector, Electrical
9220309 - Connector Body Assembly
9220316 - Connector Body Assembly
9220322 - Sealant
9221103 - Connector, Electrical
9223305 - Ring, Compression
9223306 - Option Set Key
10985667 - Sealant

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

10985689 - Potting
10985722 - Cable
10985723 - Receptacle
10985724 - Receptacle, Hermetic
10985739 - Cable, Plug and Receptacle Assembly
10983075 - Sleeve, Potting
ET - 8850284 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material used to fabricate any part complies with the specifications listed on the applicable drawing.

3.2 Assembly. The Fuze and Test Plug shall comply with all requirements specified on Drawing (dwg.) 8850284, with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

*3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

*3.5 Mating assembly (see dwg. 8857462 and 10985724). The electrical connectors shall be capable of being completely mated and unmated with their proper receptacles, without the use of tools. This capability shall be verified as specified in 4.4.1.

3.6 Contact Test (see dwg. 9220308). Each socket after assembly in the connector shall withstand a pull or push of 25 pounds minimum without disengaging when tested as specified in 4.4.2.

*3.7 Open circuit (see dwg. 8864047). The resistance between any pin and any pin and shell in receptacle 10985723 shall be a minimum of 10 megohms when measured as specified in 4.4.3.

3.8 Workmanship.

3.8.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

3.8.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.8.3 Burrs. Parts shall be free from burrs.

3.8.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.8.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

3.8.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

*4.2.1 Quantity to be submitted (see 6.4). When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwg. 8850284), 3 subassemblies (see dwgs. 8857452, 8857457, 8857466, and 8857505) and3 sets of parts, for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in table I. Tests need not be conducted in order specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Table I

First Article Inspection and Tests

	Contractor's Inspection Permissable Before Submission	Non-destructive	Assembly	Sub-Assemblies	Parts
1. Classification of characteristics (see 4.3.2.1)	X	X	X	X	X
2. Mating assembly (see 3.5)	X	X		X	X
3. Contact test (see 3.6)	X	X		X	
4. Open circuit (see 3.7)	X	X	X		
5. Paint adhesion (see 4.3.3.4)	X	X	X		

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Product acceptance inspection.

4.3.1 Lot formation. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, sub-assemblies, or assemblies from the same lot which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristic in the sample found to be defective shall reject the inspection lot. Sequence for the characteristics in each classification need not be followed as long as all characteristic inspections are performed.

* Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	1121-∞	45
26-27	22	48-51	30	113-131	38		

*Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	274-∞	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics. Critical, Major, and Minor classifications are defined in MIL-STD-105. Inspection shall be conducted as follows:

*4.3.2.1.1 Housing, nose (see dwg. 8857458 covering a detail of dwg. 8857457).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Width of flat mounting surface, min.....	Gage
102.	Diameter of through hole.....	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

103.	Location of 2 tapped holes with through hole	Gage
104.	Pitch diameter of 2 tapped holes	Gage
105.	Minor diameter of 2 tapped holes, max	Gage
106.	Diameter of counterbore	Gage
107.	Location of through hole	Gage
108.	Large inside diameter, max	Gage
109.	Depth of counterbore	Gage
110.	Depth of small cavity, min	Gage
111.	Length of large inside diameter	Gage
112.	Material (see 3.1)	Visual

Minor:

201.	Diameter of left basic location	Gage
202.	Location of right basic diameter	Gage
203.	Total length, max	Gage
204.	Radius or chamfer present	Visual
205.	Surface Finish	Visual
206.	Stamping and metal not raised by stamping	Visual/Manual
207.	Protective finish present, no bare spot	Visual
208.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.2 Packing, preformed (see MS-9021-007 covering a detail of dwg. 8857457).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) available for part in accordance with MS9021	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.3 Option set key (see dwg. 9223306 covering a detail of dwg. 8857457).

Categories	Characteristics	Method of Inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Major:		
101.	Width of right projection	Gage
102.	Symmetry of right projection	Gage
103.	Large diameter of right projection, max	Gage
104.	Depth of right projection, min	Gage
105.	Distance from right face to left of flange	Gage
106.	Width of groove	Gage
107.	Diameter of groove	Gage
108.	Left diameter, min	Gage
109.	Width of slot, min	Gage
110.	Surface finish on sides of groove	Visual
111.	Material (see 3.1)	Visual
Minor:		
201.	Protective finish present; no bare spot	Visual
202.	Workmanship (see 3.8)	Visual/manual

*4.3.2.1.4 Ring, compression (see dwg 9223305 covering a detail of dwg 8857457).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) available for part in accordance with dwg 9223305	Visual
102.	No cracks, splits, or tears	Visual
Minor:		
202.	Workmanship (see 3.8)	Visual/manual

*4.3.2.1.5 Switch, option (see dwg 8857476 covering a detail of dwg 8857457).

Categories	Characteristics	Method of Inspection
Critical: None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Major:
101. Location of 2 holes..... Gage
102. Diameter of 2 holes..... Gage
103. Objective evidence (see 6.2) available for switch in accordance with dwg 8857476..... Visual

Categories	Characteristics	Method of Inspection

Minor:
201. Marking..... Visual
202. Workmanship (see 3.8)..... Visual/Manual

*4.3.2.1.6 Screw, assembled washer (see 8857466 covering a detail of dwg 8857457).

Categories	Characteristics	Method of Inspection

Critical: None defined

Major:
101. Objective evidence (see 6.2) available for part in accordance with dwg 8857466..... Visual

Minor:
202. Workmanship (see 3.8)..... Visual/Manual

*4.3.2.1.7 Nose housing and selector assembly (see dwg 8857457 covering a detail of dwg 8857452

Categories	Characteristics	Method of Inspection

Critical: None defined

Major:
101. No incorrect assembly or part missing..... Visual/Manual
102. Option set key can be rotated thru 135° (approximate) starting with slot parallel with axis.. Visual/Manual

Minor:
201. Workmanship (see 3.8)..... Visual

*4.3.2.1.8 Pin, groove (see MS-35671-34 : covering a detail of dwg 8857452).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of inspection
Critical: None defined		
Major:		
101.	Objective evidence (see 6.2) available for part in accordance with MS35671	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.9 Ring, fuze retaining (see dwg 8857453 covering a detail of dwg 8857452).

Categories	Characteristics	Method of inspection
Critical: None defined		
Major:		
101.	Distance between flats	Gage
102.	Pitch diameter of thread	Gage
103.	Minor diameter of thread, max	Gage
104.	Depth of thread cavity, min	Gage
105.	Right inside diameter, max	Gage
106.	Width of outside groove, min	Gage
107.	Total length, min	Gage
108.	Material (see 3.1)	Visual
109.	Thread relief present	Visual
Minor:		
201.	Left outside diameter	Gage
202.	Right outside diameter	Gage
203.	Distance from left face to outside groove	Gage
204.	Surface finish	Visual
205.	Blunt start on thread	Visual
206.	Stamping and metal not raised by stamping	Visual/Manual
207.	Protective finish present; no bare spot	Visual
208.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.10 Support, fuze, training (see dwg 8857454 covering a detail of dwg 8857452).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of inspection
Critical: None defined		
Major:		
101.	Small width between openings in flange (2 places).	Gage
102.	Location of 2 small spaces between openings in flange	Gage
103.	Small width of 3 openings in flange, min.	Gage
104.	Large width between openings in flange	Gage
105.	Symmetry of large space between openings	Gage
106.	Inside diameter of 3 openings in flange	Gage
107.	Concentricity of inside diameter of 3 openings in flange	Gage
108.	Thickness of flange	Gage
109.	Outside diameter	Gage
110.	Depth of cavity, min.	Gage
111.	Depth of 2 recessed curved sections, min.	Gage
112.	Total length	Gage
113.	Pitch diameter of 4 large tapped holes	Gage
114.	Minor diameter of 4 large tapped holes, max.	Gage
115.	Location of 4 large tapped holes	Gage
116.	Diameter of 20 holes	Gage
117.	Location of 20 holes	Gage
118.	Pitch diameter of 2 small tapped holes	Gage
119.	Minor diameter of 2 small tapped holes, max.	Gage
120.	Diameter of counterbore 2 small tapped holes, min.	Gage
121.	Depth of counterbore 2 small tapped holes	Gage
122.	Location of 2 small tapped holes	Gage
123.	Width of 2 recessed curved sections, min.	Gage
124.	Concentricity of 2 recessed sections	Gage
125.	Material (see 3.1)	Visual
Minor:		
201.	Large outside diameter of flange	Gage
202.	Small outside diameter of flange	Gage
203.	Chamfer or radii missing	Visual
204.	Surface Finish	Visual
205.	Scribe lines present	Visual
206.	Stamping and metal not raised by stamping	Visual
207.	Protective finish present; no bare spots	Visual
208.	Workmanship (see 3.8)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

*4.3.2.1.11 Adhesive sealant (see dwg 9220322 covering a detail of dwgs 9220309 and 9220316).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) available for sealant in accordance with drawing 9220322.....	Visual
Minor: None defined		

* 4.3.2.1.12 Connector, electrical (see dwg 9220308 covering a detail of dwg 8857452).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major:		
101.	No incorrect assembly and no part missing.....	Visual
Minor:		
202.	Workmanship (see 3.8).....	Visual/Manual

4.3.2.1.13 Fuze, training, XM555 (see dwg 8857452 covering a detail of dwg 8850284) before assembly of pins.

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major:		
101.	Diameter of pin holes.....	Gage
Minor: None defined		

*4.3.2.1.14 Fuze, training XM555 (see dwg 8857452 covering a detail of dwg 8850284).

Categories	Characteristics	Method of Inspection
Critical: None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Major:

101.	Alignment of scribe mark on fuze support	Gage
102.	Pins below surface	Visual/Manual
103.	Pins tight	Manual
104.	Retaining ring rotates freely	Manual
105.	No incorrect assembly and no part missing	Visual

Minor:

201.	Paint present, no bare spot	Visual
202.	Stamping and stamping filled with paint	Visual
203.	Marking	Visual
204.	Serialization (see 3.4)	Visual
205.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.15 Connector body assembly (see dwg 9220316 covering a detail of dwg 9221103).

Categories	Characteristics	Method of Inspection

Critical: None defined

Major:

101.	No incorrect assembly or part missing	Visual
102.	Objective evidence (see 6.2) available for tubing insulation in accordance with MIL-I-23053	Visual

Minor:

201.	Marking	Visual
202.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.16 Pin (see dwg 8857472 covering a detail of dwg 8857505).

Categories	Characteristics	Method of Inspection

Critical: None defined

Major:

101.	Left diameter, min	Gage
102.	Right diameter, max	Gage
103.	Middle diameter, min	Gage
104.	Length of right diameter, min	Gage
105.	Length from right end to shoulder between left and middle diameters, min	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Major:		
106.	Total length, max	Gage
107.	Material (see 3.1)	Visual
Minor:		
201.	Radius present	Visual
202.	Surface Finish	Visual
203.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.17 Connector, electrical (see dwg 9221103 covering a detail of dwg 8857505).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major:		
101.	No incorrect assembly and no part missing	Visual
Minor:		
202.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.18 Adapter (see dwg 8857464 covering a detail of dwg 8857505).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major:		
101.	Location of 4 holes with center hole	Gage
102.	Diameter of 4 holes	Gage
103.	Location of 4 tapped holes with center hole	Gage
104.	Pitch diameter of 6 tapped holes	Gage
105.	Minor diameter of 6 tapped holes	Gage
106.	Depth of chamfer in center holes, min	Gage
107.	Diameter of center hole, min	Gage
108.	Length from shoulder to end, max	Gage
109.	Total length, min	Gage
110.	Pitch diameter of 3 section thread, max	Gage
111.	Major diameter of 3 section thread, min	Gage
112.	Length of diameter rear of 3 section thread clearance, max	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Major:		
113.	Material (see 3.1)	Visual
114.	No step present see detail A	Visual
Minor:		
201.	Chamfer or radii present	Visual
202.	Surface finish	Visual
203.	Stamping	Visual
204.	Protective finish present, no bare spot	Visual
205.	Blunt start on thread	Visual
206.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.19 Cover, electrical connector (see dwg MS-25178-10), screw, lockwasher, Rd, Hd. (see dwg BCYX1.1-420429), and screw, tapping (see MS-24629-10 Type F) covering details of dwg 8857505.

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major:		
101.	Objective evidence (see 6.2) available for part in accordance with applicable standard	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.20 Wire handle and cleats (see dwg 8857506 covering a detail of dwg 8857505).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major:		
101.	Objective evidence (see 6.2) available for part in accordance wth dwg 8857506	Visual
Minor:		
201.	Protective Finish present; no bare spot	Visual
202.	Marking	Visual
203.	Workmanship (see 3.8)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

*4. 3. 2. 1. 21 Connector, receptacle, electrical (see dwg 8857462 covering a detail of dwg 8857505).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6. 2) available for part in accordance with dwg 8857462	Visual
Minor:		
201.	Workmanship (see 3. 8)	Visual/Manual

*4. 3. 2. 1. 22 Plug, test, training (see dwg 8857505 covering a detail of dwg 8850284).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Location of 4 guide pins of connectors	Gage
102.	Pins replaced	Visual
103.	No part missing and no part improperly assembled	Visual/Manual
104.	Objective evidence (see 6. 2) available for sealing compound in accordance with drawing note	Visual
105.	Sealing compound present or properly applied	Visual
Minor:		
201.	Paint present no bare spot, correct color	Visual
202.	Marking properly filled with paint as applicable	Visual
203.	Workmanship (see 3. 8)	Visual/Manual

*4. 3. 2. 1. 23 Fuze, training, XM555 and test plug, training (see dwg 8850284 covering a detail of dwgs 8850283 and 8864047).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Properly assembled	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.24 Cap protective (see dwg 8861940); cable (see dwg 10985722); receptacle (see dwg 10985723); receptacle, hermetic (see dwg 10985724); sealant (see dwg 10985667); potting (see dwg 10985689) covering details of dwgs 8864047 and 10985739 as applicable.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) available for part in accordance with applicable drawing	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.25 Can, hermetically sealed(see dwg 8861955 covering a detail of dwg 8864047).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Diameter of hole	Gage
102.	Objective evidence (see 6.2) available for container in accordance with MIL-C-10464 with exceptions listed on dwg 8861955	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.26 Cup, nose (see dwg 8861941 covering a detail of dwg 8864047).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Material (see 3.1)	Visual
102.	No dent, void or imperfection in surface larger than one square inch (for plastic only)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Minor:
201. Radius present ..... Visual
202. Evidence of poor workmanship (see 3.8) ..... Visual/Manual

*4.3.2.1.27 Cushion, bottom (see dwg 8861942) and cushion support bottom (see dwg 8861946) covering a detail of dwg 8864047).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	No dent, void or imperfection in the surface larger than one half square inch	Visual
102.	Material (see 3.1)	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.28 Cushion, support, top (see dwg 8861947 covering a detail of dwg 8864047).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	No dent, void or imperfection in the surface larger than one half square inch	Visual
102.	Material (see 3.1)	Visual
Minor:		
202.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.29 Cushion, top (see dwg 8861944 covering a detail of dwg 8864047).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	No dent, void or imperfection in the surface larger than one half square inch	Visual
102.	Material (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Minor:
202. Workmanship (see 3.8) ..... Visual/Manual

*4.3.2.1.30 Pad (see dwg 8861948 covering a detail of dwg 8864047).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. No tears, splits or holes ..... Visual
102. Material (see 3.1) ..... Visual

Minor:
201. Evidence of poor workmanship (see 3.8) ..... Visual/Manual

*4.3.2.1.31 Sleeve potting (see dwg 10983075) covering a detail of dwg 10985739

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. No hole, split, crack or gouge ..... Visual
102. Material (see 3.1) ..... Visual

Minor: None defined.

*4.3.2.1.32 Cable, plug, and receptacle assembly (see dwg 10985739 covering a detail of dwg 8864047 before potting.

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Length between connectors ..... **Measure
102. Soldering ..... Visual/Manual
103. Wiring ..... Visual
104. Sealant present ..... Visual

**Measure with suitable scale

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Minor:

201. Workmanship (see 3.8) ..... Visual/Manual

*4.3.2.1.33 Cable, plug and receptacle assembly (see dwg 10985739 covering a detail of dwg 8864047)

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Potting and boot assembly	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.34 Container, metal, ammo, for fuze, training; XM555 with test plug (see dwg 8864047) prior to seaming bottom cover (see section 5).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Container or cover not perforated	Visual
102.	No component missing	Visual
103.	No dent which interferes with assembly of packing material	Visual/Manual
104.	Tightly packed	Manual
105.	Soldering of connector in accordance with MIL-S-6872	Visual/Manual
106.	Glass insert of receptacle not cracked or damaged after soldering	Visual
107.	Proper rubber adhesive application	Visual
108.	Potting	Visual/Manual
109.	Cable packed properly	Visual
Minor:		
201.	Workmanship (see 3.8)	Visual/Manual

*4.3.2.1.35 Container, metal, ammo, for fuze, training: XM555 with test plug (see dwg 8864047) after seaming bottom cover (see section 5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Bottom cover seamed properly	Visual
102.	Correct color	Visual
103.	Fuze tight in container	Manual
104.	Blue squares present	Visual
Minor:		
201.	Marking	Visual
202.	Protective finish present; no bare spot	Visual
203.	Serialization correct	Visual
204.	Workmanship (see 3.8)	Visual

*4.3.2.1.36 Preparation for delivery (see section 5).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) available for packing in accordance with MIL-STD-1169	Visual
Minor:		
201.	Marking, missing, incorrect, incomplete or unidentifiable	Visual
202.	Workmanship (see 3.8)	Visual/Manual

4.3.3 Testing. The contractor shall perform all the tests specified in this paragraph. Tests do not have to be performed in the order specified.

Test	Test Classification
a. Mating assembly	Major
b. Contact test	Major
c. Open circuit	Major
d. Paint adhesion	Minor

None of these tests are considered destructive and samples so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

4.3.3.1 Mating assembly (see 3.5). Each connector in the lot shall be subjected to this test (see 4.4.1). If any connector fails to comply with 3.5, it shall be classified defective and removed from the lot.

4.3.3.2 Contact test (see 3.6). Each socket in the connector shall be tested as specified in 4.4.2. If any socket fails to comply with 3.6, the connector shall be rejected and removed from the lot.

4.3.3.3 Open circuit (see 3.7). Each container and training fuze shall be tested as specified in 4.4.3. If the container and fuze fails to comply with 3.7, the container and fuze shall be rejected and removed from the lot.

4.3.3.4 Paint adhesion (see dwgs 8857452, 8857505, 8864047 and 8850284). Each part or assembly shall be tested for paint adhesion as specified in Paint Adhesion Section 4, TT-C-490. Any part or assembly which fails to comply with the requirements for Paint Adhesion, Section, TT-C-490 will be classifed defective and removed from the lot.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). EL's for assemblies are listed on the Equipment Tabulation, ET-8850284. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment. The contractor shall obtain approval of such designs, operating instructions, and special calibration instructions as specified in 6.3 prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired.

b. The code "C D" is listed in the "Part or Identifying Number" column on the EL.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

*4.4.1 Mating assembly (see 3.5). The electrical connectors will be matched to a fixture equivalent to the termination that they are used on.

*4.4.2 Contact test (see 3.6). Each contact shall be pulled in both directions with a suitable approved testing device which will limit the pull to a minimum of 25 pounds.

4.4.3 Open circuit (see 3.7). Each container shall be tested packed with a training fuze for shipment. Check between each pin and each pin and shell on connector 10985724 with a Vaccuum Tube Voltmeter capable of measuring resistance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing and marking for fuze with test plug. Preservation, packaging, packing and marking for fuze with test plug shall be in accordance with dwg 8864047.

5.2 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1 Level A. The container shall be preserved and packaging in accordance with instructions contained in MIL-STD-1169(MU).

5.2.2 Level C. The container shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.3 Packing.

5.3.1 Levels A and C. The container shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.4 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

6. NOTES

*6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions, and calibration instructions from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

6.4 Instructions for first article inspection (see 4.2.1). Parts may be used in subassemblies if the examination or tests (see 4.2.2 Table I) are verified by a representative designated by the Government. Subassemblies may be used in final assemblies if the examination or tests (see 4.2.2 Table I) are verified by a representative designated by the Government.

6.5 Identification of changes. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - MU

Preparing activity:
Army - MU
Project No. 1110-A010

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-14761A(MU) Fuze, Training: XM555 and Test Plug, Training

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:42Z
Check the source to verify that this is the current version before use.