MIL-W-14743C (PA)
25 October 1974
SUPERSEDING
MIL-W-14743B (PA)
22 January 1974

MILITARY SPECIFICATION

WARHEAD SECTION, GUIDED MISSILE, HE, M207 LESS S & A DEVICE PARTS FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts, assembly and packing of one type of high explosive warhead section designated as Warhead Section, Guided Missile, HE, M207, Less S&A Device.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

UU-T-106	Tape, Pressure-Sensitive, Adhesive, Masking, Paper
UU-T-450	Tissue, Facial

MILITARY

MIL-A-2550	Ammunition, General Specification for

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168	Lot Numbering of Ammunition

FSC: 1336

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

MIL-STD-1169	Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

PICATINNY ARSENAL

PRODUCT AND PACKING DRAWINGS

9225122	-	Liner Cone, Warhead
9225133	-	Nose Crush Switch Assembly
9225138	-	Warhead Section, Metal Parts Assembly (TOW)

INSPECTION EQUIPMENT DRAWINGS

9246410	-	Fixture, Test to Failure of Ring, Retaining

2.2 Other Publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids, or request for proposal, shall apply.

AMERICAN SOCIETY FOR TESTING MATERIALS

ASTM D 1002-64	Standard Method of Test for Strength Properties of Adhesives in Shear by Tension Loading (Metal-to-Metal)

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania, 19103).

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

3.2 Components and Assemblies. The components and assemblies shall comply with all requirements on Drawing (dwg.) 9225138 and with all requirements of applicable standards and specifications.

3.3 Airtightness. The warhead assembly shall be air tight.

3.4 Continuity Measurement of Nose Crush Switch Assembly. The wire-to-shell resistance shall be 0.2 ohms, maximum (max.) for each of the two (2) wires.

3.5 Insulation Resistance Measurement of Nose Crush Switch Assembly. The wire-to-wire insulation resistance shall be 500 megohms, minimum (min.).

3.6 Liner-Body Cleaning Process Qualification. The liner-body cleaning process shall be qualified when a simulated liner-body joint exhibits the capability of producing an adhesive joint with an individual shear strength of 300 psi min. and an average shear strength of 500 psi min.

3.7 Adhesion and Mar Resistance of Paint. The paint on the warhead shall not exhibit flaking, peeling, loss of adhesion, marring or discoloration.

3.8 Torque Strength of Retaining Ring. The retaining ring shall exhibit an individual torque strength of 300 inch pounds min.

3.9 Workmanship. All parts and assemblies shall be fabricated in a thorough, workmanlike manner. The parts shall be free of burrs, sharp edges, cracks, flash, tool marks, blisters, porosity, chipped edges, warpage, dirt, rust and other foreign matter. The cleaning method used shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents. Surface coatings shall be continuous except for scratches not exposing base metal.

3.10 First Article Inspection. This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. Unless otherwise specified in the contract or order, the supplier is responsible for the performance of all of the inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Submission of Product. At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with an identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission. The contractor shall submit a first article sample to a Government approved facility as designated by the Contracting Officer (See 6.4) for evaluation in accordance with the provisions of 4.2.2. The first article sample, shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

consist of five (5) complete sets of parts (i.e., five [5] each of every component and every subassembly) which have been produced by the contractor or furnished by a supplier, and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings of tests and examinations and certificates of conformance for materials(See 4.1.1c). A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawings, specification or source of supply such as to significantly affect product uniformity as determined by the Government.

4.2.1.1 Molded Parts. Five (5) molded parts from each mold cavity shall be submitted as part of the first article sample.

4.2.2 Inspections to be Performed. All warhead metal parts and assemblies will be subjected by the Government to any or all of the examinations and tests specified in 4.3.2 and 4.3.3 of this specification, and to any or all requirements of the applicable drawings.

4.2.3 Rejection. If any assembly fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article or portion thereof. Until a first article sample is accepted, the contractor is in no way authorized by the Government to initiate regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection Provisions

4.3.1 Lot Formation. The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

requirements. The sample selected shall represent only that quantity of units from which the sample was drawn, and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision, and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing, not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of complete warhead metal parts assemblies shall contain:

a. Liner Cone Warhead (dwg. 9225122) from not more than one interfix lot number from one manufacturer.

b. Body, (dwg. 9225121) from not more than one interfix lot number, from one manufacturer.

c. Cone, Inner (dwg. 9225125) from not more than one interfix lot number from one manufacturer.

d. Ogive (dwg. 9225130) from not more than one interfix lot number from one manufacturer.

e. Post, Insulator (dwg. 9225132) from not more than one interfix lot number from one manufacturer.

f. Ring, Retaining (dwg. 9225147) from not more than one interfix lot number from one manufacturer.

g. Bushing, Boattail (dwg. 9225123) from not more than one interfix lot number from one manufacturer.

h. Conduit (dwg. 9225142) from not more than one interfix lot number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

4.3.2 Examination. The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for Critical Defects (and Major Defects, when so specified) shall be 100 percent. Sampling plans for Major and Minor Defects shall be in accordance with MIL-STD-105, except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of Major and Minor Defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each Major Defect and an AQL of 0.65 percent for each Minor Defect. When this method is elected, it shall be applied to all of the Major and Minor Defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Liner, Cone, Warhead (See dwg. 9225122, covering a detail of dwg. 9225138).

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 1.0 Percent	
101.	Wall thickness variation in any transverse plane	Gage
102.	Total wall thickness variation	Gage
103.	Surface finish	Gage
104.	Body mating diameter	Gage
105.	Depth to small datum	Gage
106.	Wall thickness	Gage
107.	Depth to large datum	Gage
108.	Straightness	Gage
Minor:	AQL 0.65 Percent	
201.	Evidence of poor workmanship (See 3.9)	Visual

4.3.2.2 Body (See dwg. 9225121, covering a detail of dwg. 9225138).

Categories	Defects	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

Major:	100 Percent	
101.	Location of small aft holes	Gage
102.	Large aft diameter	Gage
	1.0 Percent	
103.	Liner mating diameter	Gage
104.	Location of wireway slot	Gage
105.	Location of boattail positioning slot	Gage
106.	Perpendicularity of aft shoulder with outside diameter	Gage
107.	Perpendicularity of forward shoulder with outside diameter	Gage
108.	Pitch diameter of large aft thread	Gage
109.	Length of ring retaining full thread	Gage
110.	Pitch diameter of small aft thread	Gage
Minor:	AQL 1.0 Percent	
201.	Minor diameter of small aft thread, max.	Gage
202.	Major diameter of large aft thread, min.	Gage
203.	Evidence of poor workmanship (See 3.9)	Visual

4.3.2.3 Bushing, Boattail (See dwg. 9225123), covering a detail of dwg. 9225138).

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 1.0 Percent	
101.	Width of warhead positioning tab	Gage
102.	Height of warhead positioning tab	Gage
103.	Width of S&A positioning tab	Gage
104.	Height of S&A positioning tab	Gage
105.	Height of boattail bushing flange	Gage
Minor:	AQL 0.65 Percent	
201.	Evidence of poor workmanship (See 3.9)	Visual

4.3.2.4 Body Sub-Assembly, Warhead Section (See dwg. 9225124, covering a detail of dwg. 9225138).

Categories	Defects	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

Major:	AQL 1.0 Percent	
101.	Runout of body inside diameter with datums	Gage
102.	Runout of booster pellet cavity diameter with datums	Gage
103.	Perpendicularity of aft face of bushing boattail with datums	Gage
104.	Diameter of nose crush switch assembly mounting hole	Gage
105.	Location of nose crush switch assembly mounting holes	Gage
106.	Aft cavity diameter	Gage
107.	Ogive mating diameter, max.	Gage
108.	Inside corner radius, large aft mounting shoulder, max.	Gage
109.	Alignment of liner cone and body; ogive mating holes	Gage
110.	Adhesive present beyond liner-body mating diameters	Visual
111.	Adhesive present beyond boattail-body mating diameters	Visual
Minor:	AQL 0.65 Percent	
201.	Evidence of poor workmanship (See 3.9)	Visual

4.3.2.5 Cone, Inner (See dwg. 9225125, covering a detail of dwg. 9225138).

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 0.40 Percent	
101.	Thickness of cone	Gage
102.	Position of post insulator holes	Gage
Minor:	AQL 0.65 Percent	
201.	Evidence of poor workmanship (See 3.9)	Visual

4.3.2.6 Ogive (See dwg. 9225130, covering a detail of dwg. 9225138).

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 0.65 Percent	
101.	Thickness of ogive	Gage
102.	Outside configuration	Gage
103.	Runout of ogive nose to datums	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.0 Percent	
201.	Paint-free area improper	Visual
202.	Evidence of poor workmanship (See 3.9)	Visual

4.3.2.7 Nose Crush Switch Assembly (See dwg. 9225133, covering a detail of dwg. 9225138).

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 1.0 Percent	
101.	Warhead body mating diameter	Gage
102.	Diameter of warhead body mating rivet hole	Gage
103.	Location of warhead body mating rivet holes	Gage
104.	Nose crush switch assembly thickness	Gage
105.	Part missing or not assembled as specified	Visual
106.	Cracked post insulator	Visual
Minor:	AQL 0.65 Percent	
201.	Evidence of poor workmanship (See 3.9)	Visual

4.3.2.8 Conduit (See dwg. 9225142, covering a detail of dwg. 9225138).

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 1.0 Percent	
101.	Overall profile	Gage
102.	Height	Gage
103.	Width	Gage
104.	Thickness	Gage
105.	Location of large radius	Gage
Minor:	AQL 0.65 Percent	
201.	Evidence of poor workmanship (See 3.9)	Visual

4.3.2.9 Retaining Ring (See dwg. 9225147, covering a detail of dwg. 9225138).

Categories	Defects	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.65 Percent	
101.	Pitch diameter	Gage
102.	Minor diameter (max.)	Gage
103.	Flange inside diameter	Gage
Minor:	AQL 0.65 Percent	
201.	Evidence of poor workmanship (See 3.9)	Visual

4.3.3 Testing .

4.3.3.1 First Article Sample (See 4.2.1). The assemblies and components submitted as the first article sample shall be tested as specified below after having been examined for requirements as specified in 4.2.2. Rejection and resubmission shall be in accordance with 4.2.3.

4.3.3.1.1 Airtightness (See 3.3 and 4.3.3.2.1).

4.3.3.1.2 Continuity (See 3.4 and 4.3.3.2.2).

4.3.3.1.3 Insulation Resistance (See 3.5 and 4.3.3.2.3).

4.3.3.1.4 Liner-Body Cleaning Process Qualification (See 3.6) - Major Defect. Ten (10) sample specimens shall be tested in accordance with the procedure in 4.4.4, using equipment as specified in 4.3.4. Failure of one or more sample specimens to meet the minimum strength requrement or the average of the specimens to meet the minimum average strength requirement shall reject the liner-body cleaning process.

4.3.3.1.5 Adhesion and Mar Resistance of Paint (See 3.7) - Major Defect. These tests shall be performed on each assembly in accordance with the procedures in 4.4.5, using equipment as specified in 4.3.4.

4.3.3.1.6 Torque Strength of Retaining Ring (See 3.8)) - Major Defect. This test shall be performed on each ring in accordance with the procedure in 4.4.6, using equipment as specified in 4.3.4.

4.3.3.2 Production

4.3.3.2.1 Airtightness (See 3.3) - Major Defect. This test shall be performed 100 percent in accordance with the procedure in 4.4.1, using equipment as specified in 4.3.4. Any assembly failing to meet the requirement shall be classed defective and removed from the lot.

4.3.3.2.2 Continuity (See 3.4) - Major Defect. This test shall be performed 100 percent in accordance with the procedure in 4.4.2, using equipment as specified in 4.3.4. Any assembly failing to meet the requirement shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

4.3.3.2.3 Insulation Resistance (See 3.5) - Major Defect. This test shall be performed 100 percent in accordance with the procedure in 4.4.3, using equipment as specified in 4.3.4. Any assembly failing to meet the specified requirement shall be classed defective and removed from the lot.

4.3.3.2.4 Adhesion and Mar Resistance of Paint (See 3.6) - Major Defect. The sampling plan for these tests shall be in accordance with MIL-STD-105, using inspection Level II with an AQL of 0.10 percent. These tests shall be performed in accordance with the procedure in 4.4.5, using equipment as specified in 4.3.4.

4.3.3.2.5 Molded Components. At the start of production from a new mold, or repair to a mold or cavity, consecutively produced units from each mold or cavity shall be dimensionally examined until 4 consecutive units meet all applicabte drawing requirements. After adjustment or repair, those dimensions affected by the adjustment or repair shall be examined. During production, the molding procedures shall be monitored for uniformity of molding practices. Suspected deviations in mold product shall be examined to determine if corrective action or mold repair is required.

4.3.3.2.6 Torque Strength of Retaining Ring (See 3.8) - Major Defect. Ten (10) rings shall be tested from each day's production in accordance with the procedure in 4.4.6, using equipment as specified in 4.3.4. Failure of one or more rings to meet the minimum strength requirement shall reject the day's production represented by the sample.

4.3.4 Inspection Equipment. Inspection equipment required to perform the inspection prescribed in this specification is identified in the Examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection equipment design and approval.

4.4 Test Methods and Procedures

4.4.1 Airtightness. The warhead assembly shall be assembled to the test equipment and an internal air pressure of 5 pounds per square inch (psi) introduced into the explosive charge cavity. After the internal air pressure has reached the specified level, the air supply shall be shut off and the cavity under test shall be observed

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

for a zero (0) air pressure drop for a minimum time of 5 seconds after the air supply is shut off. The test equipment shall be capable of detecting a 0.01 psi pressure drop of 5 psi cavity pressure in a test container of like volume.

4.4.2 Continuity. The continuity measurements shall be taken across the wire and the appropriate ogive (black to outer, brown to inner) of the Nose Crush Switch Assembly dwg. 9225133.

4.4.3 Insulation Resistance. Insulation resistance measurements shall be taken across the ends of the wires. Resistance shall be measured under an impressed voltage of 500 volts plus or minus (±) 50 volts.

4.4.4 Liner-Body Cleaning Process Qualification. This test shall be performed as specified in Test Method ASTM D 1002-64 with the exception that the test specimen shall consist of .110 mils thick sheet stock copper, composition as specified on dwg. 9225122. The joint shall be heat-cured at 250°F for 45 minutes maximum and then cooled to room temperature.

4.4.5 Adhesion and Mar Resistance Tests

4.4.5.1 Adhesion. Firmly apply a one (1) inch wide strip of masking tape conforming to UU-T-106 for the full length of one (1) of the launch leader bonding areas and peel the tape off in one abrupt motion.

4.4.5.2 Mar Resistance. Lay a small pad of tissue, conforming to the requirements of UU-T-450, approximately one (1) inch square and 8 to 12 layers thick, on one (1) of the launch leader bonding areas, other than the arch subjected to the adhesion test. Fully saturate the pad with thinner utilized in the painting process. Cover the pad with a small beaker. Remove the pad after one (1) minute and rub the moistened spot with a clean dry cloth or tissue. Failure is indicated by discoloration of the cloth or tissue or by visible evidence of damage to the painted surface. A slight whitening of the surface wbich may be removed by light rubbing with a dry cloth shall not be reason for rejection.

4.4.6 Torque Strength of Retaining Ring. The ring shall be assembled to a post, dwg. 9246410. A torque adapter, dwg. 9246410, assembled to a torque wrench positioned over the ring, and the ring is torqued to failure. Torque values are recorded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging and Packing. Level C. The parts shall be packaged and packed in accordance with the requirements of MIL-STD-1169.

5.2 Marking. Marking shall be in accordance with the requirements of MIL-STD-1169.

6. NOTES

6.1 Intended Use. The Warhead Section, M207 covered by this specification is intended for use in the TOW Guided Missile, BG M71.

6.2 Ordering Data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data Cards. Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

c. Inspection equipment design requirements (See 4.3.4 and 6.3).

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers (under the "Method of Inspection" headings in Section 4). Design responsibility for all other inspection equipment is assigned to the contractor. Equipment to be designed by the contractor is designated "CD". The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3, should he elect to do so.

6.3.1 SIE Designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

b. A source control drawing or a specification control drawing, as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor Designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified, and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government, and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commerical equipment, or with SIE designs if not otherwise covered thereby (See 6.3.1 c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and other specific identifying information from Section 4 of this specification shall be referenced on each contractor design, together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Picatinny Arsenal, ATTN: SARPA-QA-A-R, Dover, New Jersey, 07801, in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

6.4 Submission of First Article Sample. Instructions as to the submission and location for testing and evaluation of the first article sample shall be obtained from the Contracting Officer. Upon receipt of such request, the Contracting Officer shall advise Picatinny Arsenal and instructions will be issued accordingly. All inquiries should be forwarded to:

Commander
Picatinny Arsenal
ATTN: SARPA-QA-I-Q
Dover, New Jersey 07801

6.5 Definitions

6.5.1 Contractor. Unless otherwise specified, the word "Contractor", used throughout this specification, shall mean any supplier or producer of items or material to the Government. This shall include commercial contractors, sub-contractors, Government-owned, Contractor-Operated (GOCO) and Government-Owned, Government-Operated (GOGO) plants.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1336-A234

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:40Z
Check the source to verify that this is the current version before use.