MIL-G-22169(WEP)
AMENDMENT-2
1 DECEMBER 1960
SUPERSEDING
AMENDMENT-1
2 MAY 1960

MILITARY SPECIFICATION

GYRO, VERTICAL AND MOUNT

This amendment forms a part of Military Specification MIL-G-22169(AER) dated 15 August, 1959 and has been approved by the Bureau of Naval Weapons, Department of the Navy.

By this amendment basic MIL-G-22169(AER) is changed to MIL-G-22169(WEP) and throughout the specification Bureau of Aeronautics shall be changed to Bureau of Naval Weapons.

Page 6: Add new paragraph

"4.3.2 Authorization - Requests for authorization for Qualification Tests shall be addressed to the Bureau of Naval Weapons, Department of the Navy, Washington 25, D. C., the qualifying agency."

Page 7, paragraph 4.7.2: Add

"Insulation breakdown shall be defined as an alternating current leakage impedance of less than 200,000 ohms, or a leakage current of 2.5 milliamperes."

Page 8, paragraph 4.7.6: Delete last sentence and substitute

"The average of A. B and C phase currents shall not exceed 0.300 ampere when fast erection is applied."

Page 8, paragraph 4.7.8, After paragraph title: Add

"These tests shall be conducted with the gyro mounted on a pitch, roll and yaw mechanism with a movement of ± 1-1/2°."

Page 8, paragraph 4.7.10, End of fifth sentence: Delete

"and at the end of that time, the spin axis shall not have drifted more than 2° in a northerly or southerly direction, 1° in an easterly direction, or 3° in a westerly direction."

Page 9, paragraph 4.7.17, eighth line, after "and 4.7.10 Drift": Add

", except that the maximum time specified in 4.7.8 shall be changed from 2 minutes, 30 seconds, to 5 minutes."

Page 10, paragraph 4.7.20, seventh line, after "4.7.10 Drift": Add

", except that the maximum time specified in 4.7.8 shall be changed from 2 minutes, 30 seconds, to 5 minutes."

FSC 6605

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:17Z
Check the source to verify that this is the current version before use.