MILITARY SPECIFICATION

INDICATOR, TORQUEMETER, ENGINE, TURBOPROP

This amendment forms a part of Military Specification MIL-I-22126B(AS), dated 17 August 1972 and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 14

Paragraph 3.14 - Delete the text, and substitute:

"The generation of radio interference by the torquemeter indicator and the vulnerability of the indicator to radio interference shall meet the requirements of MIL-STD-461 for Class 1D equipment except that test method CS02 shall apply only to 0.15 MHz"

Page 17

Paragraph 4.4.2.1.1 - Insert "Light tests" in the list between "Power consumption" and "High temperature operation."

Page 18

Paragraph 4.4.2.2.2 - Delete "Salt fog test" at the top of the list. Add "Specular reflectance" at the bottom of the list.

Paragraph 4.4.3.2 - Delete this paragraph and substitute the following paragraph:

4.4.3.2 Reliability production (sampling) phase tests - The equipment, throughout production, shall be tested as outlined in MIL-STD-781 (as modified herein) under the section entitled "Production Acceptance (Sampling)Phase of Production Reliability Tests." Test Level E shall be used.

Paragraph 4.4.3.2.1 - Delete this paragraph, and substitute the following paragraph:

4.4.3.2.1 All equipment test - Each equipment produced except those submitted for the Reliability Qualification Test, shall be tested

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:12Z
Check the source to verify that this is the current version before use.

for 75 hours (25 cycles of Table III). Prior to the 75 hour test on each equipment, a burn-in period may be used at the option of the contractor. If the burn-in period is to be used, the details thereof must be included in the approved test procedures. To determine whether or not the MTBF is being met at any time during the contract, the operating test hours and the failures (not counting burn-in failures or burn-in operating time) shall be totaled and the results compared with the reject line of Test Plan XXIX of MIL-STD-781. (Extend the line as necessary to accommodate the data.) These totals shall accumulate so that at any one time the experience from the beginning of the contract is included. At the conclusion of each month, the test results shall be sent to the procuring activity and to Naval Air Systems Command: Avionics Division, At any time that the current totals of test hours and test failures plotted on Test Plan XXIX curves show a reject situation, the procuring activity shall be notified. The procuring activity reserves the right to stop the acceptance of equipment at any time that a reject situation exists pending a review of the contractor's efforts to improve the equipment, the equipment parts, the equipment workmanship, etc., so that the entire compilation will show other than a reject decision."

Page 19

Paragraph 4.4.3.3.2 - Delete the first sentence, and substitute:

"The scale error and friction test, described under Inspection methods, shall be conducted at least once each week on Reliability Qualification Phase samples and at the end of the 75 hours on each of the production equipment."

Page 24

Insert the following paragraph between paragraphs 4.6.12 and 4.6.13:

"Light tests: Each lighted sample indicator shall be subjected to and shall meet the requirements of the following tests specified in MIL-L-25467:

(1) Color
(2) Brightness
(3) Stray light"

Page 26

Paragraph 4.6.19 - Delete the text, and substitute:

"The indicator shall be tested for conducted and radiated radio noise interference in accordance with 3.14, herein, and MIL-STD-462."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:12Z
Check the source to verify that this is the current version before use.

Paragraph 4.6.21 - Add the following at the end of the paragraph:

"Not sooner than four hours after return to room temperature the indicator shall be subjected to and shall meet the requirements of 4.6.4."

Paragraph 4.6.22 - Add the following at the end of the paragraph:

"Not sooner than four hours after return to room temperature the indictor shall be subjected to and shall meet the requirements of 4.6.4."

Page 27

Paragraph 4.6,27 - Add the following at the end of the paragraph:

"One of the three sample indicators shall be subjected to and shall meet the 'Equipment crash-safety' portion of the test. This indicator shall not be required to meet the requirements of subsequent tests."

Add Paragraph 4.6.31"

"4.6.31 Specular reflectance - Each sample indicator shall be subjected to and meet the requirements of the Specular reflectance test of MIL-C-14806."

DOD Proj. No.
6620-N046

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:12Z
Check the source to verify that this is the current version before use.