INCH-POUND

MIL-I-22126B(AS)
AMENDMENT 3
16 April 2001
SUPERSEDING
AMENDMENT 2
11 January 1974

MILITARY SPECIFICATION

INDICATOR, TORQUEMETER, ENGINE, TURBOPROP

INACTIVE FOR NEW DESIGN AFTER 16 OCTOBER 1996

This amendment forms a part of MIL-I-22126B(AS), dated 17 August 1972, and has been approved by the Naval Air Systems Command, Department of the Navy. It is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

* 3.1: Delete and substitute:

"3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.3."

PAGE 14

3.14: Delete and substitute:

"The generation of radio interference by the torquemeter indicator and the vulnerability of the indicator to radio interference shall meet the requirements of MIL-STD-461 for class 1D equipment except that test method CS02 shall apply only to 0.15 MHz."

PAGE 15

* 4.2(a): Delete and substitute:

"(a) First article inspection. First article inspection consists of examinations and tests performed on sample indicators submitted."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:12Z
Check the source to verify that this is the current version before use.

* 4.3: Delete and substitute:

"4.3 First article inspection. First article inspection of the indicator shall consist of all the examinations and tests of this specification performed in the order specified under the paragraph headed Inspection methods and samples submitted."

* 4.3.1: Delete and substitute:

"4.3.1 First article inspection sample. First article inspection samples shall consist of three indicators manufactured in accordance with the specification. The indicators submitted for first article inspection shall have been previously subjected only to the individual inspections. The samples shall be forwarded to the laboratory designated in the Letter of Authorization (see 6.7). A copy of the installation instructions shall be furnished with each first article inspection sample in accordance with 3.11.1."

* 4.3.1.1: Delete and substitute:

"4.3.1.1 First article inspection sample identification. The first article inspection samples shall be plainly identified by durable tags, securely attached, and marked with the following information:

Sample for First Article Inspection
Indicator, Torquemeter, Engine, Turboprop
Submitted by (manufacturer's name, date)
for First article inspection in accordance with
Specification MIL-I-22126B(AS) under authorization
(reference letter authorizing tests).

PAGE 16

* 4.3.2: Delete.

PAGE 17

4.4.2.1.1: Insert "Light tests" in the list between "Power consumption" and "High temperature operation."

PAGE 18

4.4.2.2.2: Delete "Salt fog test" at the top of the list. Add "Specular reflectance" at the bottom of the list.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:12Z
Check the source to verify that this is the current version before use.

* 4.4.3, second sentence: Delete "Qualification Phase and."

* 4.4.3.1: Delete.

4.4.3.2: Delete and substitute:

"4.4.3.2 Reliability production (sampling) phase tests. The equipment, throughout production, shall be tested as outlined in MIL-STD-781 (as modified herein) under the section entitled "Production acceptance (sampling) phase of production reliability tests." Test level E shall be used."

4.4.3.2.1: Delete and substitute:

"4.4.3.2.1 All equipment test. Equipment shall be tested for 75 hours (25 cycles of table III). Prior to the 75 hour test on each equipment, a burn-in period may be used at the option of the contractor. If the burn-in period is to be used, the details thereof must be included in the approved test procedures. To determine whether or not the MTBF is being met at any time during the contract, the operating test hours and the failures (not counting burn-in failures or burn-in operating time) shall be totaled and the results compared with the reject line of test plan XXIX of MIL-STD-781. (Extend the line as necessary to accommodate the data.) These totals shall accumulate so that at any one time the experience from the beginning of the contract is included. At the conclusion of each month, the test results shall be sent to the procuring activity and to Naval Air Systems Command, Avionics Division. At any time that the current totals of test hours and test failures plotted on test plan XXIX curves show a reject situation, the procuring activity shall be notified. The procuring activity reserves the right to stop the acceptance of equipment at any time that a reject situation exists pending a review of the contractor's efforts to improve the equipment, the equipment parts, the equipment workmanship, etc., so that the entire compilation will show other than a reject decision."

PAGE 19

* 4.4.3.3.2: Delete the first sentence and substitute:

"The scale error and friction test, described under inspection methods, shall be conducted at the end of the 75 hours on each of the production equipment."

PAGE 24

Insert the following paragraph between paragraphs 4.6.12 and 4.6.13:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:12Z
Check the source to verify that this is the current version before use.

"Light tests. Each lighted sample indicator shall be subjected to and shall meet the requirements of the following test specified in MIL-L-25467:

(1) Color
(2) Brightness
(3) Stray light"

PAGE 26

4.6.19: Delete and substitute:

"The indicator shall be tested for conducted and radiated radio noise interference in accordance with 3.14, herein, and MIL-STD-462."

4.6.21: Add the following at the end of the paragraph:

"Not sooner than four hours after return to room temperature the indicator shall be subjected to and shall meet the requirements of 4.6.4."

4.6.22: Add the following at the end of the paragraph:

"Not sooner than four hours after return to room temperature the indicator shall be subjected to and shall meet the requirements of 4.6.4."

PAGE 27

4.6.27: Add the following at the end of the paragraph:

"One of the three sample indicators shall be subjected to and shall meet the equipment crash safety promotion of the test. This indicator shall not be required to meet the requirements of subsequent tests."

Add as 4.6.31:

"4.6.31 Specular reflectance. Each sample indicator shall be subjected to and meet the requirements of the specular reflectance test of MIL-C-14806."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:12Z
Check the source to verify that this is the current version before use.

PAGE 28

* 6.2.1: Add as 6.2.1(f):

"(f) When first article is required (see 3.1)."

PAGE 29

* 6.7: Delete.

PAGE 30

6.9: Add as 6.9:

"6.9 Subject term (key word) listing.

Cadmium plating"

NOTE: The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationships to the last previous amendment.

Preparing activity:
Navy - AS

(Project 6620-0728)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:12Z
Check the source to verify that this is the current version before use.