INCH-POUND

MIL-DTL-21097/14F
18 August 2005
SUPERSEDING
MIL-C-21097/14E
21 July 1986

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, PRINTED WIRING BOARD MALE ADAPTER, CONTACT SPACING: 0.200, ALTERNATE DUAL ROW, TYPE CS, BLADE CONTACT (MOUNTING PROVISION A)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-21097.




FIGURE 1. Blade contact type CS alternate dual row contacts.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.


Inches	mm	Inches	mm
.001	0.03	.128	3.25
.010	0.25	.155	3.94
.015	0.38	.160	4.06
.0245	0.622	.200	5.08
.082	2.08	.280	7.11
.100	2.54	.400	10.16
.106	2.69	.415	10.54
.125	3.18	.460	11.68

NOTES:

1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .005 (.13 mm) for three place decimals.
3. Metric equivalents are given for information only.
4. See table I for dimensions.
5. All even numbered contacts to be identified with .047 (1.19 mm) minimum high characters, as shown.


FIGURE 1. Blade contact type CS alternate dual row contacts - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.



Printed wiring board	
Size	T dim
2	.062 (1.57)
3	.093 (2.36)
4	.125 (3.18)

Inches	mm	Inches	mm
.002	0.05	.300	7.62
.050	1.27	.350	8.89
.052	1.32	.531	13.49
.093	2.36	.625	15.88
.100	2.54	.895	22.73
.128	3.25	4.731	120.17
.200	5.08		



NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .005 (.13 mm) for three-place decimals.
3. Metric equivalents are given for information only.
4. See table II for dimensions B, C, D, and E.

FIGURE 2. Printed wiring test board.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.

TABLE I. Connector, electrical, male adapter, type CS, class b, mounting provision A.

Dash number	Style	Size	Dimensions (inches) 1/				
			A (maximum)	B ±0.007 (0.18)	C	D ±0.010 (0.25)	E
01	17	2				0.120 (3.05)	
02	17	3	2.390 (60.71)	2.130 (54.10)	1.600 (40.64)	0.152 (3.86)	0.265 (6.73)
03	17	4				0.183 (4.65)	
04	23	2				0.120 (3.05)	
05	23	3	2.990 (75.95)	2.730 (69.34)	2.200 (55.88)	0.152 (3.86)	0.265 (6.73)
06	23	4				0.183 (4.65)	
07	29	2				0.120 (3.05)	
08	29	3	3.590 (91.19)	3.330 (84.58)	2.800 (71.12)	0.152 (3.86)	0.265 (6.73)
09	29	4				0.183 (4.65)	
10	35	2				0.120 (3.05)	
11	35	3	4.190 (106.43)	3.930 (99.82)	3.400 (86.36)	0.152 (3.86)	0.265 (6.73)
12	35	4				0.183 (4.65)	
13	41	2				0.120 (3.05)	
14	41	3	4.790 (121.67)	4.530 (115.06)	4.000 (101.60)	0.152 (3.86)	0.265 (6.73)
15	41	4				0.183 (4.65)	
16	47	2				0.120 (3.05)	
17	47	3	5.623 (142.82)	5.363 (136.22)	4.600 (116.84)	0.152 (3.86)	0.265 (6.73)
18	47	4				0.183 (4.65)	

1/ Dimensions are in inches. Metric equivalents are given for information only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.

TABLE II. Printed wiring test board.

Style	Dimensions (inches) 1/			
	B	C	D	E
17	3.390 (86.10)	1.600 (40.64)	.265 (6.73)	2.130 (54.10)
23	3.990 (101.34)	2.200 (55.88)	.265 (6.73)	2.730 (69.34)
29	4.590 (116.58)	2.800 (71.12)	.265 (6.73)	3.330 (84.58)
35	5.190 (131.82)	3.400 (86.36)	.265 (6.73)	3.930 (99.82)
41	5.790 (147.06)	4.000 (101.60)	.265 (6.73)	4.530 (115.06)
47	6.390 (162.23)	4.600 (116.84)	.265 (6.73)	5.363 (136.22)

1/ Millimeters are in parentheses.

REQUIREMENTS

Dimensions and configurations: See figure 1 and table I.

Contacts material: Gilding metal brass in accordance with copper alloy number UNS C21000 of ASTM B36.

Mating receptacle: Shall be in accordance with MIL-DTL-21097/13.

Printed wiring test board: Two-ounce copper one side only, gold plated as specified in IPC-D-275. Board shall conform to IPC-D-275 and MIL-PRF-31032. See figure 2 for the applicable connector size.

Finish: Shall be in accordance with MIL-DTL-21097.

Part or Identifying Number (PIN): M21097/14-(dash number from table I).

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-21097, this document references the following:

MIL-DTL-21097/13
MIL-PRF-31032
ASTM B36
IPC-D-275

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIALS

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA – CC

Review activities:
Army – AR, AT, CR4, MI
Navy – AS, MC, OS

Preparing activity:
DLA - CC

(Project 5935-4505-005)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.