INCH-POUND

MIL-DTL-21097/15G
w/AMENDMENT 2
4 January 2022
SUPERSEDING
MIL-DTL-21097/15G
w/AMENDMENT 1
1 February 2017

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, PRINTED WIRING BOARD MALE ADAPTER, CONTACT SPACING: 0.200, ALTERNATE DUAL ROW, TYPE CS, BLADE CONTACT (NO MOUNTING PROVISION)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-21097.




FIGURE 1. Blade contact type CS alternate dual row contacts.

AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.001	0.03	.155	3.94
.010	0.25	.160	4.06
.015	0.38	.200	5.08
.0245	0.622	.230	5.84
.082	2.08	.280	7.11
.100	2.54	.400	10.16
.106	2.69	.415	10.54
.125	3.18	.460	11.68
.150	3.81		


NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .005 (.13 mm) for three place decimals.
3. Metric equivalents are given for information only.
4. See table I for dimensions.
5. All even numbered contacts to be identified with .047 (1.19 mm) minimum high characters, as shown.

FIGURE 1. Blade contact type CS alternate dual row contacts - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.



Printed wiring board	
Size	T dim
2	.062 (1.57)
3	.093 (2.36)
4	.125 (3.18)



Inches	mm
.002	0.05
.050	1.27
.052	1.32
.093	2.36
.100	2.54
.200	5.08
.300	7.62
.350	8.89
.625	15.88
.895	22.73
4.731	120.17

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ± .005 (.13 mm) for three-place decimals.
3. Metric equivalents are given for information only.
4. See table II for dimensions B and C.

FIGURE 2. Printed wiring test board.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.

TABLE I. Connector, electrical, male adapter, type CS, class b, no mounting provision.

Dash number	Style	Size	Dimensions (inches) 1/ A (maximum)	B	C ±.010 (0.25)
01	17	2	2.070 (52.58)	1.600 (40.64)	0.120 (3.05)
02	17	3			0.152 (3.86)
03	17	4			0.183 (4.65)
04	23	2	2.670 (67.82)	2.200 (55.88)	0.120 (3.05)
05	23	3			0.152 (3.86)
06	23	4			0.183 (4.65)
07	29	2	3.270 (83.06)	2.800 (71.12)	0.120 (3.05)
08	29	3			0.152 (3.86)
09	29	4			0.183 (4.65)
10	35	2	3.870 (98.30)	3.400 (86.36)	0.120 (3.05)
11	35	3			0.152 (3.86)
12	35	4			0.183 (4.65)
13	41	2	4.470 (113.54)	4.000 (101.60)	0.120 (3.05)
14	41	3			0.152 (3.86)
15	41	4			0.183 (4.65)

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.

TABLE I. Connector, electrical, male adapter, type CS, class b, no mounting provision – Continued.

Dash number	Style	Size	Dimensions (inches) 1/ A (maximum)	B	C ±0.010 (0.25)
16	47	2	5.070 (128.78)	4.600 (116.84)	0.120 (3.05)
17	47	3			0.152 (3.86)
18	47	4			0.183 (4.65)

1/ Dimensions are in inches. Metric equivalents are given for information only.

TABLE II. Printed wiring test board.

Style	Dimensions (inches) 1/ B	C
17	3.390 (86.11)	1.600 (40.64)
23	3.990 (101.35)	2.200 (55.88)
29	4.590 (116.59)	2.800 (71.12)
35	5.190 (131.83)	3.400 (86.36)
41	5.790 (147.07)	4.000 (101.60)
47	6.390 (162.31)	4.600 (116.84)

1/ Millimeters are in parentheses.

REQUIREMENTS

Dimensions and configuration: See figure 1, table I, and table II.

Contact material: Gilding metal brass in accordance with copper alloy UNS C21000 of ASTM B36/B36M.

Mating receptacle: Shall be in accordance with MIL-DTL-21097/13.

Printed wiring test board: Two-ounce copper one side only, gold plated in accordance with IPC-2221. Board in accordance with IPC-2221. See figure 2 for the applicable connector size.

Finish: See MIL-DTL-21097.

Part or Identifying Number (PIN): M21097/15-(dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-DTL-21097, this document references the following:

MIL-DTL-21097/13
ASTM B36/B36M
IPC-2221

CONCLUDING MATERIALS

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2022-018)

Review activities:
Army – AR, AT, AV, CR4, MI
Navy – AS, MC, OS, SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:50Z
Check the source to verify that this is the current version before use.