
MILITARY SPECIFICATION SHEET

LOUDSPEAKER, PERMANENT MAGNET (ENCASED, 2-WATT, FUNGUS-, GUNBLAST-, AND IMMERSION-RESISTANT), TYPE LS-454/U

This specification is approved for use by all Departments and Agencies of the Department of Defense

The complete requirements for procuring the loudspeaker described herein shall consist of this document and the latest issue of Specification MIL-L-12632



INCHES	MM
3.19	81.03
4.91	124 71
7.03	178.56


NOTES
1. Dimensions are in inches
2. Metric equivalents (to the nearest 01 mm) are given for general information only and are based upon 1 inch = 25 4 mm
3. Steel clamp firmly clamped on the cord jacket Design optional A strain relief bushing (e g Heyco) is a suitable substitute for the grommet/clamp combination


FIGURE 1 Loudspeaker LS-454/U

Ⓐ denotes changes,

FSC 5965


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:07Z
Check the source to verify that this is the current version before use.





DETAIL A

INCHES	MM
.12	3.03
.25	6.35
.50	12.70
1 38	35.05
4.50	114.30
73.00	1854.20




DETAIL B

NOTES


1 Dimensions are in inches
2 Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25 4 mm
3 Unless otherwise specified tolerance is ± .06 (1 52 mm)
4 Stay cord shall be securely knotted and excess length trimmed
5 Seal stay cord knot with glyptal No 2V3407 as supplied by General Electric Co Inc Schenectady N Y or equal
6 Plug connector shall be type U-229 U conforming to MIL-C-55116
(A) The U-229 U connector used on this item need not be regaged or first article tested if government source inspected or obtained from a government approved vendor's plant for the U-229 U connector Otherwise gages are to be obtained from or approved by US Army Electronics Command, Directorate of Procurement and Production, Engineering Support Division, Gage Engineering Branch (AMSEL-PP-ES-6) Ft Monmouth NJ
7 Cord shall conform to type COS-2123 of MIL-C-3884
8 Skin back ends, twist and solder coat Plug end leads shall be .50 (12 70 mm) long before assembly
9 Connect white conductor to terminal E and black conductor to terminal A of plug U 229 U

FIGURE 2 Cord assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:07Z
Check the source to verify that this is the current version before use.



INCHES	MM
.005	.13
.06	1.52
.159	4.04
.38	9.65
.44	11.18
.66	16.76
.796	20.22
1.19	30.23
1.31	33.27
1.593	40.46
1.62	41.15



ELECTRICAL CHARACTERISTICS
Rated power level 2 watts, ±1 db
Frequency response range 250 to 5000 Hz at rated power flat within 2 db
Reference frequency 1000 Hz
Primary impedance 600 ± 60 Ω
Secondary impedance 8 Ω
Insertion loss 0.5 db, max with 2 watts input at reference frequency
Temperature rise 40° C max above an ambient of 65° C with rated power at 300 Hz
Test voltage 500 volts rms
Duty cycle Continuous
Maximum altitude 10,000 feet
Harmonic distortion Not more than 1 percent at rated power
Polarity Additive, with terminals 2 and 3 connected

NOTES
1. Dimensions are in inches
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm
3. Unless otherwise specified, tolerance is ± .02 (.51 mm)
4. Solder lug terminals No. 18 AWG
5. Markings shall be as shown.

FIGURE 2. Audio transformer

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:07Z
Check the source to verify that this is the current version before use.




FIGURE 4 Schematic diagram and label size

REQUIREMENTS

Design and construction (see figure 1)
Loudspeaker unit - Type LS-445 U of MIL-L-12606
Cabinet - In accordance with MIL-L-12632
Cord assembly - See figure 2
Cord - Type COS-2(23) of MIL-C-3884
Plug - Type U-229 U of MIL-C-55116
Audio transformer - See figure 3
Wiring - See figure 4

Schematic-diagram label In accordance with MIL-L-12632 and figure 4

Frequency response test voltage (rms)
36 0 volts

(1) Marking. See Figure 1.

Custodians
Army - LL
Navy - EC
Air Force - 85

Review activities
Army - EL
Navy -
Air Force - 80 13
DSA - ES

User activities
Army - MI
Navy - MC CG OS
Air Force -

Preparing activity
Army - LL

Agent
DSA - ES

(Project 5965-0141-3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:07Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION: MIL-L-12632/4A LOUDSPEAKER, PERMANENT MAGNET (ENCASED, 2-WATT, FUNGUS-, GENBLAST-, AND IMMERSION-RESISTANT), TYPE LS-454/U

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes" in what way?)*

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

ESC-FM 1068-68

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:07Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: AMSEL- RD-ZS
Fort Monmouth, New Jersey 07703

To detach this form, cut along this line

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:07Z
Check the source to verify that this is the current version before use.