MIL-M-12624C(EL)
AMENDMENT 1
19 September 1972

MILITARY SPECIFICATION

MICROPHONE, RIBBON

(MICROPHONE T-23( ))

This amendment forms part of Military Specification MIL-M-12624C(EL), 11 February 1972.

Page 1

2.1: Delete

"MIL-T-152	Treatment, Moisture-and-Fungus-Resistant, of Communication, Electronic, and Associated Electrical Equipment
MIL-V-173	Varnish, Moisture-and-Fungus-Resistant (For the Treatment of Communications, Electronic, and Associated Electrical Equipment)"

Page 4

3.7.1: Delete and substitute:

"3.7.1 Fungus.- The microphone shall be resistant to fungus growth when tested in accordance with 4.16".

Page 6

Add the following paragraphs:

"3.13 Rain.- After testing as specified in 4.17, the microphone shall meet the performance requirement of 3.4.4."

"3.14 Wind.- The microphone shall meet the requirement of 3.4.5 after being subjected to the wind test (see 4.18)."

FSC 5895

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:05Z
Check the source to verify that this is the current version before use.

Page 7 and 8

Table: Delete and substitute:

Table II Order of Environmental Testing

Inspection (Note 1)	Number of Units				
	Four		Nine		
	2 units	2 units	3 units	3 units	3 units
Non-damaging (Note 2)					
Low temperature	1		1		
High temperature	2		2		
Rain	3		3		
Wind	4		4		
Potentially damaging					
Humidity (moisture-resistance)	5			1	
Bounce (vibration)		1			1
Shock; ballistic		2			2
Fungus		3			3

Note 1: Other inspections may precede, follow, or be interspersed between the non-damaging tests.

Note 2: The order of non-damaging tests and the choice of which units are subjected to the non-damaging tests may be varied if convenient, except that the bounce (vibration) test shall be performed on the same units used for the shock test.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:05Z
Check the source to verify that this is the currentversion before use.

Page 10 and 11

Table V: Delete and substitute:

Table V Group C Inspection

Inspection (Note 1)	Reqt Para	Insp Para
Group 1		
Low temperature	3.10.1.1	4.10.1
High temperature	3.10.1.2	4.10.2
Humidity (moisture-resistance)	3.10.2	4.11
Rain	3.13	4.17
Wind	3.14	4.18
Group 2		
Bounce (vibration)	3.10.3	4.12
Shock; ballistic	3.10.3	4.13
Fungus	3.7.1	4.16
Group 3		
Equipment verification reivew (Note 2)	3.2	4.5

Note 1: The order of inspection shall be in accordance with table II.
Note 2: Equipment verification review shall only be performed on the first production lot.

Page 15

4.10.1, line 4: Delete "-34.4°C (-30°F)" and substitute "-45.5°C(-50°F)" and delete "-31.7°C (-25°F)" and substitute "-40°C (-40°F)".

Page 16

Add the following paragraphs:

"4.16 Fungus test.- The microphone shall be tested in accordance with Method 508, Procedure I of MIL-STD-810. Spraying shall include parts and materials on and under the cover, and the interior of the microphone case. The microphone shall remain in an open condition during the test. Operation is not required (see 3.7.1)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:05Z
Check the source to verify that this is the current version before use.

Page 10 and 11

Table V: Delete and substitute:

Table V Group C Inspection

Inspection (Note 1)	Reqt Para	Insp Para
Group 1		
Low temperature	3.10.1.1	4.10.1
High temperature	3.10.1.2	4.10.2
Humidity (moisture-resistance)	3.10.2	4.11
Rain	3.13	4.17
Wind	3.14	4.18
Group 2		
Bounce (vibration)	3.10.3	4.12
Shock; ballistic	3.10.3	4.13
Fungus	3.7.1	4.16
Group 3		
Equipment verification reivew (Note 2)	3.2	4.5

Note 1: The order of inspection shall be in accordance with table II.
Note 2: Equipment verification review shall only be performed on the first production lot.

Page 15

4.10.1, line 4: Delete "-34.4°C (-30°F)" and substitute "-45.5°C(-50°F)" and delete "-31.7°C (-25°F)" and substitute "-40°C (-40°F)".

Page 16

Add the following paragraphs:

"4.16 Fungus test.- The microphone shall be tested in accordance with Method 508, Procedure I of MIL-STD-810. Spraying shall include parts and materials on and under the cover, and the interior of the microphone case. The microphone shall remain in an open condition during the test. Operation is not required (see 3.7.1)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:05Z
Check the source to verify that this is the current version before use.