MILITARY SPECIFICATION SHEET

BATTERY, STORAGE, LEAD-ACID

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the batteries described herein shall consist of this document and the latest issue of specification MIL-B-83769.

Military part numbers	-M83769/6-1 (see Figures 1 & 2) Not For Navy Use
	-M83769/6-2 (see Figures 3 & 4) For Navy Use
Nominal voltage	-24 volts
Maximum weight	-80 pounds (wet)
Capacity at 1-hour rate	-31 AH
Discharge rate for cell terminal post, intercell connectors, terminal connectors	-330 amps
Dimensions and configurations	-see Figures 1 through 4
Disconnect receptacle	-Figure 2 of MIL-B-83769

Notes:

1. Dimensions in inches, tolerance $\pm$ 0.063 inches unless otherwise specified.
2. Draft angles allowed in conformance with commercial die casting practices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:40Z
Check the source to verify that this is the current version before use.

M83769/6-1 shall conform to MIL-B-83769 except as modified by the following:

3.0 REQUIREMENTS

3.4.13 Change to read: Filler caps. Filler caps shall incorporate baffles or other means of minimizing the splashing of electrolyte. The caps shall be threaded for mating with cell cover filling holes described in 3.4.12.

(C) 3.4.14 Interior and exterior finish. The exterior of metallic battery containers, covers, the interior and exterior of metallic disconnect receptacles and screws, except threaded areas, shall be thoroughly covered with an acid resistant coating which shall meet the requirements of 3.5.1 when subjected to the tests of 4.6.1. If the basic case material will meet the requirements of 3.5.1, acid resistant coating is not required. Each battery shall have four CAUTION labels on the outside, one of each of the three sides that do not contain the receptacle and one on the container cover. Each CAUTION label shall be 4 inches by 7 inches and shall contain a yellow background color and red letters 1/2 inch high:

CAUTION


FOR GROUND USE ONLY
DO NOT INSTALL IN AIRCRAFT

The colors shall conform to FED-STD-595, colors 13432 or 13538, and 11105. The label material, lettering and method of attachment shall be of a permanent nature for the life of the battery.

3.5.13 Altitude. Delete.

3.5.17 Life cycling. Delete requirement for inverted operation (last two sentences in paragraph).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:40Z
Check the source to verify that this is the current version before use.



Ⓒ CONTAINER MATERIAL: NON-METALLIC, ALUMINUM, STEEL OR ALUMINUM ALLOY DIE CASTING PER QQ-A-591

Part No.
M83769/6-1

NOT FOR NAVY USE

Figure 1. Battery assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:40Z
Check the source to verify that this is the current version before use.




Figure 2. Container cover for Part No. M83769/6-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:40Z
Check the source to verify that this is the current version before use.

M83769/6-2 shall conform to MIL-B-83769 except as modified by the following:

(C) 3.4.14 Interior and exterior finish. The exterior of metallic battery containers, covers, the interior and exterior of metallic disconnect receptacles and screws, except threaded areas, shall be thoroughly covered with an acid resistant coating which shall meet the requirements of 3.5.1 when subjected to the tests of 4.6.1.


3.5.17 Life cycling. Batteries, when cycled in accordance wth 4.6.18, shall provide no less than one hundred thirty (130) cycles of charge and discharge in an ambient temperature of $27^{\circ} \pm 5^{\circ}C$ with the battery exposed on all four sides and the top (lid) off to allow free air circulation. During the life test, inability to meet the 1 hour rate discharge requirement for three (3) consecutive discharges shall constitute a failure. No reduction of capacity to less than 100 percent of that specified in Table I for cycles 126 thru 130 shall be permitted. During life cycling, batteries shall operate normally in an upright position, but shall be inverted for 2.5 minutes of discharge during cycle one hundred thirty (130). The battery shall not exhibit an excessive loss of electrolyte or a change in battery voltage in excess of 0.5 volt as a result of the inversion during cycle one hundred thirty (130).

(C) 4.6.18.1 The charges preceding cycles 1 through 7 and 126 through 130 shall be in accordance with 4.5.1.3.1. The remaining charges during cycling shall be in accordance with 4.5.1.3.2.

4.6.18.2 Cycling. Cycling shall consist of a series of cycles of charge and discharge as specified below, all of which shall be counted as life cycles. Cycling shall be as follows:

Cycle Number	Test	Rate
13	1-hour at $27^{\circ} \pm 5^{\circ}C$	1.0 C
4	5-minute at $27^{\circ} \pm 5^{\circ}C$	6.0 C
5	5-hour at $27^{\circ} \pm 5^{\circ}C$	0.2 C
6	5-minute at $-18^{\circ} \pm 2^{\circ}C$	6.0 C
7-125	1-hour at $27^{\circ} \pm 5^{\circ}C$	1.0 C
126	5-minute at $27^{\circ} \pm 5^{\circ}C$	6.0 C
127	2-hour at $27^{\circ} \pm 5^{\circ}C$	0.5 C
128	5-minute at $27^{\circ} \pm 5^{\circ}C$	6.0 C
129	2-hour at $27^{\circ} \pm 5^{\circ}C$	0.5 C
130	5-minute at $27^{\circ} \pm 5^{\circ}C$	6.0 C

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:40Z
Check the source to verify that this is the current version before use.



Ⓒ MATERIAL: NON-METALLIC, ALUMINUM, STEEL OR ALUMINUM ALLOY DIE CASTING PER QQ-A-591

Part No.
M83769/6-2 Ⓒ

FOR NAVY USE

Figure 3. Battery assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:40Z
Check the source to verify that this is the current version before use.




Figure 4. Container cover for Part No. M83769/6-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:40Z
Check the source to verify that this is the current version before use.

During cycles 7 thru 125, the batteries shall not require water additions more than once in four (4) consecutive cycles. During life cycle one hundred thirty (130), when the battery is subjected to the five (5) minute discharge, the battery shall be inverted during the last 2.5 minutes of discharge.

International standardization. Certain provisions of this specification are the subject of International Standardization Agreements (ASCC AIR STD 12/15 and STANAG 3514AE). When revision or cancellation of this standard is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels, including department standardization offices, if required.

Custodians:
Air Force - 99
Army - ER
Navy - AS

Preparing Activity:
Navy - AS
(Project No. 6140-0572-6)

Review Activities:
Air Force - 11, 80
Army - AV
DLA - GS

NOTICE: Review/user information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DoDISS.

☆U.S. GOVERNMENT PRINTING OFFICE: 1983 — 605-034/2170

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:40Z
Check the source to verify that this is the current version before use.